

#### MATERIAL SAFETY DATA SHEET

### **ORANGE**

 Version Number 1.1
 Page 1 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY : Product Stewardship (770) 271-5902

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : ORANGE
Product code : CC10031020
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
2-Naphthalenecarboxylic acid,	7585-41-3	1 - 5
4-[(5-chloro-4-methyl-2-sulfophenyl)azo]-3-		
hydroxy-, barium salt (1:1)		
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

# 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.



#### MATERIAL SAFETY DATA SHEET

# **ORANGE**

 Version Number 1.1
 Page 2 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

**Chronic exposure** : Refer to Section 11 for Toxicological Information.

Medical Conditions Aggravated by Exposure: : None known.

#### 4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

### 5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not relevant

Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

: None

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.

#### 7. HANDLING AND STORAGE



### MATERIAL SAFETY DATA SHEET

# ORANGE

Page 3 of 8 Version Number 1.1 Print Date 11/10/2011 Revision Date 02/12/2003

Handling Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation.

Keep containers dry and tightly closed to avoid moisture absorption Storage

and contamination. Keep in a dry, cool place.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection Safety glasses with side-shields.

Hand protection Protective gloves.

Skin and body protection Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene

Considerations

Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures

appropriate exhaust ventilation at machinery.

Exposure limit(s)



### MATERIAL SAFETY DATA SHEET

# **ORANGE**

 Version Number 1.1
 Page 4 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

Components	Value	Exposure time	Exposure type	List:
2-Naphthalenecarboxy	0.5 mg/m3	PEL:	as Ba	OSHA Z1
lic acid,				
4-[(5-chloro-4-methyl-				
2-sulfophenyl)azo]-3-h				
ydroxy-, barium salt				
(1:1)				
2-Naphthalenecarboxy	0.5 mg/m3	Time Weighted Average		ACGIH
lic acid,		(TWA):		
4-[(5-chloro-4-methyl-				
2-sulfophenyl)azo]-3-h				
ydroxy-, barium salt				
(1:1)	10 / 0	TT: XXX : 1 . 1 . 1		A COTT
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
Careram careonate	15 mg/m3	PEL:	Total dust.	OSHA Z1
Calcium carbonate	5 mg/m3	Recommended exposure	Respirable.	NIOSH
Curerum cureenate	3 mg/ms	limit (REL):	respiration.	1,10511
	10 mg/m3	Recommended exposure	Total	NIOSH
		limit (REL):		
	5 mg/m3	Recommended exposure	Respirable.	NIOSH
		limit (REL):		
	10 mg/m3	Recommended exposure	Total	NIOSH
		limit (REL):		
	10 mg/m3	Recommended exposure	Total	NIOSH
		limit (REL):		
	5 mg/m3	Recommended exposure	Respirable.	NIOSH
		limit (REL):		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Quartz	0.05	Time Weighted Average	Respirable dust.	ACGIH
	mg/m3	(TWA):		
Quartz	0.1 mg/m3	PEL:	Respirable dust.	OSHA
	0.3 mg/m3	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Evaporation rate : Not applicable. Appearance : Pellets Specific Gravity : Not determined : Not established Color : ORANGE Bulk density Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not applicable: Not applicable : Not determined Vapor density Boiling Point: : Not applicable pН

Water solubility : Insoluble



#### MATERIAL SAFETY DATA SHEET

### **ORANGE**

 Version Number 1.1
 Page 5 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

### 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

 $: \quad Carbon \ dioxide \ (CO2), \ carbon \ monoxide \ (CO), \ oxides \ of \ nitrogen$ 

(NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
7585-41-3	2-Naphthalenecarboxylic acid, 4-[(5-chloro-4-methyl-2-s ulfophenyl)azo]-3-hydrox y-, barium salt (1:1)	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

### Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	1

#### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

#### NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.



#### MATERIAL SAFETY DATA SHEET

### **ORANGE**

 Version Number 1.1
 Page 6 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

### **Additional Health Hazard Information:**

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

#### 12. ECOLOGICAL INFORMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix

of the polymer.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the matrix

of the polymer.

Additional advice : No data available.

### 13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastics the product can be recycled. Where

possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

# 14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.

IMO / IMDG : Refer to specific regulation.

### 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)



### MATERIAL SAFETY DATA SHEET

# **ORANGE**

 Version Number 1.1
 Page 7 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

Chemical Name	CAS-No.	% in Product	RQ for	RQ for
			component	Mixture/Prod
				uct
2-Naphthalenecarboxylic	7585-41-3	3.1967	1,000 lbs	31,282 LB
acid,				
4-[(5-chloro-4-methyl-2-sul				
fophenyl)azo]-3-hydroxy-,				
barium salt (1:1)				

California Proposition : WARNING! This product contains a chemical known to the State of

65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
BARIUM COMPOUNDS [EXCEPT BASO4]	7585-41-3	03.19

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No. 7585-41-3

DSL : DSL status has not been determined. Quantity use in Canada may be

restricted by regulations.

National Inventories:

Australia AICS : Not determined.

China IECS : Not determined.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.



### MATERIAL SAFETY DATA SHEET

# **ORANGE**

 Version Number 1.1
 Page 8 of 8

 Revision Date 02/12/2003
 Print Date 11/10/2011

Philippines PICCS : Not determined.

# 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.