

MATERIAL SAFETY DATA SHEET

PG 31132 SI PP

Version Number 1.0 Revision Date 02/10/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 31132 SI PP
Product code	:	CC10031132
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Aluminum	7429-90-5	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





PG 31132 SI PP Version Number 1.0 Page 2 of 6 Revision Date 02/10/2003 Print Date 11/10/2011 **Medical Conditions** : None known. Aggravated by Exposure: 4. FIRST AID MEASURES Inhalation Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Do not induce vomiting without medical advice. When symptoms Ingestion : persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. **5. FIRE-FIGHTING MEASURES** Flash point : Not applicable Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media : Carbon dioxide blanket, Water spray, dry powder, foam. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None • Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat · only in areas with appropriate exhaust ventilation.

MATERIAL SAFETY DATA SHEET

PG 31132 SI PP



Version Number 1.0 Revision Date 02/10/2003		Page 3 of 6 Print Date 11/10/2011
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPO	SUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Aluminum	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
	5 mg/m3	Time Weighted Average	Welding fume. as Al	ACGIH
		(TWA):		
Aluminum	15 mg/m3	PEL:	Total dust. as Al	OSHA Z1
	5 mg/m3	PEL:	Respirable dust. as Al	OSHA Z1
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Mica	20 mppcf	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average	Dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable



MATERIAL SAFETY DATA SHEET

PG 31132 SI PP

Version Number 1.0 Revision Date 02/10/2003 Page 4 of 6 Print Date 11/10/2011

10. STABILITY AND REACTIVITY			
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.		
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.		
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.		

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7429-90-5	Aluminum	Irritant	Skin, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION				
Persistence and degradability	: Not readily biodegradable.			
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.			
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.			
Additional advice	: No data available.			
	13. DISPOSAL CONSIDERATIONS			
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia			



MATERIAL SAFETY DATA SHEET

PG	31	132	51	PP
FG	JI	132	J	ГГ

sion Number 1.0 ision Date 02/10/2003			Page 5 0 Print Date 11/10/20	
has the responsibility for proper waste classification, trans and disposal in accordance with applicable federal, state/p and local regulations.				
	14. TRANSPORT	INFORMATION		
U.S. DOT Classification	: Refer to specific	regulation.		
ICAO/IATA	: Refer to specific	regulation.		
IMO / IMDG	: Refer to specific	regulation.		
	15. REGULATOR	Y INFORMATION		
US Regulations:				
OSHA Status	: Classified as haz	ardous based on composition	nents.	
TSCA Status	: All components Inventory.	: All components of this product are listed on or exempt from the TSCA		
US. EPA CERCLA Hazardo	us Substances (40 CFR 3	02)		
Not applicable				
California Propositio 65	n : This product doe	es not contain a substance	e listed by California Prop 65.	
SARA Title III Section 302	Extremely Hazardous Sul	ostance		
Not applicable				
SARA Title III Section 313	Foxic Chemicals:			
Chemical Name		CAS-No.	Weight %	
ALUMINUM (FUM	E OR DUST)	7429-90-5	05.51	
Canadian Regulations:				
WHMIS Classification	on : D2B			
WHMIS Ingredient D	isclosure List			

MATERIAL SAFETY DATA SHEET



PG 31132 SI PP Page 6 of 6 Version Number 1.0 Print Date 11/10/2011 Revision Date 02/10/2003 CAS-No. 7429-90-5 12001-26-2 DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. National Inventories: Australia AICS : Listed. : Listed. China IECS Europe EINECS : Not determined. Japan ENCS Not determined. : Korea KECI : Listed. **Philippines PICCS** : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.