PolvOne

MATERIAL SAFETY DATA SHEET JONSERED RED

Version Number 1.1 Revision Date 10/26/2006

Product Use

Page 1 of 6 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	JONSERED RED
Product code	:	CC10032248
Chemical Name	:	Mixture
CAS-No.	:	Mixture

: Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Benzenesulfonic acid,	5160-02-1	10 - 30
5-chloro-2-[(2-hydroxy-1-naphthalenyl)azo]-		
4-methyl-, barium salt (2:1)		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eves	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	 eyes. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET JONSERED RED

Version Number 1.1 Revision Date 10/26/2006 Page 2 of 6 Print Date 11/25/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET JONSERED RED

Version Number	er 1.1
Revision Date	10/26/2006

Storage

Page 3 of 6 Print Date 11/25/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment not	rmally required.
Eye/Face Protection	: Safety glasses with side-shields.	
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved clothing.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Handle in accordance with good industrial hygier Wash hands before breaks and at the end of work	• 1
Engineering measures	: Heat only in areas with appropriate exhaust venti appropriate exhaust ventilation at machinery.	ilation. Provide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Benzenesulfonic acid,	0.5 mg/m3	Time Weighted Average	as Ba	ACGIH
5-chloro-2-[(2-hydrox		(TWA):		
y-1-naphthalenyl)azo]-				
4-methyl-, barium salt				
(2:1)				
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	20 mg/m3	Short Term Exposure Limit	as Ti	MX OEL
	_	(STEL):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 RED
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable

10. STABILITY AND REACTIVITY

3/6

MATERIAL SAFETY DATA SHEET JONSERED RED

Version Number 1.1 Revision Date 10/26/2006 Page 4 of 6 Print Date 11/25/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
5160-02-1	Benzenesulfonic acid, 5-chloro-2-[(2-hydroxy-1- naphthalenyl)azo]-4-methy 1-, barium salt (2:1)	Irritant	Eyes, Skin.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.



MATERIAL SAFETY DATA SHEET JONSERED RED

sion Number 1.1 ision Date 10/26/2006		Page 5 Print Date 11/25/2
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	:	No data available
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ex	trem	ely Hazardous Substance
		fied under this section, this product is Not Applicable under this regula

PolyOne

MATERIAL SAFETY DATA SHEET JONSERED RED

on Number 1.1 sion Date 10/26/2006				Page Print Date 11/25	
SARA Title III Section 313 Tox	ic C	Chemicals:			
Unless specific chemicals are id	enti	fied under this section, t	his product is Not	Applicable under this regu	ıla
Chemical Name			CAS-No.	Weight %	
BARIUM COMPOUNDSBA [EXCEPT BASO4]	RIU	JM COMPOUNDS	5160-02-1	10.00 - 30.00	
Canadian Regulations:				I	
Canadian Regulations.					
National Pollutant Releas	se Iı	ventory (NPRI)			
Not applicable					
WHMIS Classification	:	Not controlled.			
DSL	:	All components of thi Substances List (DSL)		ne Canadian Domestic	
National Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			
Japan ENCS	:	Listed			
Korea KECI	:	Listed			
Philippines PICCS	:	Listed			
		16. OTHER INFOR	MATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.