

MATERIAL SAFETY DATA SHEET

PG 32611 PEARL GD PP

Version Number 1.0 Revision Date 03/05/2003 Page 1 of 6 Print Date 11/10/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 32611 PEARL GD PP
Product code	:	CC10032611
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	1 - 5
Mica	12001-26-2	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

PG 32611 PEARL GD PP

	No. 1 and a
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
Hazards	. 1000
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

PG 32611 PEARL GD PP

Version Number 1.0 Revision Date 03/05/2003 Page 3 of 6 Print Date 11/10/2011

Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.	
8. EXPOSU		RE CONTROLS / PERSONAL PROTECTION	
Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields.	
Hand protection	:	Protective gloves.	
Skin and body protection	:	Long sleeved clothing.	
Additional Protective Measures	:	Safety shoes.	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Mica	3 mg/m3	Time Weighted Average	Total dust.	ACGIH
	_	(TWA):		
Mica	20 mppcf	PEL:	Total dust.	OSHA

Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets YELLOW Very faint Not determined Not applicable Insoluble 	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	 Not applicable. Not determined Not established Not applicable Not applicable Not applicable
	10. STABILITY AN	ID REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		



MATERIAL SAFETY DATA SHEET

PG 32611 PEARL GD PP

	003			Print Date 11/10/2				
		decomposition	, do not overheat.					
Incompatible Mater	ials	: Incompatible v	Incompatible with strong acids and oxidizing agents.					
Hazardous decompo products	osition			xide (CO), oxides of nitrogen d smoke are all possible.				
11. TOXICOLOGICAL INFORMATION								
This mixture has no health data for the in				re effects listed are based on exis				
<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics								
CAS-No.		emical Name	Effect	Target Organ				
1309-37-1	Iron oxi	de	Systemic effects	Respiratory system.				
12001-26-2	Mica		Systemic effects	Respiratory system.				
		12. ECOLOGIC	AL INFORMATION					
Dereistance and dee	radability							
Persistence and deg	radability	: Not readily bio	degradable.					
Environmental Toxi	city	: Chemicals are of the polymer		s they are bound within the matrix				
Bioaccumulation Po	otential	: Chemicals are a of the polymer		s they are bound within the matrix				
Additional advice		: No data availal	ble.					
		13. DISPOSAL (CONSIDERATIONS					
		T 1 1						
Product		possible, recyc generator of wa classification, t	ling is preferred to dis aste material has the re	et can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.				
	aging	 possible, recyc generator of wa classification, t applicable fede Recycling is pr has the response 	ling is preferred to dis aste material has the re- transportation and disp eral, state/provincial ar- referred when possible sibility for proper was accordance with appl	posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.				
	aging	 possible, recyc generator of wa classification, t applicable fede Recycling is pr has the respons and disposal in and local regul 	ling is preferred to dis aste material has the re- transportation and disp eral, state/provincial ar- referred when possible sibility for proper was accordance with appl	posal or incineration. The esponsibility for proper waste bosal in accordance with nd local regulations. . The generator of waste material te classification, transportation				
Contaminated packa		 possible, recyc generator of wa classification, t applicable fede Recycling is pr has the respons and disposal in and local regul 	ling is preferred to dis aste material has the re- transportation and disp eral, state/provincial and referred when possible sibility for proper waster accordance with appli- ations.	posal or incineration. The esponsibility for proper waste bosal in accordance with nd local regulations. . The generator of waste material te classification, transportation				
Product Contaminated packa U.S. DOT Classifica ICAO/IATA		 possible, recyc generator of wa classification, t applicable fede Recycling is pr has the respons and disposal in and local regul 14. TRANSPOR	ling is preferred to dis aste material has the re- transportation and disp eral, state/provincial ar referred when possible sibility for proper wast accordance with appl ations. T INFORMATION ic regulation.	posal or incineration. The esponsibility for proper waste bosal in accordance with nd local regulations. . The generator of waste material te classification, transportation				



MATERIAL SAFETY DATA SHEET

PG 32611 PEARL GD PP

Version Number 1.0 Revision Date 03/05/2003 Page 5 of 6 Print Date 11/10/2011

IMO / IMDG	:	Refer to specific regulation.				
	15	3. REGULATORY INFORMATION				
US Regulations:						
OSHA Status	:	Classified as hazardous based on components.				
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous Substances (40 CFR 302)						
Not applicable						
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.				
SARA Title III Section 302 Ext	rem	ely Hazardous Substance				
Not applicable						
SARA Title III Section 313 Tox	tic C	Chemicals:				
	N	ot applicable				
Canadian Regulations:						
WHMIS Classification	:	Not controlled.				
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:						
Australia AICS	:	Listed.				
China IECS	:	Listed.				
Europe EINECS	:	Not determined.				
Japan ENCS	:	Not determined.				
Korea KECI	:	Listed.				



MATERIAL SAFETY DATA SHEET

PG 32611 PEARL GD PP

Version Number 1.0 Revision Date 03/05/2003 Page 6 of 6 Print Date 11/10/2011

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.