

MATERIAL SAFETY DATA SHEET

TL. DARK PUPRLE

Version Number 1.0 Revision Date 05/08/2003 Page 1 of 6 Print Date *11/11/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TL. DARK PUPRLE
Product code	:	CC10036108
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	0.1 - 1

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.		
88			



MATERIAL SAFETY DATA SHEET

TL. DARK PUPRLE

Version Number 1.0 Page 2 of 6 Revision Date 05/08/2003 Print Date 11/11/2011 **4. FIRST AID MEASURES** Inhalation Move to fresh air in case of accidental inhalation of fumes from ÷ overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. Ingestion Do not induce vomiting without medical advice. When symptoms : persist or in all cases of doubt seek medical advice. Eyes Rinse immediately with plenty of water, also under the eyelids, for at : least 15 minutes. If eye irritation persists, seek medical attention. Skin Wash off with soap and plenty of water. If skin irritation persists seek : medical attention. **5. FIRE-FIGHTING MEASURES** Flash point Not applicable : Flammable Limits Upper explosion limit Not applicable : Lower explosion limit Not applicable : Autoignition temperature Not relevant : Suitable extinguishing media Carbon dioxide blanket, Water spray, dry powder, foam. : Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in positive : Procedures pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion None · Hazards 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should not : be allowed to enter drains, water courses or the soil. Clean up promptly by sweeping or vacuum. Package all material in Methods for cleaning up : plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. 7. HANDLING AND STORAGE Handling Take measures to prevent the build up of electrostatic charge. Heat : only in areas with appropriate exhaust ventilation. Storage Keep containers dry and tightly closed to avoid moisture absorption ·



MATERIAL SAFETY DATA SHEET

TL. DARK PUPRLE

Ad contamination. Keep in a CONTROLS / PERSONAL o personal respiratory protect afety glasses with side-shield rotective gloves. ong sleeved clothing. afety shoes. andle in accordance with goo lash hands before breaks and eat only in areas with approp popropriate exhaust ventilation Exposure time Time Weighted Average (TWA): PEL:	PROTECTION tive equipment normally restricted industrial hygiene and satisticate the end of workday. riate exhaust ventilation. Hat machinery. Exposure type Total dust.	fety practice.		
o personal respiratory protect afety glasses with side-shield rotective gloves. ong sleeved clothing. afety shoes. andle in accordance with goo Yash hands before breaks and eat only in areas with approp popropriate exhaust ventilation <u>Exposure time</u> <u>Time Weighted Average</u> (TWA):	tive equipment normally re s. d industrial hygiene and sat at the end of workday. riate exhaust ventilation. F at machinery. Exposure type Total dust.	fety practice. Provide List: ACGIH		
afety glasses with side-shield rotective gloves. ong sleeved clothing. afety shoes. andle in accordance with goo 'ash hands before breaks and eat only in areas with approp popropriate exhaust ventilation <u>Exposure time</u> Time Weighted Average (TWA):	s. d industrial hygiene and sat at the end of workday. riate exhaust ventilation. F at machinery. Exposure type Total dust.	fety practice. Provide List: ACGIH		
rotective gloves. ong sleeved clothing. afety shoes. andle in accordance with goo Vash hands before breaks and eat only in areas with approp opropriate exhaust ventilation <u>Exposure time</u> Time Weighted Average (TWA):	d industrial hygiene and sat at the end of workday. riate exhaust ventilation. H at machinery. Exposure type Total dust.	Provide List: ACGIH		
ong sleeved clothing. afety shoes. andle in accordance with goo Yash hands before breaks and eat only in areas with approp opropriate exhaust ventilation <u>Exposure time</u> Time Weighted Average (TWA):	at the end of workday. riate exhaust ventilation. F at machinery. Exposure type Total dust.	Provide List: ACGIH		
afety shoes. andle in accordance with goo Vash hands before breaks and eat only in areas with approp popropriate exhaust ventilation <u>Exposure time</u> Time Weighted Average (TWA):	at the end of workday. riate exhaust ventilation. F at machinery. Exposure type Total dust.	Provide List: ACGIH		
andle in accordance with goo Yash hands before breaks and eat only in areas with approp popropriate exhaust ventilation <u>Exposure time</u> Time Weighted Average (TWA):	at the end of workday. riate exhaust ventilation. F at machinery. Exposure type Total dust.	Provide List: ACGIH		
Yash hands before breaks and eat only in areas with approp opropriate exhaust ventilation Exposure time Time Weighted Average (TWA):	at the end of workday. riate exhaust ventilation. F at machinery. Exposure type Total dust.	Provide List: ACGIH		
Exposure time Time Weighted Average (TWA):	at machinery. Exposure type Total dust.	List: ACGIH		
Time Weighted Average (TWA):	Total dust.	ACGIH		
Time Weighted Average (TWA):	Total dust.	ACGIH		
Time Weighted Average (TWA):	Total dust.			
		OSHA Z1		
	OPERTIES			
CAL AND CHEMICAL PR				
_				
		applicable.		
	Specific Gravity : Not determin Bulk density : Not establishe			
	Vapor pressure: Not applicableVapor density: Not applicablepH: Not applicable			
-				
uble	. 1014	ipplicable		
TABILITY AND REACTI	VITY			
able.				
'ill not occur.				
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.				
ecomposition, do not overhea	Incompatible Materials : Incompatible with strong acids and oxidizing agents.			
t V	table. Vill not occur. Leep away from oxidizing age	table. Vill not occur. Leep away from oxidizing agents and open flame. To av		



MATERIAL SAFETY DATA SHEET

TL. DARK PUPRLE

Version Number 1.0 Revision Date 05/08/2003 Page 4 of 6 Print Date *11/11/2011*

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No. Chemical Name OSHA IARC NTP					
	CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	:	No data available.
	1	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material



MATERIAL SAFETY DATA SHEET

TL. DARK PUPRLE

sion Number 1.0 ision Date 05/08/2003	Page 5 0 Print Date 11/11/20
	has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
	15. REGULATORT INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
Not applicable	
California Proposition	This product does not contain a substance listed by California Prop 65.
65	
SARA Title III Section 302 B	Extremely Hazardous Substance
Not applicable	
SARA Title III Section 313 7	oxic Chemicals:
Not applicable	
Canadian Regulations:	
WHMIS Classificatio	n : D2B
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	



MATERIAL SAFETY DATA SHEET

TL. DARK PUPRLE

Version Number 1.0 Revision Date 05/08/2003 Page 6 of 6 Print Date 11/11/2011

Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Listed.
Korea KECI	: Listed.
Philippines PICCS	: Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.