

MATERIAL SAFETY DATA SHEET **GOLD**

Version Number 1.1 Revision Date 03/31/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone:Emergency telephone:number | Product Stewardship (440) 930-1395 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--------------------------------------|---|
| Product name : | GOLD |
| Product code : | CC10036397 |
| Chemical Name : | Mixture |
| CAS-No. : | Mixture |
| Product Use : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|------------|------------|----------|
| Iron oxide | 1309-37-1 | 1 - 5 |
| Mica | 12001-26-2 | 5 - 10 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---|---|
| Acute exposure | |
| Inhalation | : Particulates, like other inert materials can be mechanically irritating. If overheated or burnt, the polymer releases formaldehyde. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Particulates, like other inert materials can be mechanically irritating. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |
| Medical Conditions Aggravated by Exposure: | : None known. |



MATERIAL SAFETY DATA SHEET **GOLD**

Version Number 1.1 Revision Date 03/31/2004 Page 2 of 6 Print Date 11/14/2011

| | 4. FIRST AID MEASURES |
|--|--|
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists se medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. |
| Special Fire Fighting Procedures Unusual Fire/Explosion Hazards | Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May burn with invisible flame. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |
| Handling | : Take measures to prevent the build up of electrostatic charge. Oper container only in a well-ventilated area. Heat only in areas with |



MATERIAL SAFETY DATA SHEET **GOLD**

| ion Number 1.1 sion Date 03/31/2004 | | | | Print Da | Page 3 ate 11/14/ |
|---|---------------------|--|--|---|--------------------------|
| | aj | ppropriate exhaust | ventilation. | | |
| Storage | | Keep containers dry nd contamination. | | closed to avoid moisture lry, cool place. | absorption |
| 8. F | XPOSURE | CONTROLS / PE | RSONAL | PROTECTION | |
| Respiratory protection | V ir p | When temperatures enadequate to mainta | exceed 230 in concentr respirator. | ive equipment normally re °C (446°F) and ventilatio rations below exposure lin Air purifying respirators | n is nits, use a |
| Eye/Face Protection | | afety glasses with s or abnormal process | | . Wear face-shield and pams. | rotective sui |
| Hand protection | : P | rotective gloves. | | | |
| Skin and body protection | : L | ong sleeved clothin | g. | | |
| Additional Protective Measures | : S | afety shoes. | | | |
| General Hygiene Considerations | | | | l industrial hygiene and sa at the end of workday. | fety practic |
| Engineering measures Exposure limit(s) | | leat only in areas with a peropriate exhaust v | | iate exhaust ventilation. | Provide |
| Components | Value | Exposure ti | me | Exposure type | List: |
| Iron oxide | 5 mg/m3 | Time Weighted (TWA): | | Dust and fume. as Fe | ACGIH |
| Mica | 20 mppcf 3 mg/m3 | PEL: Time Weighted (TWA): | Average | Total dust. Respirable fraction. | OSHA ACGIH |
| | 9. PHYSI | CAL AND CHEM | CAL PRO | DPERTIES | |
| Form | : Solic | | Evapo | ration rate : Not : | applicable determined |
| Appearance Color | : Pene | ' | Bulk d | 5 | established |
| Odor | : form | aldehyde | Vapor | pressure : Not | applicable |
| Melting point/range | | determined | | | applicable |
| Boiling Point: Water solubility | : Not a : Insol | applicable luble | pН | : Not a | applicable |
| | 10. 5 | STABILITY AND | REACTIV | /ITY | |
| | | | | | |



MATERIAL SAFETY DATA SHEET **GOLD**

Version Number 1.1 Revision Date 03/31/2004

Page 4 of 6 Print Date 11/14/2011

| Stability | : | Stable. |
|----------------------------------|---|--|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Maintain polymer temperature below 230°C (446°F). Avoid prolonged exposure at or above recommended processing temperature. |
| Incompatible Materials | : | Incompatible with strong oxidizers and with strong acids and bases (decomposes to form formaldehyde). At melt temperatures, acetal resins are incompatible with halogenated polymers such as vinyl (PVC) and any elastomers containing any halogenated polymers. At processing conditions, these materials are mutually destructive and involve rapid degradation. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume well above threshold levels are a likely result. Unsafe pressurization of equipment such as extruder or mold can also result. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of halogenated materials from coming in contact with the acetal. Prevent contamination of virgin or rework resin. |
| Hazardous decomposition products | : | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. Decomposition of this material depends on the lenght of time it is exposed to elevated temperatures. At the recommended processing temperature of 210°C-220°C (410°F-428°F), decomposition should not be significant until after 30 minutes. Decomposition may be accelerated by contaminants, pigments and/or other additives. |

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|---|----------------------------|----------------------------|-----------------------------------|
| 1309-37-1 | Iron oxide | Systemic effects | Respiratory system. |
| 12001-26-2 | Mica | Systemic effects | Respiratory system. |
| | | | |
| | 12. ECOLOGI | CAL INFORMATION | I |
| | | | |
| Persistence and deg | radability : Not readily l | piodegradable. | |
| Persistence and deg Environmental Toxi | | re not readily available a | s they are bound within the matri |
| - | icity : Chemicals a | re not readily available a | s they are bound within the matri |



MATERIAL SAFETY DATA SHEET **GOLD**

| sion Date 03/31/2004 | Page Print Date 11/14 |
|------------------------------|---|
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the mat of the polymer. |
| Additional advice | : Not applicable |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste mater has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| | |
| U.S. DOT Classification | : Not regulated for transportation. |
| ICAO/IATA (air) | : Refer to specific regulation. |
| IMO / IMDG (maritime) | : Refer to specific regulation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSO Inventory. |
| US. EPA CERCLA Hazardou | us Substances (40 CFR 302) |
| Not applicable | |
| California Propositior 65 | n : This product does not contain a substance listed by California Prop |
| SARA Title III Section 302 E | Extremely Hazardous Substance |
| Not applicable | |
| | |



MATERIAL SAFETY DATA SHEET **GOLD**

Version Number 1.1 Revision Date 03/31/2004

Page 6 of 6 Print Date 11/14/2011

| SARA Title III Section 313 Toxic Chemicals: | | | |
|---|-------|--|--|
| Not applicable Canadian Regulations: | | | |
| National Pollutant Release | se Iı | nventory (NPRI) | |
| Not applicable | | | |
| WHMIS Classification | : | Not controlled. | |
| DSL | : | All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. | |
| National Inventories: | | | |
| Australia AICS | : | Listed | |
| China IECS | : | Listed | |
| Europe EINECS | : | Listed | |
| Japan ENCS | : | Not determined | |
| Korea KECI | : | Listed | |
| Philippines PICCS | : | Listed | |

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.