

# MATERIAL SAFETY DATA SHEET

## 030PG3

Version Number 1.1 Revision Date 01/08/2004 Page 1 of 6 Print Date 11/13/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030PG3
Product code	:	CC10037010
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Calcium carbonate	1317-65-3	30 - 60

## 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



## MATERIAL SAFETY DATA SHEET **030PG3**

Version Number 1.1 Revision Date 01/08/2004 Page 2 of 6 Print Date 11/13/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



# MATERIAL SAFETY DATA SHEET **030PG3**

ion Number 1.1				
sion Date 01/08/2004			Drint D	Page 3 0ate 11/13/2
sion Date 01/08/2004			PIIIILD	ale 11/13/2
Handling		ake measures to prevent th nly in areas with appropria	e build up of electrostatic ch te exhaust ventilation.	narge Heat
Storage		Leep containers dry and tight nd contamination. Keep in	ntly closed to avoid moisture a dry, cool place.	e absorption
8. H	XPOSURE	CONTROLS / PERSON	AL PROTECTION	
Respiratory protection	: N	lo personal respiratory prot	ective equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shie	elds.	
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		landle in accordance with g Vash hands before breaks a	ood industrial hygiene and s nd at the end of workday.	afety practice
Engineering measures		leat only in areas with appr ppropriate exhaust ventilati	opriate exhaust ventilation.	Provide
Exposure limit(s)				
~				
	Value	Exposure time	Exposure type	List:
Components Calcium carbonate	Value 5 mg/m3	Exposure time PEL:	Exposure type Respirable fraction.	List: OSHA Z1
Components	Value 5 mg/m3 15 mg/m3		Exposure type Respirable fraction. Total dust.	OSHA Z1
Components	5 mg/m3 15 mg/m3 0.05	PEL: PEL: Time Weighted Average	Respirable fraction.Total dust.	OSHA Z1
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3	PEL: PEL: Time Weighted Average (TWA):	Respirable fraction.           Total dust.           e         Respirable fraction.	OSHA Z1 OSHA Z1 ACGIH
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3	PEL: PEL: Time Weighted Average (TWA): PEL:	Respirable fraction.         Total dust.       Respirable fraction.         Respirable fraction.       Respirable fraction.	OSHA Z1 OSHA Z1 ACGIH OSHA Z1
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3	PEL: PEL: Time Weighted Average (TWA):	Respirable fraction.           Total dust.           e         Respirable fraction.	OSHA Z1 OSHA Z1 ACGIH OSHA Z1
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average (TWA): PEL: PEL:	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.	OSHA Z1 OSHA Z1 ACGIH OSHA Z1
Components Calcium carbonate	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3	PEL: PEL: Time Weighted Average (TWA): PEL:	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.	OSHA Z1 OSHA Z1
Components Calcium carbonate Quartz Form	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 applicable
Components Calcium carbonate Quartz Form Appearance	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F t Events Spont	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.    PROPERTIES          aporation rate       : Not         ecific Gravity:       : Not	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 OSHA Z1
Components Calcium carbonate Quartz Form Appearance Color	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solic : Pelle : NO I	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F the Event of the Even	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.         PROPERTIES         aporation rate       : Not         ecific Gravity:       : Not         lk density       : Not	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 OSHA Z1 applicable determined established
Components Calcium carbonate Quartz Form Appearance Color Odor	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIO : Solid : Pelle : NO I : Very	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F ts Spe PIGMENT Bu r faint Va	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.         PROPERTIES         aporation rate       : Not         ecific Gravity:       : Not         lk density       : Not         por pressure       : Not	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 applicable determined established applicable
Components Calcium carbonate Quartz Quartz Form Appearance Color Odor Melting point/range	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F CAL AND CHEMICAL F L Events Specent PIGMENT Bu r faint Va determined Va	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.         PROPERTIES         aporation rate       : Not         ecific Gravity:       : Not         lk density       : Not         por pressure       : Not         pour density       : Not	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 established applicable applicable applicable
Components Calcium carbonate Quartz Form Appearance Color Odor	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : NO I : Very : Not	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F CAL AND CHEMICAL F I Event PIGMENT Bu r faint Va determined Va applicable pH	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.         PROPERTIES         aporation rate       : Not         ecific Gravity:       : Not         lk density       : Not         por pressure       : Not         pour density       : Not	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 applicable determined established applicable
Components Calcium carbonate Quartz Quartz Form Appearance Color Odor Melting point/range Boiling Point:	5 mg/m3 15 mg/m3 0.05 mg/m3 5 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : NO 1 : Very : Not 2 : Insol	PEL: PEL: Time Weighted Average (TWA): PEL: PEL: CAL AND CHEMICAL F CAL AND CHEMICAL F I Event PIGMENT Bu r faint Va determined Va applicable pH	Respirable fraction.         Total dust.         e       Respirable fraction.         Respirable fraction.         Total dust.         PROPERTIES         aporation rate       : Not         ecific Gravity:       : Not         lk density       : Not         pour density       : Not	OSHA Z1 OSHA Z1 ACGIH OSHA Z1 OSHA Z1 applicable determined established applicable applicable



## MATERIAL SAFETY DATA SHEET 030PG3

Version Number 1.1 Revision Date 01/08/2004		Page 4 of 6 Print Date <i>11/13/2011</i>
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

#### Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET **030PG3** 

Version Number 1.1 Revision Date 01/08/2004 Page 5 of 6 Print Date 11/13/2011

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long term exposure may cause caughing, chest pain, diminished chest expansion and possibly silicosis which is a scarring of the lungs.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	



## MATERIAL SAFETY DATA SHEET **030PG3**

/ersion Number 1.1 Revision Date 01/08/2004		Page 6 o Print Date 11/13/20
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	rem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	ic (	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	se I	nventory (NPRI)
Not applicable		
WHMIS Classification	:	D2A
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Listed
		16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.