

MATERIAL SAFETY DATA SHEET

SEARS LT. GRAY PS - UV2B

Version Number 1.0 Revision Date 05/27/2003 Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SEARS LT. GRAY PS - UV2B
Product code	:	CC10037269
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to 		
Skin	eyes.Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET

SEARS LT. GRAY PS - UV2B

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	



MATERIAL SAFETY DATA SHEET

SEARS LT. GRAY PS - UV2B

Version Number 1.0 Revision Date 05/27/2003

Page 3 of 6 Print Date 11/11/2011

Keep containers dry and tightly closed to avoid moisture absorption Storage : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. : Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures : appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- : Solid : Pellets : GREY : Very faint : Not determined : Not applicable : Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН
- Not applicable. : Not determined : Not established : : Not applicable : Not applicable
- : Not applicable

10. STABILITY AND REACTIVITY

Stability

Stable. :

Hazardous Polymerization

Will not occur. :



MATERIAL SAFETY DATA SHEET

SEARS LT. GRAY PS - UV2B

ion Number 1.0 sion Date 05/27/200)3			Page / Print Date 11/11/
Conditions to avoid :			om oxidizing agents an n, do not overheat.	d open flame. To avoid therma
Incompatible Material	s	: Incompatible	with strong acids and o	oxidizing agents.
				oxide (CO), oxides of nitrogen nd smoke are all possible.
	11	. TOXICOLOG	ICAL INFORMATIO	DN
This mixture has not b health data for the ind				are effects listed are based on ex
Toxicity Overview This product contains	the followi	ng components w	hich in their pure form	have the following characterist
CAS-No.	Che	emical Name	Effect	Target Organ
1317-65-3		carbonate	Irritant	Eyes, Skin.
			Systemic effects	Eyes, Skin, Respiratory system
13463-67-7	Titanium	dioxide	Systemic effects	Respiratory system.
Environmental Toxicity Bioaccumulation Potential Additional advice		 Chemicals are not readily available as they are bound within the matrix of the polymer. Chemicals are not readily available as they are bound within the matrix of the polymer. No data available. 		
		13. DISPOSAL	CONSIDERATIONS	
Product		possible, recy generator of v classification	cling is preferred to dis waste material has the r	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.
ha		has the respon	nsibility for proper was in accordance with app	e. The generator of waste materi te classification, transportation licable federal, state/provincial
		14 TDANSDO	RT INFORMATION	
		14. I KANSI U		



MATERIAL SAFETY DATA SHEET

SEARS LT. GRAY PS - UV2B

rsion Number 1.0 vision Date 05/27/2003		Page 5 of 6 Print Date 11/11/2011
U.S. DOT Classification	:	Refer to specific regulation.
ICAO/IATA	:	Refer to specific regulation.
IMO / IMDG	:	Refer to specific regulation.
	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	Subs	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extr	eme	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	ic C	Chemicals:
Not applicable		
Canadian Regulations:		
WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
DSL National Inventories:	•	
	•	
National Inventories:		Substances List (DSL) or are exempt.
National Inventories: Australia AICS	:	Substances List (DSL) or are exempt.



MATERIAL SAFETY DATA SHEET

SEARS LT. GRAY PS - UV2B

Version Number 1.0 Revision Date 05/27/2003 Page 6 of 6 Print Date 11/11/2011

Korea KECI :	Listed.
--------------	---------

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.