

MATERIAL SAFETY DATA SHEET UV MAGENTA POT

Version Number 1.0 Revision Date 06/12/2003

Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV MAGENTA POT
Product code	:	CC10038301
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10
Iron oxide	1309-37-1	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET UV MAGENTA POT

Version Number 1.0 Revision Date 06/12/2003 Page 2 of 6 Print Date 11/11/2011

Aggravated by Exposure:		
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, Water spray, dry powder, foam. 	
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None 	
	6. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.	



MATERIAL SAFETY DATA SHEET **UV MAGENTA POT**

Version Number 1.0 Revision Date 06/12/2003

Page 3 of 6 Print Date 11/11/2011

Storage Keep containers dry and tightly closed to avoid moisture absorption : and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection No personal respiratory protective equipment normally required. : Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection Long sleeved clothing. : Additional Protective Safety shoes. ÷ Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Solid

RED

Pellets

Very faint

Insoluble

:

Not determined

Not applicable

Form	:
Appearance	:
Color	:
Odor	:
Melting point/range	÷
Boiling Point:	
Water solubility	
water solubility	·

Evaporation rate pН

Specific Gravity Bulk density Vapor pressure Vapor density

Keep away from oxidizing agents and open flame. To avoid thermal

: Not applicable. Not determined

Not established

:

: : Not applicable

: Not applicable

: Not applicable

10. STABILITY AND REACTIVITY

Stability Stable. :

Hazardous Polymerization Will not occur. :

Conditions to avoid

3/6



MATERIAL SAFETY DATA SHEET UV MAGENTA POT

ision Date 06/12/2	2003			Page 4 Print Date 11/11/2
		decompositio	n, do not overheat.	
		_		
Incompatible Mater	ials	: Incompatible	with strong acids and o	oxidizing agents.
Hazardous decompo products	osition			xide (CO), oxides of nitrogen ad smoke are all possible.
	1	1. TOXICOLOG	ICAL INFORMATIO	DN
This mixture has no health data for the in Toxicity Overview				are effects listed are based on exis
	ns the follow	ng components w	hich in their pure form	have the following characteristic:
CAS-No.		emical Name	Effect	Target Organ
13463-67-7 1309-37-1	Titaniun Iron oxi	n dioxide	Systemic effects Systemic effects	Respiratory system. Respiratory system.
1309-37-1	IIOII OXI	Je	Systemic effects	Respiratory system.
		12. ECOLOGIC	AL INFORMATION	
Environmental Toxi Bioaccumulation Po		of the polyme	r.	s they are bound within the matrix s they are bound within the matrix
		of the polyme	r.	
Additional advice		: No data availa		
			ible.	
		13. DISPOSAL	CONSIDERATIONS	
Product		: Like most the possible, recy generator of w classification,	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
Product Contaminated packa	aging	 Like most the possible, recygenerator of w classification, applicable fed Recycling is p has the response 	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r transportation and disp leral, state/provincial ar preferred when possible isbility for proper was n accordance with appl	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
	aging	 Like most the possible, recy generator of v classification, applicable fed Recycling is p has the respon and disposal i and local regu 	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r transportation and disp leral, state/provincial ar preferred when possible isbility for proper was n accordance with appl	et can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. b. The generator of waste material te classification, transportation
		 Like most the possible, recy generator of v classification, applicable fed Recycling is p has the respon and disposal i and local regu 	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r transportation and disp leral, state/provincial an preferred when possible asibility for proper was n accordance with appli- lations.	et can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. b. The generator of waste material te classification, transportation



MATERIAL SAFETY DATA SHEET UV MAGENTA POT

Version Number 1.0 Revision Date 06/12/2003 Page 5 of 6 Print Date 11/11/2011

IMO / IMDG :	Refer to specific regulation.
15	5. REGULATORY INFORMATION
US Regulations:	
OSHA Status :	Classified as hazardous based on components.
TSCA Status :	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)
Not applicable	
California Proposition : 65	This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extrem	ely Hazardous Substance
Not applicable	
SARA Title III Section 313 Toxic C	Chemicals:
Not applicable Canadian Regulations:	
WHMIS Classification :	D2B
WHMIS Ingredient Disclosu	ire List
CAS-No. 1309-37-1	
DSL :	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS :	Listed.
China IECS :	Listed.
Europe EINECS :	Not determined.
Japan ENCS :	Not determined.

DLYONE CORPORA	TION	PolyOne.
ATERIAL SAFETY DATA SH		
V MAGENTA POT		
rsion Number 1.0 vision Date 06/12/2003		Page 6 o Print Date 11/11/20
Korea KECI	: Not determined.	
Philippines PICCS	: Not determined.	
	16. OTHER INFO	PRMATION