

MATERIAL SAFETY DATA SHEET **SKY BLUE**

Version Number 1.0 Revision Date 06/20/2003

Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SKY BLUE
Product code	:	CC10038534
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **SKY BLUE**

Version Number 1.0 Revision Date 06/20/2003 Page 2 of 6 Print Date 11/11/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
Hazards	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET **SKY BLUE**

Version Number 1.0 Revision Date 06/20/2003

Storage

Page 3 of 6 Print Date 11/11/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form	: Solid	Evaporation rate	: Not applicable.
Appearance	: Pellets	Specific Gravity	: Not determined
Color	: BLUE	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapor density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		
	10. STABILITY AN	ND REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid		oxidizing agents and open f o not overheat.	lame. To avoid thermal



MATERIAL SAFETY DATA SHEET **SKY BLUE**

Version Number 1.0 Revision Date 06/20/200)3			Page 4 of 6 Print Date 11/11/2011
Incompatible Material	s :	Incompatible wi	ith strong acids and or	kidizing agents.
Hazardous decomposit products	tion :			tide (CO), oxides of nitrogen 1 smoke are all possible.
	11 /			ът
	11, 1	IUXICULUGIC	CAL INFORMATIO	N
This mixture has not b health data for the indi				re effects listed are based on existing
<u>Toxicity Overview</u> This product contains	the following	components whi	ch in their pure form l	nave the following characteristics:
CAS-No.	Chem	nical Name	Effect	Target Organ
13463-67-7	Titanium di		Systemic effects	Respiratory system.
	14			
		2. ECULUGICA	L INFORMATION	
Persistence and degrad	lability :	Not readily biod	legradable.	
Environmental Toxicit	ty :	Chemicals are not of the polymer.	ot readily available as	they are bound within the matrix
Bioaccumulation Poter	ntial :	Chemicals are no of the polymer.	ot readily available as	they are bound within the matrix
Additional advice	:	No data availab	le.	
	13	3. DISPOSAL C	ONSIDERATIONS	
Product	:	possible, recycli generator of was classification, tr	ing is preferred to disp ste material has the re	t can be recycled. Where bosal or incineration. The sponsibility for proper waste osal in accordance with d local regulations.
Contaminated packagi	ng :	has the responsi	bility for proper waste accordance with appli	The generator of waste material e classification, transportation cable federal, state/provincial
	1	4. TRANSPORT	INFORMATION	
U.S. DOT Classification	on :	Refer to specific	e regulation.	
ICAO/IATA	:	Refer to specific	c regulation.	
IMO / IMDG	:	Refer to specific	c regulation.	



MATERIAL SAFETY DATA SHEET **SKY BLUE**

Version Number 1.0 Revision Date 06/20/2003 Page 5 of 6 Print Date 11/11/2011

	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: This product does not contain a substance listed by California Prop 65
SARA Title III Section 302 Ext	remely Hazardous Substance
Not applicable	
SARA Title III Section 313 Tox	tic Chemicals:
Not applicable Canadian Regulations:	
WHMIS Classification	: D2B
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.
	: Not determined.
Europe EINECS	
Europe EINECS Japan ENCS	: Listed.
-	: Listed.
Japan ENCS	



MATERIAL SAFETY DATA SHEET **SKY BLUE**

Version Number 1.0 Revision Date 06/20/2003 Page 6 of 6 Print Date 11/11/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.