## MATERIAL SAFETY DATA SHEET **BROWN**

Version Number 1.1 Revision Date 09/17/2007 Page 1 of 6 Print Date 12/1/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BROWN
Product code	:	CC10039330
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

## 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	10 - 30
Rutile, antimony chromium buff	68186-90-3	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to even</li> </ul>
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

# MATERIAL SAFETY DATA SHEET **BROWN**

Version Number 1.1 Revision Date 09/17/2007 Page 2 of 6 Print Date 12/1/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:	Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne

## MATERIAL SAFETY DATA SHEET **BROWN**

#### Version Number 1.1 Revision Date 09/17/2007

Page 3 of 6 Print Date 12/1/2011

	a	nd contamination. Keep in a d	ry, cool place.				
8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION				
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally r	equired.			
Eye/Face Protection : Safety glasses with side-shields							
Hand protection : Protective gloves							
Skin and body protection	: L	ong sleeved clothing					
Additional Protective : Safety shoes Measures							
General Hygiene:Handle in accordance with good industrial hygiene and safety practice.ConsiderationsWash hands before breaks and at the end of workday.							
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.							
Exposure limit(s)							
Components	Value	Exposure time	Exposure type	List:			
Iron oxide	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH			
	10 mg/m3	PEL:	Fume.	OSHA Z1			
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL			
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL			
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH			
	0.5 mg/m3	PEL:	as Cr	OSHA Z1			
	0.5 mg/m3	Time Weighted Average		MX OEL			

 
 Image of a regime
 Image of a regime

 0.5 mg/m3
 Time Weighted Average (TWA):
 as Sb

 0.5 mg/m3
 PEL:
 as Sb

 0.5 mg/m3
 Time Weighted Average (TWA):
 as Sb

## 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range
- : Solid
  : pellets
  : BROWN
  : Very faint
  : Not determined
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density
- Not applicableNot determinedNot establishedNot applicableNot applicable

ACGIH

OSHA Z1

MX OEL





## MATERIAL SAFETY DATA SHEET BROWN

#### Version Number 1.1 Revision Date 09/17/2007

Page 4 of 6 Print Date 12/1/2011

		ot applicable soluble	рН	: Not applicable
	1(	). STABILITY AND I	REACTIVITY	
Stability	:	Stable.		
Hazardous Polymerization	:	Will not occur.		
Conditions to avoid	:	Keep away from oxid decomposition, do no	00	pen flame. To avoid thermal
Incompatible Materials	:	Incompatible with str	ong acids and oxid	lizing agents.
Hazardous decomposition products	:			le (CO), oxides of nitrogen smoke are all possible.
	11 <b>.</b> ′	<b>FOXICOLOGICAL I</b>	NFORMATION	

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.

### Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	ot readily biodegradable.	
Environmental Toxicity	nemicals are not readily available lymer matrix.	as they are bound within the
Bioaccumulation Potential	nemicals are not readily available lymer matrix.	as they are bound within the
Additional advice	o data available	
	<b>DISPOSAL CONSIDERATIONS</b>	5
Product	ke most thermoplastic plastics the	product can be recycled. Where



# MATERIAL SAFETY DATA SHEET **BROWN**

sion Number 1.1 vision Date 09/17/2007	Page 5 of 6 Print Date 12/1/2011
Contaminated packaging	<ul> <li>possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> <li>Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.</li> </ul>
	14. TRANSPORT INFORMATION
U.S. DOT Classification ICAO/IATA (air) IMO / IMDG (maritime)	<ul> <li>Not regulated for transportation.</li> <li>Refer to specific regulation.</li> <li>Refer to specific regulation.</li> </ul>
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 Ex	tremely Hazardous Substance
	dentified under this section, this product is Not Applicable under this regulation

PolvOn<u>e</u>

## MATERIAL SAFETY DATA SHEET **BROWN**

Version Number 1.1 Revision Date 09/17/2007

Page 6 of 6 Print Date 12/1/2011

Chemical Name	CAS-No.	Weight %
CHROMIUM III COMPOUNDSANTIMONY	68186-90-3	10.00 - 30.00
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Rutile, antimony chromium buff	68186-90-3	10.00 - 30.00	69
		10.00 - 30.00	17

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
1309-37-1	
68186-90-3	

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

## **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.