

MATERIAL SAFETY DATA SHEET

PG 39890 PU LDPE

Version Number 1.1 Revision Date 09/09/2003

Page 1 of 6 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	: Product Stewardship (770) 271-5902			
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).			
Product name	:	PG 39890 PU LDPE			
Product code	:	CC10039890			
Chemical Name	:	Mixture			
CAS-No.	:	Mixture			
Product Use	:	Industrial Applications			

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

PG 39890 PU LDPE

Version Number 1.1 Revision Date 09/09/2003 Page 2 of 6 Print Date 11/12/2011

Medical Conditions Aggravated by Exposure:	: None known.		
	4. FIRST AID MEASURES		
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.		
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: Not applicable		
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None 		
	5. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		
Handling	: Take measures to prevent the build up of electrostatic charge. Heat		



MATERIAL SAFETY DATA SHEET **PG 39890 PU LDPE**

rsion Number 1.1 vision Date 09/09/2003		Page 3 of 6 Print Date 11/12/2011
Storage	:	only in areas with appropriate exhaust ventilation. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	POSUI	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

|--|

: Solid Evaporation rate Not applicable. Form : Not determined Appearance : Pellets Specific Gravity : Color : PURPLE Bulk density Not established : Odor Very faint Vapor pressure : Not applicable : Melting point/range : Not determined Vapor density : Not applicable Boiling Point: : Not applicable pН Not applicable : Water solubility : Insoluble

10. STABILITY AND REACTIVITY

Stability

: Stable.





MATERIAL SAFETY DATA SHEET **PG 39890 PU LDPE**

Version Number 1.1 Page 4 of 6 Revision Date 09/09/2003 Print Date 11/12/2011 Hazardous Polymerization : Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials : Incompatible with strong acids and oxidizing agents. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : (NOx), other hazardous materials, and smoke are all possible. products

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eves, Skin, Respiratory system.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION



MATERIAL SAFETY DATA SHEET **PG 39890 PU LDPE**

Version Number 1.1 Revision Date 09/09/2003 Page 5 of 6 Print Date 11/12/2011

U.S. DOT Classification	: Refer to specific regulation.			
ICAO/IATA	: Refer to specific regulation.			
IMO / IMDG	: Refer to specific regulation.			
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	: Classified as hazardous based on components.			
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCLA Hazardous	Substances (40 CFR 302)			
Not applicable				
California Proposition 65	: This product does not contain a substance listed by California Prop 65.			
SARA Title III Section 302 Extremely Hazardous Substance				
Not applicable				
SARA Title III Section 313 Toxic Chemicals:				
Not applicable				
Canadian Regulations:				
National Pollutant Release Inventory (NPRI)				
Not applicable				
WHMIS Classification : D2B				
WHMIS Ingredient Disclosure List				
CAS-No.				
7631-86-9				
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.			



MATERIAL SAFETY DATA SHEET **PG 39890 PU LDPE**

Version Number 1.1 Revision Date 09/09/2003

Page 6 of 6 Print Date *11/12/2011*

National Inventories:

:	Listed.
:	Listed.
:	Not determined.
:	Listed.
:	Listed.
:	Listed.
	: : :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.