

MATERIAL SAFETY DATA SHEET ORANGE 1505C

Version Number 1.0

Revision Date 08/11/2003

Page 1 of 6 Print Date 11/11/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE 1505C
Product code	:	CC10040241
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	



MATERIAL SAFETY DATA SHEET ORANGE 1505C

Version Number 1.0 Revision Date 08/11/2003 Page 2 of 6 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET ORANGE 1505C

Version Number 1.0 Revision Date 08/11/2003 Page 3 of 6 Print Date 11/11/2011

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. Eye/Face Protection Safety glasses with side-shields. : Hand protection Protective gloves. : Skin and body protection : Long sleeved clothing. Additional Protective Safety shoes. : Measures General Hygiene Handle in accordance with good industrial hygiene and safety practice. : Considerations Wash hands before breaks and at the end of workday. : Heat only in areas with appropriate exhaust ventilation. Provide Engineering measures appropriate exhaust ventilation at machinery. Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1


Form	: Solid	Evaporation rate	: Not applicable.
Appearance	: Pellets	Specific Gravity	: Not determined
Color	: ORANGE	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapor density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		
	10. STABILITY AN	D REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
		• 1• • • • • • •	ame. To avoid thermal

3/6



MATERIAL SAFETY DATA SHEET ORANGE 1505C

sion Number 1.0 ision Date 08/11/200	3		Page 4 Print Date 11/11/2
	decomposition	n, do not overheat.	
Incompatible Materials	s : Incompatible	with strong acids and o	oxidizing agents.
Hazardous decomposit	ion · Carbon dioxid	e (CO2), carbon mono	oxide (CO), oxides of nitrogen
products			nd smoke are all possible.
	11. TOXICOLOG	ICAL INFORMATIO	DN
health data for the indi	een evaluated as a whole for vidual components which co		ure effects listed are based on exi
<u>Toxicity Overview</u> This product contains t	the following components wl	nich in their pure form	have the following characteristic
CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system
Persistence and degrad Environmental Toxicit Bioaccumulation Poter Additional advice	y : Chemicals are of the polymer	not readily available a r. not readily available a r.	is they are bound within the matrix
	13. DISPOSAL	CONSIDERATIONS	<u> </u>
Product	: Like most ther possible, recyc generator of w classification,	moplastics the production of the production of the production of the production of the product o	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
Contaminated packagin	has the respon	sibility for proper was accordance with app	e. The generator of waste materia te classification, transportation licable federal, state/provincial
	14 TDANSDOI		
	14. I KANSFOI	RT INFORMATION	



PolvOne
POLYONE CORPORATION
MATERIAL SAFETY DATA SHEET
ORANGE 1505C
Version Number 1.0Page 6 ofRevision Date 08/11/2003Print Date 11/11/201
Korea KECI : Listed.
Philippines PICCS : Listed.
16. OTHER INFORMATION
specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.