

MATERIAL SAFETY DATA SHEET

STAN-TONE VC-29297 SHERWOOD GREEN 564

Version Number 1.1 Revision Date 10/19/2004 Page 1 of 6 Print Date 11/16/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	STAN-TONE VC-29297 SHERWOOD GREEN 564
Product code :	CC10040514
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion		
Acute exposure			
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Particulates, like other inert materials can be mechanically irritating. Experience shows no unusual dermatitis hazard from routine handling. 		
Chronic exposure Medical Conditions	Refer to Section 11 for Toxicological Information.None known.		
Aggravated by Exposure:			



MATERIAL SAFETY DATA SHEET

STAN-TONE VC-29297 SHERWOOD GREEN 564

Version Number 1.1 Revision Date 10/19/2004 Page 2 of 6 Print Date 11/16/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	÷	Not applicable
Autoignition temperature	:	Not relevant
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Suitable extinguishing media	•	Carbon dioxide blanket, water spray, dry powder, toannione.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29297 SHERWOOD GREEN 564

Version Number 1.1 Revision Date 10/19/2004

Storage

Page 3 of 6 Print Date 11/16/2011

condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 powder, granular
 GREEN
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not determined
 Not applicable
 Not applicable
 Not applicable

10. STABILITY AND REACTIVITY

3/6



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29297 SHERWOOD GREEN 564

Version Number 1.1 Revision Date 10/19/2004 Page 4 of 6 Print Date <u>11/16/</u>2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	To avoid thermal decomposition, do not overheat. Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

_

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: No data available
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial



MATERIAL SAFETY DATA SHEET STAN-TONE VC-29297 SHERWOOD GREEN 564 Version Number 1.1

Revision Date 10/19/2004

Page 5 of 6 Print Date 11/16/2011

		and local regulations.		
	1	4. TRANSPORT INFORMATION		
U.S. DOT Classification	:	Not regulated for transportation.		
ICAO/IATA (air)	:	Not regulated for transportation.		
IMO / IMDG (maritime)	:	Not regulated for transportation.		
	15	REGULATORY INFORMATION		
US Regulations:				
OSHA Status	:	Classified as hazardous based on components.		
TSCA Status	:	All components of this product are listed on or exempt from the TSC Inventory.		
US. EPA CERCLA Hazardo	ous Sub	tances (40 CFR 302)		
Not applicable				
California Propositio 65	on :	WARNING! This product contains a chemical known to the State of California to cause cancer.		
65		California to cause cancer.		
65 SARA Title III Section 302		California to cause cancer.		
65 SARA Title III Section 302 Not applicable	Extrem	California to cause cancer. ely Hazardous Substance		
65 SARA Title III Section 302	Extrem	California to cause cancer. ely Hazardous Substance		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable	Extrem	California to cause cancer. ely Hazardous Substance		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313	Extrem	California to cause cancer. ely Hazardous Substance		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable Canadian Regulations:	Extrem Toxic C	California to cause cancer. ely Hazardous Substance hemicals:		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable Canadian Regulations: National Pollutant Re	Extrem Toxic C	California to cause cancer. ely Hazardous Substance hemicals:		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable Canadian Regulations:	Extrem Toxic C	California to cause cancer. ely Hazardous Substance hemicals:		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable Canadian Regulations: <u>National Pollutant Re</u> Chemical Name	Extrem Toxic C	California to cause cancer. ely Hazardous Substance themicals: eventory (NPRI) CAS-No. Weight % NPRI ID#		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable Canadian Regulations: <u>National Pollutant Re</u> Chemical Name	Extrem Toxic C	California to cause cancer. ely Hazardous Substance themicals: eventory (NPRI) CAS-No. Weight % NPRI ID#		
65 SARA Title III Section 302 Not applicable SARA Title III Section 313 Not applicable Canadian Regulations: <u>National Pollutant Re</u> Chemical Name	Extrem Toxic C	California to cause cancer. ely Hazardous Substance themicals: eventory (NPRI) CAS-No. Weight % NPRI ID#		

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET STAN-TONE VC-29297 SHERWOOD GREEN 564

Version Number 1.1 Revision Date 10/19/2004 Page 6 of 6 Print Date 11/16/2011

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.