

# MATERIAL SAFETY DATA SHEET

# AMPLIFY GREEN

Version Number 1.0 Revision Date 08/05/2003 Page 1 of 6 Print Date 11/11/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	AMPLIFY GREEN
Product code	:	CC10040929
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

## POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



## MATERIAL SAFETY DATA SHEET AMPLIFY GREEN

Version Number 1.0 Revision Date 08/05/2003 Page 2 of 6 Print Date 11/11/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



## MATERIAL SAFETY DATA SHEET AMPLIFY GREEN

Version Number 1.0 Revision Date 08/05/2003

Storage

Page 3 of 6 Print Date 11/11/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.	
Eye/Face Protection	:	Safety glasses with side-shields.	
Hand protection	:	Protective gloves.	
Skin and body protection	:	Long sleeved clothing.	
Additional Protective Measures	:	Safety shoes.	
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.	
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

Pellets
GREEN
Very faint
Not determined
Not applicable
Insoluble

: Solid

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH Not applicable.Not determinedNot established

Not applicableNot applicable

: Not applicable

### **10. STABILITY AND REACTIVITY**

Stability	Stable.	
Hazardous Polymerization	Will not occur.	
Conditions to avoid	Keep away from oxidizing agents and open flame. To avo	id thermal



## MATERIAL SAFETY DATA SHEET AMPLIFY GREEN

ision Date 08/05/2	003		Page 4 Print Date 11/11/2
	decompos	sition, do not overheat.	
Incompatible Mater	ials : Incompat	ible with strong acids and	oxidizing agents.
Hazardous decompo products		ioxide (CO2), carbon mono ther hazardous materials, a	oxide (CO), oxides of nitrogen nd smoke are all possible.
	11. TOXICOL	OGICAL INFORMATIO	ON
health data for the in Toxicity Overview	ndividual components whic	ch comprise the mixture.	ure effects listed are based on exis
This product contain	is the following component	its which in their pure form	have the following characteristic
CAS-No.	Chemical Name		Target Organ
7631-86-9 13463-67-7	Silica, amorphous Titanium dioxide	Irritant Systemic effects	Eyes, Respiratory system. Respiratory system.
13403-07-7	Thainum dioxide	Systemic effects	Respiratory system.
Bioaccumulation Pc	tential : Chemical of the pol		s they are bound within the matrix
Additional advice	: No data a	•	
Additional advice	: No data a	•	5
Additional advice Product	: No data a <b>13. DISPOS</b> : Like mos possible, generator classifica	wailable. SAL CONSIDERATIONS t thermoplastics the produ recycling is preferred to di	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
	<ul> <li>No data a</li> <li>13. DISPOS</li> <li>Like mos possible, generator classifica applicable</li> <li>Recycling has the re and dispo</li> </ul>	t thermoplastics the produce thermoplastics the produce of waste material has the production, transportation and disticate federal, state/provincial and the produce sponsibility for proper waste	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
Product	<ul> <li>No data a</li> <li>13. DISPOS</li> <li>Like mos possible, generator classifica applicable</li> <li>Recycling has the re and dispo and local</li> </ul>	Available. <b>SAL CONSIDERATIONS</b> t thermoplastics the produce recycling is preferred to directly of the second of waste material has the second the second term of term	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia te classification, transportation
Product	<ul> <li>No data a</li> <li>13. DISPOS</li> <li>Like mos possible, generator classifica applicable</li> <li>Recycling has the re and dispo and local</li> <li>14. TRANS</li> </ul>	Available. <b>SAL CONSIDERATIONS</b> t thermoplastics the produ recycling is preferred to di of waste material has the r tion, transportation and dis e federal, state/provincial a g is preferred when possible esponsibility for proper was usal in accordance with app regulations.	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia te classification, transportation



## MATERIAL SAFETY DATA SHEET AMPLIFY GREEN

Version Number 1.0 Revision Date 08/05/2003 Page 5 of 6 Print Date 11/11/2011

IMO / IMDG	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous Su	US. EPA CERCLA Hazardous Substances (40 CFR 302)				
Not applicable					
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.				
SARA Title III Section 302 Extre	mely Hazardous Substance				
Not applicable					
SARA Title III Section 313 Toxic	Chemicals:				
Not applicable Canadian Regulations:					
National Pollutant Release	Inventory (NPRI)				
Not applicable					
WHMIS Classification	: D2B				
WHMIS Ingredient Disclo	sure List				
CAS-No. 7631-86-9	]				
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:					
Australia AICS	: Listed.				
China IECS	: Listed.				

		PolyOne.
POLYONE CORPORA	TION	- •
MATERIAL SAFETY DATA SH	EET	
AMPLIFY GREEN		
Version Number 1.0 Revision Date 08/05/2003		Page 6 of 6 Print Date 11/11/2011
Europe EINECS	: Not determined.	
Japan ENCS	: Listed.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	

~

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.