

MATERIAL SAFETY DATA SHEET

### FL PINK

Version Number 1.1 Revision Date 09/09/2003 Page 1 of 6 Print Date 11/12/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	FL PINK
Product code	:	CC10040999
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion	<ul><li>Resin particles, like other inert materials, can be mechanically irritating.</li><li>May be harmful if swallowed.</li></ul>		
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



#### MATERIAL SAFETY DATA SHEET

### FL PINK

Version Number 1.1 Revision Date 09/09/2003 Page 2 of 6 Print Date 11/12/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not relevant</li> <li>Carbon dioxide blanket, water spray, dry powder, foam.</li> </ul>
Special Fire Fighting Procedures Unusual Fire/Explosion	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>None</li> </ul>
Hazards	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



## MATERIAL SAFETY DATA SHEET

## FL PINK

Storage

Version Number	er 1.1
<b>Revision Date</b>	09/09/2003

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
Silica, amorphous	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
		$(\mathbf{I} \mathbf{W} \mathbf{A})$ :		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES
-------------------------------------

Form
Appearance
Color
Odor
Melting point/range
<b>Boiling Point:</b>
Water solubility

: Pellets : PINK : Very faint : Not determined : Not applicable : Insoluble

: Solid

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pН

: Not applicable. : Not determined : Not established

- : Not applicable
- : Not applicable
- : Not applicable

### **10. STABILITY AND REACTIVITY**

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal



## MATERIAL SAFETY DATA SHEET

## FL PINK

ision Date 09/09/2	2003			Page 4 c Print Date 11/12/20
		decompositio	n, do not overheat.	
Incompatible Mater	ials	: Incompatible	with strong acids and o	oxidizing agents.
Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.				
	11	. TOXICOLOG	ICAL INFORMATIO	DN
health data for the in Toxicity Overview	ndividual com	ponents which co	omprise the mixture.	are effects listed are based on exist have the following characteristics
CAS-No.	Ch	emical Name	Effect	Torgot Orgon
CAS-No. 7631-86-9	Silica, an		Irritant	Target OrganEyes, Respiratory system.
13463-67-7	Titanium		Systemic effects	Respiratory system.
			· ·	
Bioaccumulation Potential Additional advice		<ul><li>of the polyme</li><li>Chemicals are of the polyme</li></ul>	e not readily available a	s they are bound within the matrix
		: No data availa	able.	
			able. CONSIDERATIONS	
Product		<ul> <li><b>13. DISPOSAL</b></li> <li>Like most the possible, recy generator of v classification,</li> </ul>	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
	aging	<ul> <li>13. DISPOSAL</li> <li>Like most the possible, recy generator of v classification, applicable feet</li> <li>Recycling is p has the respondent</li> </ul>	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r transportation and disp leral, state/provincial a preferred when possible nsibility for proper was n accordance with app	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
Product	aging	<ul> <li>13. DISPOSAL</li> <li>Like most the possible, recy generator of v classification, applicable feed</li> <li>Recycling is p has the respon and disposal i and local regularies</li> </ul>	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r transportation and disp leral, state/provincial a preferred when possible nsibility for proper was n accordance with app	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste material te classification, transportation
Product		<ul> <li>13. DISPOSAL</li> <li>Like most the possible, recy generator of v classification, applicable feed</li> <li>Recycling is p has the respon and disposal i and local regutes</li> <li>14. TRANSPO</li> </ul>	CONSIDERATIONS rmoplastics the produc cling is preferred to dis vaste material has the r transportation and disp leral, state/provincial a preferred when possible nsibility for proper was n accordance with app ilations.	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste material te classification, transportation



### MATERIAL SAFETY DATA SHEET

## FL PINK

Version Number 1.1 Revision Date 09/09/2003 Page 5 of 6 Print Date 11/12/2011

IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	ubstances (40 CFR 302)
Not applicable	
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extre	emely Hazardous Substance
Not applicable	
SARA Title III Section 313 Toxi	c Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Releas	e Inventory (NPRI)
Not applicable	
WHMIS Classification	: D2B
WHMIS Ingredient Discl	osure List
CAS-No. 7631-86-9	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Listed.
China IECS	: Listed.

		PolyOne.
POLYONE CORPORAT	TION	
MATERIAL SAFETY DATA SHE	ET	
FL PINK		
Version Number 1.1 Revision Date 09/09/2003		Page 6 of 6 Print Date 11/12/2011
Europe EINECS	: Not determined.	
Japan ENCS	: Listed.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	

 $\sim$ 

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.