MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

Version Number 1.2 Revision Date 01/05/2004 Page 1 of 7 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030GY533 MB132 PVC CC HMF
Product code	:	CC10041020
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Carbon black	1333-86-4	1 - 5
Titanium dioxide	13463-67-7	10 - 30
Calcium carbonate	1317-65-3	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

Version Number 1.2 Revision Date 01/05/2004 Page 2 of 7 Print Date 11/13/2011

Chronic exposure	: 1	Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	:	None known.
		4. FIRST AID MEASURES
Inhalation		Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion		Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes		Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin		Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5	FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	:	Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. AC	CIDENTAL RELEASE MEASURES
Personal precautions		Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions		Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up		Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

Version Number 1.2 Revision Date 01/05/2004 Page 3 of 7 Print Date 11/13/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA):	black	
	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
Quartz	0.05	Time Weighted Average	Respirable fraction.	ACGIH
	mg/m3	(TWA):		
	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance : Solid : Pellets

Specific Gravity: Not determined : Not determined

MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

Version Number 1.2 Revision Date 01/05/2004 Page 4 of 7 Print Date *11/13/2011*

Color Odor Melting point/range Boiling Point: Water solubility	: GREY: Very faint: Not determined: Not applicable: Insoluble	Bulk density Vapor pressure Vapour density pH	 Not established Not applicable Not applicable Not applicable
	10. STABILITY ANI) REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from ox decomposition, do		flame. To avoid thermal
Incompatible Materials	acetal copolymers a processing. At pro- destructive and invo mechanically clean quantities of these r	and with amine containin cessing conditions, these plve rapid degradation. T processing equipment to	materials are mutually Thoroughly purge and
Hazardous decomposition products	(NOx), hydrogen cl smoke are all possil or more) above 392	°F (200 °C) or short terr roduct decomposition and	rdous materials, and approximately 30 minutes n heating at 482 °F (250

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eves, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species



MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

Version Number 1.2

Revision Date 01/05/2004

Page 5 of 7 Print Date 11/13/2011

1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation. Long term exposure may cause caughing, chest pain, diminished chest expansion and possibly silicosis which is a scarring of the lungs.

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

	1	3. DISPOSAL CONSIDERATIONS	
Additional advice	:	No data available	
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.	
Persistence and degradability	:	Not readily biodegradable.	

PolyOne.

MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

ersion Number 1.2 evision Date 01/05/2004	Page 6 of Print Date 11/13/20	
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
14. TRANSPORT INFORMATION		
U.S. DOT Classification	: Not regulated for transportation.	
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on components.	
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.	
US. EPA CERCLA Hazardous	Substances (40 CFR 302)	
Not applicable		
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.	
SARA Title III Section 302 Ext	emely Hazardous Substance	
Not applicable		
SARA Title III Section 313 Tox	ic Chemicals:	
Not applicable Canadian Regulations:		
National Pollutant Relea	e Inventory (NPRI)	

MATERIAL SAFETY DATA SHEET 030GY533 MB132 PVC CC HMF

Version Number 1.2 Revision Date 01/05/2004 Page 7 of 7 Print Date *11/13/2011*

Not applicable

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

1333-86-4	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined
Philippines PICCS	: Not determined

:

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.