MATERIAL SAFETY DATA SHEET 030BN533 MB585 (360) PVC CCC HMF

Version Number 1.1 Revision Date 06/21/2004 Page 1 of 7 Print Date *11/14/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	030BN533 MB585 (360) PVC CCC HMF
Product code :	CC10041022
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	1 - 5
D&C red No. 9	5160-02-1	1 - 5
Calcium carbonate	1317-65-3	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET 030BN533 MB585 (360) PVC CCC HMF

Version Number 1.1 Revision Date 06/21/2004 Page 2 of 7 Print Date 11/14/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET 030BN533 MB585 (360) PVC CCC HMF

Version Number 1.1 Revision Date 06/21/2004 Page 3 of 7 Print Date 11/14/2011

Handling		Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.				
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.				
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally r	equired.		
Eye/Face Protection	: S	afety glasses with side-shields				
Hand protection	: P	Protective gloves.				
Skin and body protection	: L	Long sleeved clothing.				
Additional Protective Measures	: S	Safety shoes.				
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures		Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1		
	15	DEL	T . (. 1 . 1 (

Components	value	Exposure time Exposure type		LISU.
Calcium carbonate	5 mg/m3 PEL: Respirable fracti		Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH
		(TWA): black		
	3.5 mg/m3	PEL:	Total dust. as carbon	OSHA Z1
			black	
D&C red No. 9	0.5 mg/m3	Time Weighted Average	as Ba	ACGIH
		(TWA):		

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 BROWN
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable
 Not applicable

10. STABILITY AND REACTIVITY

3/7

PolyOne

MATERIAL SAFETY DATA SHEET 030BN533 MB585 (360) PVC CCC HMF

Version Number 1.1 Revision Date 06/21/2004 Page 4 of 7 Print Date *11/14/2011*

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
5160-02-1	D&C red No. 9	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	> 15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

MATERIAL SAFETY DATA SHEET 030BN533 MB585 (360) PVC CCC HMF

Version Number 1.1 Revision Date 06/21/2004 Page 5 of 7 Print Date 11/14/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Environmental Toxicity	: Chemicals are not readily available as they are bound within the
	polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the
	polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	

			<u>PolyOr</u>	n <u>e</u> .
POLYONE CORPORATIO	DN			
MATERIAL SAFETY DATA SHEET				
030BN533 MB585 (360) P	PVC CCC HMF			
Version Number 1.1 Revision Date 06/21/2004			Print Date	Page 6 of 7 11/14/2011
OSHA Status :	Classified as hazardous b	based on compor	ients.	
TSCA Status :	All components of this p Inventory.	roduct are listed	on or exempt from	the TSCA
US. EPA CERCLA Hazardous Sub	stances (40 CFR 302)			
Not applicable				
California Proposition : 65 SARA Title III Section 302 Extrem Not applicable SARA Title III Section 313 Toxic C			emical known to the	e State of
Chemical Name		CAS-No.	Weight %]
BARIUM COMPOUNDS		5160-02-1	3.34	
Canadian Regulations: National Pollutant Release In	nventory (NPRI)			
Not applicable				
WHMIS Classification :	D2A			
WHMIS Ingredient Disclosu	ure List			
CAS-No. 1333-86-4 5160-02-1				
DSL :	All components of this p Substances List (DSL) of		e Canadian Domes	tic

National Inventories:

Australia AICS	:	Not determined
China IECS	:	Listed
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined

		PolyOne.
OLYONE CORPORA	TION	
ATERIAL SAFETY DATA SHI		
30BN533 MB585 (360)) PVC CCC HM	
rsion Number 1.1 wision Date 06/21/2004		Page 7 of 7 Print Date 11/14/201
Korea KECI	: Not determined	
Philippines PICCS	: Listed	
	16. OTHER INFO	DRMATION