

#### MATERIAL SAFETY DATA SHEET

### YELLOW

Version Number 1.0 Page 1 of 7
Revision Date 08/12/2003 Print Date 11/11/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY : Product Stewardship (770) 271-5902

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : YELLOW
Product code : CC10041156
Chemical Name : Mixture
CAS-No. : Mixture

Product Use : Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Cadmium zinc sulfide ((Cd,Zn)S)	12442-27-2	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5
Lead chromate	7758-97-6	10 - 30

### 3. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.

**Chronic exposure** : Refer to Section 11 for Toxicological Information.



#### MATERIAL SAFETY DATA SHEET

### YELLOW

Version Number 1.0 Page 2 of 7
Revision Date 08/12/2003 Print Date 11/11/2011

Medical Conditions Aggravated by Exposure: : None known.

# 4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

### **5. FIRE-FIGHTING MEASURES**

Flash point : Not applicable

Flammable Limits

Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not relevant

Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foam.

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

None

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not

be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.

### 7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat



#### MATERIAL SAFETY DATA SHEET

### YELLOW

Version Number 1.0 Page 3 of 7
Revision Date 08/12/2003 Print Date 11/11/2011

only in areas with appropriate exhaust ventilation.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

Safety shoes.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Cadmium zinc sulfide	0.005	Time Weighted Average	as Cd	OSHA
((Cd,Zn)S)	mg/m3	(TWA):		
	0.01	Time Weighted Average	as Cd	ACGIH
	mg/m3	(TWA):		
	0.002	Time Weighted Average	Respirable fraction. as	ACGIH
	mg/m3	(TWA):	Cd	
Lead chromate	1 mg/m3	PEL:	as Cr	OSHA Z1
	0.05	Time Weighted Average	Dust. as Pb	OSHA
	mg/m3	(TWA):		
	0.03	OSHA Action level:	Dust. as Pb	OSHA
	mg/m3			
	0.012	Time Weighted Average	as Cr	ACGIH
	mg/m3 (TWA):			
	0.05	Time Weighted Average	as Pb	ACGIH
	mg/m3	(TWA):		
Titanium dioxide	Titanium dioxide 10 mg/m3			ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid Evaporation rate : Not applicable.



#### MATERIAL SAFETY DATA SHEET

### YELLOW

Version Number 1.0 Page 4 of 7
Revision Date 08/12/2003 Print Date 11/11/2011

: Pellets Specific Gravity : Not determined Appearance Color : YELLOW Bulk density : Not established Odor : Very faint Vapor pressure : Not applicable Melting point/range : Not determined Vapor density : Not applicable **Boiling Point:** : Not applicable pН : Not applicable

Water solubility : Insoluble

### 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents.

Hazardous decomposition

products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12442-27-2	Cadmium zinc sulfide	Highly Toxic	Refer to LC50 / LD50 Data on
	((Cd,Zn)S)		MSDS
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
7758-97-6	Lead chromate	Systemic effects	central nervous system,
			reproductive system.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
7758-97-6	Lead chromate	Oral LD50	> 12 gm/kg	mouse

#### Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
12442-27-2	Cadmium zinc sulfide	yes	1	no
	((Cd,Zn)S)			
7758-97-6	Lead chromate	no	no	1



#### MATERIAL SAFETY DATA SHEET

### YELLOW

 Version Number 1.0
 Page 5 of 7

 Revision Date 08/12/2003
 Print Date 11/11/2011

#### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

#### NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

### **Additional Health Hazard Information:**

Cadmium zinc sulfide ((Cd,Zn)S) 12442-27-2 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.

### **Additional Health Hazard Information:**

Lead chromate 7758-97-6 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

12	FCOL	OCICAL	INFORMATION
14.	LUUL	MILLAL	INFURMATION

Persistence and degradability : Not readily biodegradable.

Environmental Toxicity : Chemicals are not readily available as they are bound within the matrix

of the polymer.

Bioaccumulation Potential : Chemicals are not readily available as they are bound within the matrix

of the polymer.

Additional advice : No data available.

#### 13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastics the product can be recycled. Where

possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

Contaminated packaging : Recycling is preferred when possible. The generator of waste material

has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial

and local regulations.

#### 14. TRANSPORT INFORMATION

U.S. DOT Classification : Refer to specific regulation.

ICAO/IATA : Refer to specific regulation.



#### MATERIAL SAFETY DATA SHEET

# YELLOW

 Version Number 1.0
 Page 6 of 7

 Revision Date 08/12/2003
 Print Date 11/11/2011

IMO / IMDG : Refer to specific regulation.

### 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Not applicable

California Proposition

65

WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a

chemical known to the State of California to cause birth defects or

other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CADMIUM COMPOUNDSZINC COMPOUNDS	12442-27-2	0.55
CHROMIUM VI COMPOUNDSLEAD	7758-97-6	13.22
COMPOUNDS, INORGANICLEAD		
COMPOUNDS		

### Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Transfer Tollaram Trelease Introduct (171 111)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Cadmium zinc sulfide ((Cd,Zn)S)	12442-27-2	0.55	243
Cadmium zinc sulfide ((Cd,Zn)S)	12442-27-2	0.55	241
Lead chromate	7758-97-6	13.22	245
Lead chromate	7758-97-6	13.22	246

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List



#### MATERIAL SAFETY DATA SHEET

# YELLOW

 Version Number 1.0
 Page 7 of 7

 Revision Date 08/12/2003
 Print Date 11/11/2011

CAS-No. 7758-97-6

DSL : All components of this product are on the Canadian Domestic

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Listed.

Philippines PICCS : Listed.

### 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.