

MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 08/19/2003

Page 1 of 8 Print Date *11/12/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	ORANGE
Product code	:	CC10041187
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
C.I. Pigment Red 108	58339-34-7	5 - 10
Molybdate orange (Lead chromate pigment)	12656-85-8	5 - 10
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eves. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 08/19/2003 Page 2 of 8 Print Date 11/12/2011

Medical Conditions : None known. Aggravated by Exposure: :					
		4. FIRST AID MEASURES			
		4. FIRST AID MEASURES			
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
		5. FIRE-FIGHTING MEASURES			
Flash point	:	Not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	: : : : : : : : : : : : : : : : : : : :	Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive			
Procedures Unusual Fire/Explosion Hazards	:	pressure mode should be worn to prevent inhalation of airborne contaminants. None			
	6. A	CCIDENTAL RELEASE MEASURES			
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			
		7. HANDLING AND STORAGE			



MATERIAL SAFETY DATA SHEET **ORANGE**

ersion Number 1.0 evision Date 08/19/2003		Page 3 of 8 Print Date 11/12/2011			
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.			
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EXP	OSUF	RE CONTROLS / PERSONAL PROTECTION			
Respiratory protection	:	No personal respiratory protective equipment normally required.			
Eye/Face Protection	:	Safety glasses with side-shields.			
Hand protection	:	Protective gloves.			
Skin and body protection	:	Long sleeved clothing.			
Additional Protective Measures	:	Safety shoes.			
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.			
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.			
Exposure limit(s)					



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0

Revision Date 08/19/2003

Page 4 of 8 Print Date 11/12/2011

Components	Value	Exposure time	Exposure type	List:
C.I. Pigment Red 108	0.005	Time Weighted Average	as Cd	OSHA
-	mg/m3	(TWA):		
	0.0025	OSHA Action level:	as Cd	OSHA
	mg/m3			
	0.2 mg/m3	PEL:	as Se	OSHA Z1
C.I. Pigment Red 108	0.01	Time Weighted Average	as Cd	ACGIH
	mg/m3	(TWA):		
C.I. Pigment Red 108	0.2 mg/m3	Time Weighted Average	as Se	ACGIH
		(TWA):		
C.I. Pigment Red 108	0.002	Time Weighted Average	Respirable fraction. as	ACGIH
	mg/m3	(TWA):	Cd	
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Molybdate orange	0.05	Time Weighted Average	as Pb	OSHA
(Lead chromate	mg/m3	(TWA):		
pigment)				
Molybdate orange	0.01	Time Weighted Average	as Cr	ACGIH
(Lead chromate	mg/m3	(TWA):		
pigment) Molybdate orange	0.05	Time Weighted Average	as Pb	ACGIH
(Lead chromate	mg/m3	(TWA):	as 1 U	ACOIII
pigment)	mg/m3	$(\mathbf{I} \mathbf{W} \mathbf{A}).$		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	-	(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form: SolidAppearance: PelletsColor: ORANOdor: Very faMelting point/range: Not detBoiling Point:: Not appWater solubility: Insolubility
 - Pellets
 Pellets
 ORANGE
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH
- Not applicable.Not determinedNot establishedNot applicableNot applicable
- : Boiling Point: : Not applicable Not applicable pН : Water solubility : Insoluble **10. STABILITY AND REACTIVITY** Stability : Stable. Hazardous Polymerization · Will not occur. Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. Incompatible Materials Incompatible with strong acids and oxidizing agents. : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen Hazardous decomposition : (NOx), other hazardous materials, and smoke are all possible. products



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 08/19/2003

Page 5 of 8 Print Date 11/12/2011

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
58339-34-7	C.I. Pigment Red 108	Irritant	Eyes, Skin.
		Systemic effects	Liver, central nervous system, Kidney.
12656-85-8	Molybdate orange (Lead chromate pigment)	Irritant	Eyes, Skin.
		Systemic effects	central nervous system, reproductive system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
58339-34-7	C.I. Pigment Red 108	yes	1	1
12656-85-8	Molybdate orange (Lead chromate pigment)	no	no	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

C.I. Pigment Red 108 58339-34-7 Can produce rapid and sometimes fatal pulmonary edema, chronic absorption leads to liver and kidney damage.

Additional Health Hazard Information:

Molybdate orange (Lead chromate pigment) 12656-85-8 Systemic effects include neurotoxic, teratogenic, fetotoxic and reproductive with abdominal pain, anemia, pallor, decreased hand grip strength with characteristic "wrist drop".

12. ECOLOGICAL INFORMATION



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 08/19/2003	Page 6 of 8 Print Date 11/12/2011
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	Defente merifie mendetien
U.S. DOT Classification ICAO/IATA	Refer to specific regulation.Refer to specific regulation.
IMO / IMDG	Refer to specific regulation.
	. Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer., WARNING! This product contains a



MATERIAL SAFETY DATA SHEET **ORANGE**

Version Number 1.0 Revision Date 08/19/2003

Page 7 of 8 Print Date 11/12/2011

chemical known to the State of California to cause birth defects or other reproductive harm.

SARA Title III Section 302 Extremely Hazardous Substance

Not applicable

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
CADMIUM COMPOUNDSSELENIUM	58339-34-7	5.62
COMPOUNDS		
CHROMIUM VI COMPOUNDSLEAD	12656-85-8	7.60
COMPOUNDS, INORGANICLEAD		
COMPOUNDS		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight %	NPRI ID#
C.I. Pigment Red 108	58339-34-7	5.62	243
C.I. Pigment Red 108	58339-34-7	5.62	210
Molybdate orange (Lead chromate pigment)	12656-85-8	7.60	245
Molybdate orange (Lead chromate pigment)	12656-85-8	7.60	246

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
58339-34-7	
12656-85-8	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Listed.
Korea KECI	:	Listed.

:



MATERIAL SAFETY DATA SHEET

ORANGE

Version Number 1.0 Revision Date 08/19/2003 Page 8 of 8 Print Date 11/12/2011

Philippines PICCS : Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.