MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0 Revision Date 08/18/2003

Page 1 of 8 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PEWTER GM 382E-7536C UV CO-PP
Product code	:	CC10041422
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	0.1 - 1
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	10 - 30
Calcium carbonate	1317-65-3	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0 Revision Date 08/18/2003 Page 2 of 8 Print Date 11/12/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0				
Revision Date 08/18/2003				

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
 8. EXPOS	UR	E CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		



MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0 Revision Date 08/18/2003 Page 4 of 8 Print Date 11/12/2011

Components	Value	Exposure time	Exposure type	List:
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	1 mg/m3	PEL:	as Ni	OSHA Z1
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	0.5 mg/m3	Time Weighted Avera (TWA):	age as Sb	ACGIH
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	0.2 mg/m3	Time Weighted Avera (TWA):	nge Inhalable fraction. as Ni	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Carbon black	3.5 mg/m3	Time Weighted Avera (TWA):	black	ACGIH
Carbon black	3.5 mg/m3	PEL:	Total dust. as carbon black	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Avera (TWA):		ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1
Form Appearance Color	: Solid : Pellet : GRE	s S	pecific Gravity : No	t applicable. t determined t established
Odor	: Very			t applicable
Melting point/range				t applicable
Boiling Point: Water solubility	: Not a : Insolu		H : No	t applicable
	10. S	TABILITY AND REA	CTIVITY	
Stability	: St	able.		
Hazardous Polymerizatio	on : W	ill not occur.		
Conditions to avoid		eep away from oxidizing composition, do not ove	g agents and open flame. To prheat.	avoid thermal
Incompatible Materials	: In	compatible with strong a	acids and oxidizing agents.	
Hazardous decompositio products			rbon monoxide (CO), oxides aterials, and smoke are all po	

MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0 Revision Date 08/18/2003 Page 5 of 8 Print Date 11/12/2011

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	Irritant	Eyes, Skin.
		sensitizer	Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Carcinogenicity:

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1333-86-4	Carbon black	no	2B	no
8007-18-9	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	no	1	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0 Revision Date 08/18/2003 Page 6 of 8 Print Date 11/12/2011

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

Additional Health Hazard Information:

Nickel antimony yellow rutile (C.I. Pigment Yellow 53) 8007-18-9 Skin sensitizer "nickel itch", with pulmonary, brain, liver, kidney andmuscle effects.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Refer to specific regulation.
ICAO/IATA	: Refer to specific regulation.
IMO / IMDG	: Refer to specific regulation.
	15. REGULATORY INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

sion Number 1.0 ision Date 08/18/2003		Prir	Page 7 nt Date 11/12/2
US Regulations:			
OSHA Status : Classified as hazardo	us based on com	ponents.	
TSCA Status : All components of th Inventory.	is product are lis	sted on or exemp	pt from the TSCA
US. EPA CERCLA Hazardous Substances (40 CFR 302)			
Not applicable			
California Proposition : WARNING! This pr 65 California to cause ca		chemical knov	vn to the State of
SARA Title III Section 302 Extremely Hazardous Substan	ce		
Not applicable			
SARA Title III Section 313 Toxic Chemicals:			
Chemical Name	CAS-No.	Weight	0/6
NICKEL COMPOUNDSANTIMONY COMPOUNDS	8007-18-9	18.07	/0
Canadian Regulations:		·	
National Pollutant Release Inventory (NPRI)			
Chemical Name Nickel antimony yellow rutile (C.I. Pigment Yellow	CAS-No. 8007-18-9	Weight %	NPRI ID# 168
53)	0007-10-2	10.07	100
Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	18.07	17
WHMIS Classification : D2A			
WHMIS Ingredient Disclosure List			
CAS-No. 8007-18-9			
DSL : All components of th Substances List (DSL			Domestic
National Inventories:			



MATERIAL SAFETY DATA SHEET PEWTER GM 382E-7536C UV CO-PP

Version Number 1.0 Revision Date 08/18/2003 Page 8 of 8 Print Date *11/12/2011*

Australia AICS	: Listed.
China IECS	: Listed.
Europe EINECS	: Not determined.
Japan ENCS	: Listed.
Korea KECI	: Listed.
Philippines PICCS	: Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.