

MATERIAL SAFETY DATA SHEET

OAK

Version Number 1.0 Revision Date 08/22/2003

Page 1 of 6 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	OAK
Product code	:	CC10041563
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Iron oxide	1309-37-1	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

OAK

Version Number 1.0 Revision Date 08/22/2003 Page 2 of 6 Print Date 11/12/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not relevant Carbon dioxide blanket, water spray, dry powder, foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

OAK

Version Number 1.0				
Revision Date	08/22/2003			

Storage

Page 3 of 6 Print Date 11/12/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Iron oxide	5 mg/m3	Time Weighted Average	Dust and fume. as Fe	ACGIH
		(TWA):		
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

BROWNVery faintNot determinedNot applicableInsoluble

: Solid

:

: Pellets

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH

Keep away from oxidizing agents and open flame. To avoid thermal

Not applicable.Not determined

: Not established

: Not applicable

: Not applicable

: Not applicable

10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid

3/6



MATERIAL SAFETY DATA SHEET

OAK

sion Date 08/22/20	003		Page 4 Print Date 11/12/2
	decompos	sition, do not overheat.	
Incompatible Materia	oxidizing agents.		
Hazardous decompos products		ioxide (CO2), carbon mono her hazardous materials, an	oxide (CO), oxides of nitrogen nd smoke are all possible.
	11. TOXICOL	OGICAL INFORMATIO	ON
health data for the in Toxicity Overview	dividual components whic	ch comprise the mixture.	are effects listed are based on exis have the following characteristic
CAS-No.	Chemical Name	Effect	Target Organ
1309-37-1	Iron oxide	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
Environmental Toxic Bioaccumulation Pot	of the pol	ymer. s are not readily available a	s they are bound within the matrix s they are bound within the matrix
Additional advice	: No data a 13. DISPOS		
Additional advice Product Contaminated packa	13. DISPOS : Like most possible, i generator classificat applicable ging : Recycling has the re and dispo	vailable. AL CONSIDERATIONS t thermoplastics the product recycling is preferred to dis- of waste material has the re- tion, transportation and dis- e federal, state/provincial and g is preferred when possible sponsibility for proper was	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with
Product	13. DISPOS : Like most possible, i generator classificat applicable ging : Recycling has the re and dispo and local	vailable. CONSIDERATIONS t thermoplastics the product recycling is preferred to dist of waste material has the rest tion, transportation and dist e federal, state/provincial a g is preferred when possible sponsibility for proper was sal in accordance with app	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste material te classification, transportation
Product	13. DISPOS : Like most possible, i generator classificat applicable ging : Recycling has the re and dispo and local 14. TRANS	vailable. AL CONSIDERATIONS t thermoplastics the production recycling is preferred to dist of waste material has the r tion, transportation and dist e federal, state/provincial a g is preferred when possible sponsibility for proper was sal in accordance with app regulations.	ct can be recycled. Where sposal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste material te classification, transportation



MATERIAL SAFETY DATA SHEET

OAK

Version Number 1.0 Revision Date 08/22/2003 Page 5 of 6 Print Date 11/12/2011

	15 DECI	LATORY INFORMATION	
	15. K EGU	LAIOKI INFORMATION	
US Regulations:			
OSHA Status	: Classif	ied as hazardous based on compo	onents.
TSCA Status	: All con Invento	mponents of this product are listed ory.	l on or exempt from the TSCA
US. EPA CERCLA Haza	rdous Substances ((40 CFR 302)	
Not applicabl	le		
California Propos 65	ition : This pr	oduct does not contain a substanc	e listed by California Prop 65
SARA Title III Section 30	02 Extremely Haza	ardous Substance	
Not applicable			
II			
CADA Title III Castian 2	12 Taria Chamiaal	l	
	13 Toxic Chemical		
Chemical Name		CAS-No.	Weight %
Chemical Name ZINC COMPOU			Weight % 1.32
Chemical Name ZINC COMPOU		CAS-No.	
Chemical Name ZINC COMPOUT	NDS	CAS-No. 68187-51-9	
Chemical Name ZINC COMPOU	NDS	CAS-No. 68187-51-9	
Chemical Name ZINC COMPOUT	NDS	CAS-No. 68187-51-9	
Chemical Name ZINC COMPOUT	NDS Release Inventory	CAS-No. 68187-51-9	
Chemical Name ZINC COMPOUT Canadian Regulations: National Pollutant	NDS Release Inventory ation : D2B	CAS-No. 68187-51-9	
Chemical Name ZINC COMPOUT Canadian Regulations: National Pollutant WHMIS Classific WHMIS Ingredien	NDS Release Inventory ation : D2B It Disclosure List	CAS-No. 68187-51-9	
Chemical Name ZINC COMPOUT Canadian Regulations: National Pollutant WHMIS Classific	NDS Release Inventory ation : D2B It Disclosure List	CAS-No. 68187-51-9	
ZINC COMPOUI Canadian Regulations: National Pollutant WHMIS Classific WHMIS Ingredien CAS-No.	NDS Release Inventory ation : D2B at Disclosure List	CAS-No. 68187-51-9	1.32
Chemical Name ZINC COMPOUN Canadian Regulations: National Pollutant WHMIS Classific WHMIS Ingredien CAS-No. 1309-37-	NDS Release Inventory ation : D2B at Disclosure List	CAS-No. 68187-51-9	1.32





MATERIAL SAFETY DATA SHEET

OAK

Version Number 1.0 Revision Date 08/22/2003

Page 6 of 6 Print Date *11/12/2011*

China IECS	:	Listed.
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.