

MATERIAL SAFETY DATA SHEET SUPER VE SILVER BLUE

Version Number 1.1 Revision Date 01/05/2004 Page 1 of 6 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	SUPER VE SILVER BLUE
Product code	:	CC10044517
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	57583-35-4	1 - 5
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes Skin	Particulates, like other inert materials can be mechanically irritating.Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET SUPER VE SILVER BLUE

Version Number 1.1 Revision Date 01/05/2004 Page 2 of 6 Print Date 11/13/2011

-		-
Medical Conditions Aggravated by Exposure:	:	None known.
		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	4	5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	: : : :	Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. A(CCIDENTAL RELEASE MEASURES
		Wear appropriate personal protection during cleanup, such as
Personal precautions	•	impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.



MATERIAL SAFETY DATA SHEET SUPER VE SILVER BLUE

Version Number 1.1 Revision Date 01/05/2004 Page 3 of 6 Print Date 11/13/2011

		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUE	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Components Value Exposure time Exposure type List: OSHA Z1 8-Oxa-3,5-dithia-4-sta 0.1 mg/m3 PEL: as Sn nnatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester 0.1 mg/m3 Time Weighted Average as Sn ACGIH (TWA): 0.2 mg/m3 Short Term Exposure Limit ACGIH as Sn (STEL): Titanium dioxide 10 mg/m3 Time Weighted Average ACGIH (TWA): 15 mg/m3 PEL: Total dust. OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color
- : Solid: Pellets: BLUE

Evaporation rate Specific Gravity: Bulk density Not applicableNot determinedNot established



MATERIAL SAFETY DATA SHEET SUPER VE SILVER BLUE

Version Number 1.1 Revision Date 01/05/2004 Page 4 of 6 Print Date 11/13/2011

Melting point/range	: No : No	ery faint ot determined ot applicable soluble	Vapor pressure Vapour density pH	: :	Not applicable Not applicable Not applicable
	10	. STABILITY AND RE	ACTIVITY		
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:	Keep away from oxidizide decomposition, do not o		me.	To avoid thermal
Incompatible Materials	:	Avoid contact with stror acetal copolymers and v processing. At processi destructive and involve mechanically clean proc quantities of these mater Prevent cross contamina	with amine containing n ng conditions, these ma rapid degradation. The ressing equipment to av- rials from coming in co	nate ateri orou void	rials during als are mutually ghly purge and even trace
Hazardous decomposition products	:	Carbon dioxide (CO2), (NOx), hydrogen chlorid smoke are all possible. or more) above 392 °F (°C) may result in product monoxide and hydrogen	de (HCl), other hazardo Prolonged heating (app 200 °C) or short term h ct decomposition and e	ous 1 orox neati	materials, and imately 30 minutes ing at 482 °F (250

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

of the polymer.

Environmental Toxicity

: Chemicals are not readily available as they are bound within the matrix



MATERIAL SAFETY DATA SHEET SUPER VE SILVER BLUE

Version Number 1.1 Revision Date 01/05/2004 Page 5 of 6 Print Date 11/13/2011

Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 E	xtremely Hazardous Substance
Not applicable	

PolyOne

MATERIAL SAFETY DATA SHEET SUPER VE SILVER BLUE

Version Number 1.1 Revision Date 01/05/2004 Page 6 of 6 Print Date *11/13/2011*

Not applicable Canadian Regulations:	
National Pollutant Rele	ase Inventory (NPRI)
Not applicable	
WHMIS Classification	: D2B
WHMIS Ingredient Dis	closure List
CAS-No. 57583-35-4	
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Listed
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Listed

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.