MATERIAL SAFETY DATA SHEET MARIGOLD 3

Version Number 1.1 Revision Date 04/24/2007 Page 1 of 6 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MARIGOLD 3
Product code	:	CC10044939
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	5 - 10
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET MARIGOLD 3

Version Number 1.1 Revision Date 04/24/2007 Page 2 of 6 Print Date 11/27/2011

Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Elemente Limite		
Flammable Limits Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
Autoignition temperature	:	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption



MATERIAL SAFETY DATA SHEET MARIGOLD 3

Version Number 1.1 Revision Date 04/24/2007 Page 3 of 6 Print Date 11/27/2011

8 1	TYPOSUDE	CONTROLS / PERSONAL	PPOTECTION	
0.1	LAFUSUKE	CONTROLS / FERSONAL	FROIECTION	
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		afety practic
Engineering measures Exposure limit(s)		leat only in areas with appropri ppropriate exhaust ventilation a		Provide
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z
	15 mg/m3	PEL:	Total dust.	OSHA Z
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Rutile, antimony chromium buff	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	PEL:	as Cr	OSHA Z
	0.5 mg/m3	Time Weighted Average		MX OEL
		(1 WA):		
	0.5 mg/m3	(TWA): Time Weighted Average (TWA):	as Sb	ACGIH
	0.5 mg/m3		as Sb as Sb	ACGIH OSHA Z

9. PHYSICAL AND CHEMICAL PROPERTIES

Time Weighted Average

(TWA):

- Form Appearance Color Odour Melting point/range Boiling Point:
- Solid
 pellets
 YELLOW
 Very faint
 Not determined
 Not applicable

0.5 mg/m3

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH

as Sb

Not applicable
Not determined
Not established
Not applicable
Not applicable
Not applicable

MX OEL

MATERIAL SAFETY DATA SHEET MARIGOLD 3

Version Number 1.1 Revision Date 04/24/2007 Page 4 of 6 Print Date <u>11/</u>27/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony	Irritant	Eyes, Skin, Respiratory system.
	chromium buff		
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound with polymer matrix.	hin the
Bioaccumulation Potential	Chemicals are not readily available as they are bound with polymer matrix.	hin the
Additional advice	No data available	
	3. DISPOSAL CONSIDERATIONS	
Product	Like most thermoplastic plastics the product can be recyc	led. Where



MATERIAL SAFETY DATA SHEET MARIGOLD 3

sion Number 1.1 <i>r</i> ision Date 04/24/2007	Page 5 of 6 Print Date 11/27/2013
Contaminated packaging	 possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal.
	14. TRANSPORT INFORMATION
U.S. DOT Classification ICAO/IATA (air) IMO / IMDG (maritime)	 Not regulated for transportation. Refer to specific regulation. Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 E	xtremely Hazardous Substance
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	oxic Chemicals:
Unless specific chemicals are	identified under this section, this product is Not Applicable under this regulation CAS-No. Weight %

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET MARIGOLD 3

Version Number 1.1 Revision Date 04/24/2007 Page 6 of 6 Print Date 11/27/2011

Chemical Name	CAS-N	No. Weig	Weight %	
CHROMIUM III COMPOU	68186-9	90-3 5.00	- 10.00	
COMPOUNDS				
anadian Regulations:				
-				
National Pollutant Rele Chemical Name	ease Inventory (NPF		W/a: alat 0/	
Rutile, antimony chromium	buff	CAS-No. 68186-90-3	Weight % 5.00 - 10.00	NPRI ID‡ 69
Ruthe, antimony enronnum	Juli	00100-70-5	5.00 - 10.00	17
WHMIS Classification	n : D2B			
	1 1 .			
WHMIS Ingredient Dis	sclosure List			
CAS-No.				
68186-90-3				
DSL	: All compon	ents of this product a	ra on the Canadi	n Domostic
DSL		List (DSL) or are exer		
			-	
ational Inventories:				
Australia AICS	: Listed			
China IECS	. Tistad			
Uning IEUN	: Listed			
	. 215.000			
Europe EINECS	: Not determin	ned		
Europe EINECS	: Not determin			
Europe EINECS	: Not determin			
Europe EINECS Japan ENCS Korea KECI	: Not determir : Not determir : Listed			
Europe EINECS Japan ENCS	: Not determin : Not determin			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.