MATERIAL SAFETY DATA SHEET **19025-ZO**

Version Number 1.2 Revision Date 01/12/2007

Page 1 of 7 Print Date 11/25/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	19025-ZO
Product code	:	CC10045023
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %	
Vinyl acetate	108-05-4	0.1 - 1	
Zinc oxide	1314-13-2	10 - 30	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET **19025-ZO**

Version Number 1.2 Revision Date 01/12/2007 Page 2 of 7 Print Date 11/25/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
Lower explosion limit	:	Not applicable
	:	Not applicable
Autoignition temperature Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting		Fullface calf contained breathing apparetus (SCPA) used in positive
Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	•	Keep containers dry and tightly closed to avoid moisture absorption

2/7



MATERIAL SAFETY DATA SHEET 19025-ZO

Version Number 1.2 Revision Date 01/12/2007

Page 3 of 7 Print Date 11/25/2011

ð. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION		
Respiratory protection	: N	lo personal respiratory protecti	ve equipment normally re	equired.	
Eye/Face Protection	: Safety glasses with side-shields.				
Hand protection	: Protective gloves.				
Skin and body protection	: L	ong sleeved clothing.			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		fety practic	
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation		Provide	
Exposure limit(s) Components	Value	Exposure time	Exposure type	List:	
Vinyl acetate	10 ppm	Time Weighted Average			
v myr acciaic		Thic weighted Average		ACGIH	
v myr acetate		(TWA):		ACGIH	
	15 ppm	(TWA): Short Term Exposure Limit (STEL):		ACGIH	
Zinc oxide	15 ppm 10 mg/m3	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA):	Total dust. as Zn	ACGIH ACGIH	
	15 ppm 10 mg/m3 5 mg/m3	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL:	Respirable dust. as Zn	ACGIH ACGIH OSHA ZI	
	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL:	Respirable dust. as Zn Total dust. as Zn	ACGIH ACGIH OSHA ZI OSHA ZI	
	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3 2 mg/m3	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA):	Respirable dust. as Zn Total dust. as Zn Respirable fraction.	ACGIH ACGIH OSHA ZI OSHA ZI ACGIH	
	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average	Respirable dust. as Zn Total dust. as Zn	ACGIH ACGIH OSHA ZI OSHA ZI	
	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3 2 mg/m3 10 mg/m3	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit	Respirable dust. as Zn Total dust. as Zn Respirable fraction. Respirable fraction.	ACGIH ACGIH OSHA ZI ACGIH	
Zinc oxide	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3 2 mg/m3 10 mg/m3 9. PHYSIC : Solic : Pelle	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	Respirable dust. as Zn Total dust. as Zn Respirable fraction. Respirable fraction. OPERTIES ration rate : Not a in the intervention of the intervent	ACGIH ACGIH OSHA ZI OSHA ZI ACGIH ACGIH applicable determined	
Zinc oxide Zinc oxide	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3 2 mg/m3 10 mg/m3 9. PHYSIC : Solic : Pelle : TRA	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO the Evapor ets Specific NSPARENT	Respirable dust. as Zn Total dust. as Zn Respirable fraction. Respirable fraction. OPERTIES ration rate : Not a ic Gravity: ic Gravity: : Not a ic on sity	ACGIH ACGIH OSHA ZI OSHA ZI ACGIH ACGIH ACGIH	
Zinc oxide Zinc oxide	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3 2 mg/m3 10 mg/m3 9. PHYSIC : Solic : Pelle : TRA : Very	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor Specific NSPARENT Bulk dy faint Vapor	Respirable dust. as Zn Total dust. as Zn Respirable fraction. Respirable fraction. PERTIES ration rate : Not a construction of a construct	ACGIH ACGIH OSHA ZI OSHA ZI ACGIH ACGIH ACGIH	
Zinc oxide Zinc oxide	15 ppm 10 mg/m3 5 mg/m3 15 mg/m3 2 mg/m3 10 mg/m3 10 mg/m3 9. PHYSIC : Solic : Pelle : TRA : Very : Not of	(TWA): Short Term Exposure Limit (STEL): Time Weighted Average (TWA): PEL: PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO d Evapor Specific NSPARENT Bulk dy faint Vapor	Respirable dust. as Zn Total dust. as Zn Respirable fraction. Respirable fraction. PERTIES ration rate : Not a consity ic Gravity: : Not a consity pressure : Not a consity r density : Not a consity	ACGIH ACGIH OSHA ZI OSHA ZI ACGIH ACGIH ACGIH	





MATERIAL SAFETY DATA SHEET **19025-ZO**

Version Number 1.2 Revision Date 01/12/2007

Page 4 of 7 Print Date 11/25/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
108-05-4	Vinyl acetate	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system.
1314-13-2	Zinc oxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
108-05-4	Vinyl acetate	LC50	11400 mg/m3	rat
		Oral LD50	2,920 mg/kg	rat
		Dermal LD50	2,335 mg/kg	rabbit
1314-13-2	Zinc oxide	LC50	2500 mg/m3	mouse
		Oral	7,950	mousemouse
		LD50Oral	mg/kg7,950	
		LD50	mg/kg	

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
108-05-4	Vinyl acetate	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

POLYONE CORPORATION

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 19025-ZO

Version Number 1.2 Revision Date 01/12/2007 Page 5 of 7 Print Date 11/25/2011

The component is known to be a human carcinogen.
 The component is reasonably anticipated to be a human carcinogen.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materi has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSC Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	
	5/7

PolyOne

MATERIAL SAFETY DATA SHEET **19025-ZO**

Version Number 1.2 Revision Date 01/12/2007 Page 6 of 7 Print Date 11/25/2011

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	% in Product	RQ for
			component
Vinyl acetate	108-05-4	0.10 - 1.00	5,000 lbs

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight %
VINYL ACETATE MONOMERVINYL ACETATE	108-05-4	0.10 - 1.00
ZINC COMPOUNDS	1314-13-2	10.00 - 30.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)			
Chemical Name	CAS-No.	Weight %	NPRI ID#
Vinyl acetate	108-05-4	0.10 - 1.00	227
Zinc oxide	1314-13-2	10.00 - 30.00	231

WHMIS Classification : D1B

WHMIS Ingredient Disclosure List

CAS-No.	
1314-13-2	

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed

:



MATERIAL SAFETY DATA SHEET **19025-ZO**

Version Number 1.2 Revision Date 01/12/2007 Page 7 of 7 Print Date 11/25/2011

Japan ENCS : Listed

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.