

MATERIAL SAFETY DATA SHEET YELLOW 109C

Version Number 1.0 Revision Date 10/29/2003

Page 1 of 6 Print Date 11/12/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	YELLOW 109C
Product code	:	CC10045207
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET YELLOW 109C

Version Number 1.0 Revision Date 10/29/2003 Page 2 of 6 Print Date 11/12/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET YELLOW 109C

Version Number 1.0 Revision Date 10/29/2003

Storage

Page 3 of 6 Print Date 11/12/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally requ	uired.
Eye/Face Protection	: Safety glasses with side-shields.	
Hand protection	: Protective gloves. Refer to equipment supplier to ensure pr	otection.
Skin and body protection	: Long sleeved clothing.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safe Wash hands before breaks and at the end of workday.	ty practice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Pr appropriate exhaust ventilation at machinery.	ovide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form	: Solid	Evaporation rate	: Not applicable		
Appearance	: Pellets	Specific Gravity	: Not determined		
Color	: YELLOW	Bulk density	: Not established		
Odor	: Very faint	Vapor pressure	: Not applicable		
Melting point/range	: Not determined	Vapour density	: Not applicable		
Boiling Point:	: Not applicable pH : Not applica				
Water solubility	: Insoluble				
	10 STADII ITV AN	D REACTIVITY			
	IU. STADILITT AND				
Stability	: Stable.				
Stability Hazardous Polymerization					



MATERIAL SAFETY DATA SHEET YELLOW 109C

rsion Number 1.0 vision Date 10/29/20	003			Page 4 o Print Date <i>11/12/20</i>	
		decomposition	n, do not overheat.		
Incompatible Materi	als	: Incompatible	with strong acids and o	oxidizing agents.	
Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.					
	-	11. TOXICOLOG	ICAL INFORMATIO	DN	
This mixture has not health data for the in Toxicity Overview				are effects listed are based on exist	
This product contain	s the follow	ving components wh	nich in their pure form	have the following characteristics:	
CAS-No.	C	hemical Name	Effect	Target Organ	
1317-65-3	Calciur	n carbonate	Irritant	Eyes, Skin.	
			Systemic effects	Eyes, Skin, Respiratory system.	
13463-67-7	Titaniu	m dioxide	Systemic effects	Respiratory system.	
			AL INFORMATION	-	
Environmental Toxic Bioaccumulation Po Additional advice	-	of the polymerChemicals are of the polymerNo data availa	r. not readily available a r.	s they are bound within the matrix s they are bound within the matrix	
		13. DISI OSAL	CONSIDERATIONS		
Product		possible recyc generator of w classification,	ling is preferred to disp vaste material has the r	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations.	
Contaminated packa	ging	has the respon		e. The generator of waste material te classification, transportation	
		and local regu	lations.	licable federal, state/provincial	
			lations. RT INFORMATION	licable federal, state/provincial	



MATERIAL SAFETY DATA SHE	ET	
YELLOW 109C		
Version Number 1.0 Revision Date 10/29/2003		Page 5 of 6 Print Date 11/12/2011
1010011040 10120,2000		
ICAO/IATA (air)	: Refer to specific regulation.	
IMO / IMDG (maritime)	: Refer to specific regulation.	
	15. REGULATORY INFORMATION	
US Regulations:		
OSHA Status	: Classified as hazardous based on component	s.
TSCA Status	: All components of this product are listed on Inventory.	or exempt from the TSCA
US. EPA CERCLA Hazardous S	ubstances (40 CFR 302)	
Not applicable		
California Proposition 65	: WARNING! This product contains a chemic California to cause cancer.	cal known to the State of
SARA Title III Section 302 Extr	emely Hazardous Substance	
Not applicable		
SARA Title III Section 313 Toxi	c Chemicals:	
Not applicable Canadian Regulations:		
National Pollutant Releas	e Inventory (NPRI)	
Not applicable		
WHMIS Classification	: D2B	
DSL	: DSL status has not been determined. Quant restricted by regulations.	ity use in Canada may be
National Inventories:		
Australia AICS	: Listed	
China IECS	: Not determined	
Europe EINECS	: Not determined	
Japan ENCS	: Not determined	

POLYONE CORPORA	TION	N		P	<u>blyOn</u>	<u>e</u> .
ATERIAL SAFETY DATA SH						
YELLOW 109C						
/ersion Number 1.0 Revision Date 10/29/2003					Print Date	Page 6 of 6 11/12/2011
Korea KECI	: No	Not determined				
Philippines PICCS	: No	Not determined				
	1	16. OTHER INF	ORMATION			
material when used in combina conditions.		-				