MATERIAL SAFETY DATA SHEET **PG 45416 PEARL WT PE**

Version Number 1.3 Revision Date 04/24/2007

Page 1 of 6 Print Date 11/27/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PG 45416 PEARL WT PE
Product code :	CC10045416
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to
Skin	eyes. : Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 45416 PEARL WT PE**

Version Number 1.3 Revision Date 04/24/2007 Page 2 of 6 Print Date 11/27/2011

	4. FIRST AID MEASURES				
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.				
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.				
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.				
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.				
	5. FIRE-FIGHTING MEASURES				
Flash point	: Not applicable				
Flammable Limits					
Upper explosion limit	: Not applicable				
Lower explosion limit	: Not applicable				
Autoignition temperature	: Not applicable				
Suitable extinguishing media	Carbon dioxide blanket, Water spray, Dry powder, Foam.				
Special Fire Fighting Procedures	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.				
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.				
	6. ACCIDENTAL RELEASE MEASURES				
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.				
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.				
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.				
	7. HANDLING AND STORAGE				
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.				
Storage	: Keep containers dry and tightly closed to avoid moisture absorption				

PolyOne.

MATERIAL SAFETY DATA SHEET PG 45416 PEARL WT PE

Version Number 1.3 Revision Date 04/24/2007 Page 3 of 6 Print Date 11/27/2011

8. 1	EXPOSURE	CONTROLS / PERSONAL	PROTECTION				
Respiratory protection	: N	o personal respiratory protectiv	ve equipment normally	required.			
Eye/Face Protection	: S	: Safety glasses with side-shields					
Hand protection	: P	rotective gloves					
Skin and body protection	: L	ong sleeved clothing					
Additional Protective Measures	: S	afety shoes					
General Hygiene Considerations		landle in accordance with good Vash hands before breaks and a		afety practice			
Engineering measures		leat only in areas with appropri ppropriate exhaust ventilation a		Provide			
Exposure limit(s)							
Components	Value	Exposure time	Exposure type	List:			
Mica	20 mppcf	PEL:	Total dust.	OSHA			
	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH			
	3 mg/m3	Time Weighted Average (TWA):		MX OEL			
Titanium dioxide	3 mg/m3 10 mg/m3	(TWA): Time Weighted Average		MX OEL ACGIH			
Titanium dioxide	10 mg/m3	(TWA):	Total dust.	ACGIH			
Titanium dioxide		(TWA): Time Weighted Average (TWA):	Total dust. as Ti	ACGIH OSHA Z1			
Titanium dioxide	10 mg/m3 15 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average					
Titanium dioxide	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit	as Ti as Ti	ACGIH OSHA Z1 MX OEL			
Form	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solid	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO	as Ti as Ti PERTIES ration rate : Not	ACGIH OSHA Z1 MX OEL MX OEL			
Form Appearance	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO L Evapor ts Specifi	as Ti as Ti PERTIES ration rate : Not c Gravity : Not	ACGIH OSHA ZI MX OEL MX OEL			
Form Appearance Color	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk dot	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not	ACGIH OSHA ZI MX OEL MX OEL			
Form Appearance Color Odour	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 9. PHYSIC : Solic : pelle : WHI : Very	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk der faint Vapour	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not	ACGIH OSHA ZI MX OEL MX OEL			
Form Appearance Color Odour Melting point/range	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle : WHI : Very : Not of	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk de faint Vapour determined Vapour	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	ACGIH OSHA ZI MX OEL MX OEL			
Form Appearance Color Odour	10 mg/m3 15 mg/m3 10 mg/m3 20 mg/m3 20 mg/m3 9. PHYSIO : Solid : pelle : WHI : Very : Not of	(TWA): Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): Short Term Exposure Limit (STEL): CAL AND CHEMICAL PRO I Evapor ts Specifi TE Bulk der faint Vapour	as Ti as Ti PERTIES ration rate : Not c Gravity : Not ensity : Not r pressure : Not r density : Not	ACGIH OSHA Z MX OEI MX OEI applicable determined established applicable			

MATERIAL SAFETY DATA SHEET **PG 45416 PEARL WT PE**

Version Number 1.3 Revision Date 04/24/2007 Page 4 of 6 Print Date 11/27/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the polymer matrix.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 45416 PEARL WT PE**

Version Number 1.3 Revision Date 04/24/2007 Page 5 of 6 Print Date 11/27/2011

Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classifier	Not regulated for transportation
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	s Substances (40 CFR 302)
Not applicable	
California Proposition 65	: Not applicable
SARA Title III Section 302 Ex	stremely Hazardous Substance
Unless specific chemicals are i	dentified under this section, this product is Not Applicable under this regula

MATERIAL SAFETY DATA SHEET **PG 45416 PEARL WT PE**

Version Number 1.3 Revision Date 04/24/2007 Page 6 of 6 Print Date 11/27/2011

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#
Zinc iron oxide			12063-19-3	0.10 - 1.00	231
WHMIS Classification	:	D2A			
WHMIS Ingredient Dis	closu	re List			
CAS-No. 12001-26-2					
DSL	:		ts of this product a (DSL) or are exe		n Domestic
tional Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Not determined			
Japan ENCS	:	Not determined			
Korea KECI	:	Listed			
		Listed			

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.