

MATERIAL SAFETY DATA SHEET

TEAL

Version Number 1.0 Revision Date 11/24/2003 Page 1 of 6 Print Date *11/12/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	TEAL
Product code	:	CC10046248
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

TEAL

Version Number 1.0 Revision Date 11/24/2003 Page 2 of 6 Print Date 11/12/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET

TEAL

Storage

Version Number 1.0				
Revision Date	11/24/2003			

Page 3 of 6 Print Date 11/12/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	: No personal respiratory protective equipment normally required	
Eye/Face Protection	: Safety glasses with side-shields.	
Hand protection	: Protective gloves. Refer to equipment supplier to ensure protection	ion.
Skin and body protection	: Long sleeved clothing.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety pra Wash hands before breaks and at the end of workday.	actice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.	;

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

		EMICAL PROPERTIES	
Form	: Solid	Evaporation rate	: Not applicable
Appearance	: Pellets	Specific Gravity	: Not determined
Color	: GREEN	Bulk density	: Not established
Odor	: Very faint	Vapor pressure	: Not applicable
Melting point/range	: Not determined	Vapour density	: Not applicable
Boiling Point:	: Not applicable	pH	: Not applicable
Water solubility	: Insoluble		
	10. STABILITY A	ND REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from	oxidizing agents and open f	lama To avoid therm



MATERIAL SAFETY DATA SHEET

TEAL

sion Date 11/24/20	03			Page 4 Print Date 11/12/2
		decompositio	n, do not overheat.	
Incompatible Materia	als :	Incompatible	with strong acids and o	oxidizing agents.
Hazardous decompos products	sition :			oxide (CO), oxides of nitrogen nd smoke are all possible.
	11. T	OXICOLOG	ICAL INFORMATIO	DN
health data for the ind <u>Toxicity Overview</u>	dividual compo	nents which co	omprise the mixture.	ure effects listed are based on exis
-		-	-	
CAS-No. 1317-65-3	Chemi Calcium car	cal Name	Effect Irritant	Target Organ
131/-03-3	Calcium car	oonate	Systemic effects	Eyes, Skin. Eyes, Skin, Respiratory system
13463-67-7	Titanium die	oxide	Systemic effects	Respiratory system.
			CAL INFORMATION	
Bioaccumulation Potential : Che of t		of the polyme	er. e not readily available a er.	is they are bound within the matrix
	13	. DISPOSAL	CONSIDERATIONS	5
Product : Like most therr possible recycli generator of wa classification, t		ermoplastic plastics the cling is preferred to dis waste material has the r	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with	
has the re- and dispo		has the respon	nsibility for proper was in accordance with app	e. The generator of waste material te classification, transportation licable federal, state/provincial
		-	anations.	
	14		RT INFORMATION	



MATERIAL SAFETY DATA SHE	ЕТ	
TEAL		
Version Number 1.0 Revision Date 11/24/2003		Page 5 of 6 Print Date 11/12/2011
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Extr	em	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Toxi	ic C	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Releas	se Ir	nventory (NPRI)
Not applicable		
WHMIS Classification	:	D2B
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed

	PolvOne
POLYONE CORPORATIO	N Solution
MATERIAL SAFETY DATA SHEET	
TEAL	
Version Number 1.0 Revision Date 11/24/2003	Page 6 of 6 Print Date 11/12/2011
Korea KECI :	Listed
Philippines PICCS :	Listed
	16. OTHER INFORMATION
processing, storage, transportation, d specification. The information relates	ormation given is designed only as a guidance for safe handling, use, lisposal and release and is not to be considered a warranty or quality s only to the specific material designated and may not be valid for such with any other materials and/or in any particular process or processing

٦

Г