# MATERIAL SAFETY DATA SHEET

# LIME GREEN 358C M6173C

Version Number 1.0 Revision Date 01/16/2004 Page 1 of 6 Print Date 11/13/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	LIME GREEN 358C M6173C
Product code	:	CC10048406
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Chromium (III) oxide	1308-38-9	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

### MATERIAL SAFETY DATA SHEET LIME GREEN 358C M6173C

Version Number 1.0 Revision Date 01/16/2004 Page 2 of 6 Print Date 11/13/2011

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.	
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> <li>Carbon dioxide blanket, water spray, dry powder, foamnone.</li> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne</li> </ul>	
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge Heat	



## MATERIAL SAFETY DATA SHEET LIME GREEN 358C M6173C

Version Number 1.0 Revision Date 01/16/2004 Page 3 of 6 Print Date 11/13/2011

Storage

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

only in areas with appropriate exhaust ventilation.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

#### Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Chromium (III) oxide	0.5 mg/m3	Time Weighted Average	as Cr	ACGIH
		(TWA):		
	1 mg/m3	PEL:	as Cr	OSHA Z1
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
	_	(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
  Pellets
  GREEN
  Very faint
  Not determined
  Not applicable
  Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
  Not determined
  Not established
  Not applicable
  Not applicable
  Not applicable

#### **10. STABILITY AND REACTIVITY**



### MATERIAL SAFETY DATA SHEET LIME GREEN 358C M6173C

Version Number 1.0 Revision Date 01/16/2004 Page 4 of 6 Print Date 11/13/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

#### Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi and trivalent forms of chrome have a low order of acute toxicity but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) componds are not considered carcinogenic in animals or humans.

#### **12. ECOLOGICAL INFORMATION**

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound within the matrix of the polymer.	x
Bioaccumulation Potential	Chemicals are not readily available as they are bound within the matrix of the polymer.	x
Additional advice	No data available	
	13. DISPOSAL CONSIDERATIONS	
Product	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The	;



# MATERIAL SAFETY DATA SHEET LIME GREEN 358C M6173C

Version Number 1.0				Page 5	
Revision Date 01/16/2004				Print Date 11/13/2	011
Contaminated packaging	:	has the responsibility for	ion and disposal in provincial and location then possible. The proper waste class	n accordance with al regulations. generator of waste materia sification, transportation	1
		and disposal in accordance and local regulations.	e with applicable	federal, state/provincial	
	1	4. TRANSPORT INFOR	MATION		
U.S. DOT Classification	:	Not regulated for transpo	rtation.		
ICAO/IATA (air)	:	Refer to specific regulation	on.		
IMO / IMDG (maritime)	:	Refer to specific regulation	on.		
	15	REGULATORY INFO	RMATION		
US Regulations:					
OSHA Status	:	Classified as hazardous b	ased on compone	nts.	
TSCA Status	TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous Su	ubs	tances (40 CFR 302)			
Not applicable					
California Proposition 65	:	WARNING! This produ California to cause cance		nical known to the State of	
SARA Title III Section 302 Extrem	eme	ely Hazardous Substance			
Not applicable					
SARA Title III Section 313 Toxic	e C	hemicals:			
Chemical Name			CAS-No.	Weight %	
CHROMIUM III COMPO	ЭU	NDS	1308-38-9	1.32	
Canadian Regulations:					
National Pollutant Release	e In	ventory (NPRI)			



### MATERIAL SAFETY DATA SHEET LIME GREEN 358C M6173C

#### Version Number 1.0

Revision Date 01/16/2004

Page 6 of 6 Print Date 11/13/2011

		•	•
Chemical Name	CAS-No.	Weight %	NPRI ID#
Chromium (III) oxide	1308-38-9	1.32	68

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS	-No.
1308	-38-9
7631	-86-9

:

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Listed
Korea KECI	:	Listed
Philippines PICCS	:	Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.