

MATERIAL SAFETY DATA SHEET **DARK YELLOW PET**

Version Number 1.0 Revision Date 02/05/2004

Page 1 of 6 Print Date *11/13/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY : Product Stewardship (770) 271-59 TELEPHONE		Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	DARK YELLOW PET
Product code	:	CC10048545
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
9,10-Anthracenedione, 1,8-bis(phenylthio)-	13676-91-0	1 - 5
Silica, amorphous, fumed, crystal-free	112945-52-5	1 - 5
Mica	12001-26-2	10 - 30
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.





MATERIAL SAFETY DATA SHEET DARK YELLOW PET

Version Number 1.0 Revision Date 02/05/2004 Page 2 of 6 Print Date 11/13/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Greater than 200 °F (93 °C)
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable. Not applicable. Not applicable Carbon dioxide blanket, dry powder, foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: The product should not be allowed to enter drains, water courses or th soil. Should not be released into the environment.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET DARK YELLOW PET

			Print D	Page 2 ate 11/13/
Handling	: H	eat only in areas with appropr	iate exhaust ventilation.	
Storage		eep containers dry and tightly nd contamination. Store in a c		e absorption
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: U	nder normal handling condition	ons a respirator may not b	be required.
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with good Vash hands before breaks and		afety practic
Engineering measures		eat only in areas with appropropropriate exhaust ventilation		Provide
Exposure limit(s)				
<u>Exposure mini(s)</u>				
Components	Value	Exposure time	Exposure type	List:
	20 mppcf	PEL:	Total dust.	OSHA
Components		4		OSHA
Components	20 mppcf	PEL: Time Weighted Average	Total dust.	OSHA
Components Mica Silica, amorphous,	20 mppcf 3 mg/m3	PEL: Time Weighted Average (TWA):	Total dust. Respirable fraction.	OSHA ACGIH Z3
Components Mica Silica, amorphous, fumed, crystal-free	20 mppcf 3 mg/m3 20 mppcf	PEL: Time Weighted Average (TWA): PEL: Time Weighted Average	Total dust. Respirable fraction.	OSHA ACGIH Z3 ACGIH
Components Mica Silica, amorphous, fumed, crystal-free	20 mppcf 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3	PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA):	Total dust. Respirable fraction. Total dust. Total dust.	OSHA ACGIH
Components Mica Silica, amorphous, fumed, crystal-free Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : liquit : Visco : YEL : Very : Not a : Not a	PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(d Evapo ous, liquid Specif LOW Bulk of faint Vapor applicable Vapou applicable pH	Total dust. Respirable fraction. Total dust. Total dust. Total dust. OPERTIES ration rate : Not Tic Gravity: : Not pressure : Not pressure : Not ration rate : Not in Gravity: : Not pressure : Not in density : Not	OSHA ACGIH Z3 ACGIH OSHA Z determined applicable determined
Components Mica Silica, amorphous, fumed, crystal-free Titanium dioxide Form Appearance Color Odor Melting point/range	20 mppcf 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : liquit : Visco : YEL : Very : Not a	PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(d Evapo ous, liquid Specif LOW Bulk of faint Vapor applicable Vapou applicable pH	Total dust. Respirable fraction. Total dust. Total dust. Total dust. OPERTIES ration rate : Not Tic Gravity: : Not pressure : Not pressure : Not ration rate : Not in Gravity: : Not pressure : Not in density : Not	OSHA ACGIH Z3 ACGIH OSHA Z determined determined applicable determined determined
Components Mica Silica, amorphous, fumed, crystal-free Titanium dioxide Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 3 mg/m3 20 mppcf 10 mg/m3 15 mg/m3 9. PHYSIC : liquid : Visco : YEL : Very : Not a : Imm	PEL: Time Weighted Average (TWA): PEL: Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PR(d Evapo ous, liquid Specif LOW Bulk of faint Vapor applicable Vapou applicable pH	Total dust. Respirable fraction. Total dust. Total dust. Total dust. OPERTIES ration rate : Not Total consisty : Not in density : Not : Not	OSHA ACGIH Z3 ACGIH OSHA Z determined determined determined determined



MATERIAL SAFETY DATA SHEET **DARK YELLOW PET**

Version Number 1.0 Revision Date 02/05/2004

Page 4 of 6 Print Date *11/13/2011*

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13676-91-0	9,10-Anthracenedione,	sensitizer	Skin.
	1,8-bis(phenylthio)-		
112945-52-5	Silica, amorphous, fumed,	Irritant	Eyes, Respiratory system.
	crystal-free		
12001-26-2	Mica	Systemic effects	Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
112945-52-5	Silica, amorphous, fumed, crystal-free	Oral LD50	3,160 mg/kg	rat

12. ECOLOGICAL INFORMATION

Additional advice	:	No data available
Bioaccumulation Potential	:	Does not bioaccumulate.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Persistence and degradability	:	Not readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Product

: Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET DARK YELLOW PET

ersion Number 1.0 evision Date 02/05/2004				Prin	Page 5 d t Date 11/13/20
Contaminated packaging	:	Recycling is preferred has the responsibility and disposal in accord and local regulations.	for proper waste	e classification,	transportation
	1	4. TRANSPORT INF	ORMATION		
U.S. DOT Classification	:	Not regulated for trans	sportation.		
ICAO/IATA (air)	:	Not regulated for trans	sportation.		
IMO / IMDG (maritime)	:	Not regulated for trans	sportation.		
	15	. REGULATORY INI	ORMATION		
US Regulations:					
OSHA Status	:	Classified as hazardou	s based on com	ponents.	
TSCA Status	:	All components of thi Inventory.	s product are lis	ted on or exemp	ot from the TSCA
US. EPA CERCLA Hazardous Substances (40 CFR 302)					
Not applicable	Not applicable				
California Proposition 65	:	This product does not	contain a substa	nce listed by Ca	alifornia Prop 65.
SARA Title III Section 302 Extremely Hazardous Substance					
	rem	ery mazardous Substanc	æ		
Not applicable					
SARA Title III Section 313 To:	xic (Themicals:			
Not applicable Canadian Regulations:					
National Pollutant Relea	ise Ii	nventory (NPRI)			
Chemical Name Bis (2-ethylhexyl) adipate			CAS-No. 103-23-1	Weight % 17.92	NPRI ID# 24
Bis (2-eurymexyr) aurpate			103-23-1	17.92	24
WHMIS Classification	:	D2B			



MATERIAL SAFETY DATA SHEET DARK YELLOW PET

Version Number 1.0 Revision Date 02/05/2004

Page 6 of 6 Print Date *11/13/2011*

WHMIS Ingredient Disclosure List

CAS-No.	
103-23-1	
12001-26-2	

DSL

: All of the components of this product are listed on the Canadian Inventories or are exempt. However, at least one component of this product is on the Canadian Non-Domestic Substances List (NDSL). Quantity use in Canada is restricted by regulations.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.