PolvOne

MATERIAL SAFETY DATA SHEET SILVER

Version Number 1.2 Revision Date 07/25/2007

Page 1 of 8 Print Date 11/30/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	SILVER
Product code	CC10049435
Chemical Name	Mixture
CAS-No.	Mixture
Product Use	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl	57583-35-4	1 - 5
ester		
Glyceryl monostearate	31566-31-1	1 - 5
Dioctyltin bis(2-ethylhexylmercaptoacetate)	15571-58-1	1 - 5
Titanium dioxide	13463-67-7	5 - 10
Mica	12001-26-2	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion Eyes	May be harmful if swallowed.Particulates, like other inert materials can be mechanically irritating.



MATERIAL SAFETY DATA SHEET **SILVER**

sion Date 07/25/2007	Print Date 11/30/2
Skin	: Experience shows no unusual dermatitis hazard from routine handling
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in



MATERIAL SAFETY DATA SHEET **SILVER**

sion Number 1.2 ision Date 07/25/2007		Page 3 Print Date 11/30/2
		plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSUF	RE CONTROLS / PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

PolyOne

MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.2

Revision Date 07/25/2007

Page 4 of 8 Print Date *11/30/2011*

Components	Value	Exposure time	Exposure type	List:
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH
	0.1 mg/m3	PEL:	as Sn	OSHA Z1
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	MX OEL
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	MX OEL
Glyceryl monostearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Mica	3 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH
	3 mg/m3	Time Weighted Average (TWA):		MX OEL
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL
Dioctyltin bis(2-ethylhexylmerca ptoacetate)	0.1 mg/m3	PEL:	as Sn	OSHA Z1
•	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- Solid
 pellets
 GREY
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicableNot determinedNot establishedNot applicableNot applicable
- : Not applicable

10. STABILITY AND REACTIVITY

Stability

: Stable.

Hazardous Polymerization

: Will not occur.



MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.2 Revision Date 07/25/2007	Page 5 of 8 Print Date 11/30/2011
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.
15571-58-1	Dioctyltin bis(2-ethylhexylmercaptoa cetate)	Systemic effects	Respiratory system, central nervous system (CNS).
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
15571-58-1	Dioctyltin bis(2-ethylhexylmercaptoa cetate)	Oral LD50	2,100 mg/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

PolyOne.

MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.2

Revision Date 07/25/2007

Page 6 of 8 Print Date 11/30/2011

CAS-No.		mical Name	OSHA	IARC	NTP
13463-67-7	Fitanium d	ioxide	no	2B	no
IARC Carcinogen Classi 1 - The component is car 2A - The component is p 2B - The component is p NTP Carcinogen Classifi 1 - The component is kno 2 - The component is rea	cinogenic t robably ca ossibly car cations: own to be a	rcinogenic to human cinogenic to humans human carcinogen.			
	12	2. ECOLOGICAL I	NFORMATION		
Persistence and degradab	ility :	Not readily biodeg	radable.		
Environmental Toxicity	:	Chemicals are not a polymer matrix.	readily available as	s they are bound w	vithin the
Bioaccumulation Potenti	al :	Chemicals are not a polymer matrix.	readily available as	s they are bound w	vithin the
Additional advice	:	No data available			
	1	3. DISPOSAL CON	SIDERATIONS		
Product	:	Like most thermop possible recycling i generator of waste classification, trans applicable federal,	is preferred to disp material has the re sportation and disp	osal or incinerations of a sponsibility for prosal in accordance	on. The oper waste with
Contaminated packaging	:	Recycling is prefer has the responsibili and disposal in acc and local regulation	ity for proper wast ordance with appli	e classification, tra	ansportation
	1	4. TRANSPORT II	NFORMATION		
U.S. DOT Classification	:	Not regulated for tr	ansportation.		
ICAO/IATA (air)	:	Refer to specific re	-		
IMO / IMDG (maritime)	:	Refer to specific re	gulation.		
	15	. REGULATORY	INFORMATION		
US Regulations:					

PolyOne.

MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.2 Revision Date 07/2						Print Date	Page 7 of 8 11/30/2011
OSHA S	Status	:	Classified as haz	zardous based o	n components.		
TSCA S	tatus	:	All components Inventory.	of this product	are listed on or e	exempt from	the TSCA
US. EPA CERC	CLA Hazardous S	ub	stances (40 CFR 3	302)			
Not	t applicable						
Californ 65	ia Proposition	:	Not applicable				
SARA Title III	Section 302 Extre	em	ely Hazardous Su	bstance			
Unless specific	chemicals are ide	enti	fied under this see	ction, this produ	ict is Not Applic	able under t	his regulation
SARA Title III	Section 313 Toxic	c C	Chemicals:				
Unless specific	chemicals are ide	enti	fied under this see	ction, this produ	act is Not Applic	able under t	his regulation
Canadian Regul	lations:						
National	Pollutant Release	e Ir	ventory (NPRI)				
Chemical Nat		• 11		CAS-No.	Weight %	NPRI	ID#
Aluminum				7429-90-5	0.10 - 1.00	12	
	Classification	: osu					
	CAS-No. 57583-35-4						
	12001-26-2 15571-58-1						
DSL		:	All components Substances List		t are on the Cana kempt.	dian Domes	tic
National Inventor	ories:						
Australi	a AICS	:	Not determined				
China II	ECS	:	Not determined				
			7/	/8			

PolyOne.

MATERIAL SAFETY DATA SHEET **SILVER**

Version Number 1.2 Revision Date 07/25/2007			Print Date	Page 8 of 8 11/30/2011
Europe EINECS	:	Not determined		
Japan ENCS	:	Not determined		
Korea KECI	:	Not determined		
Philippines PICCS	:	Not determined		
		16. OTHER INFORMATION		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.