

MATERIAL SAFETY DATA SHEET

10015472 WHITE

Version Number 1.0 Revision Date 03/10/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440) 930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	10015472 WHITE
Product code	:	CC10050745
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. If overheated or burnt, the polymer releases formaldehyde.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET 10015472 WHITE

Version Number 1.0 Revision Date 03/10/2004 Page 2 of 6 Print Date 11/14/2011

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice. Ingestion : Do not induce vomiting without medical advice. When symptom persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention Skin : Wash off with soap and plenty of water. If skin irritation persists medical attention. Skin : Not applicable Flash point : Not applicable Flaumable Limits Upper explosion limit : Upper explosion limit : Not applicable Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foamnone. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May bu with invisible flame. Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. </th <th>Medical Conditions Aggravated by Exposure:</th> <th>: None known.</th>	Medical Conditions Aggravated by Exposure:	: None known.
overheating or combustion. When symptoms persist or in all case doubt seek medical advice. Ingestion : Do not induce vomiting without medical advice. When symptom persist or in all cases of doubt seek medical advice. Eyes : Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention Skin : Wash off with soap and plenty of water. If skin irritation persists medical attention. 5. FIRE-FIGHTING MEASURES Flash point : Not applicable Lower explosion limit : Not applicable Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foamnone. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May bu with invisible flame. 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should		4. FIRST AID MEASURES
Eyes : Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention Skin : Wash off with soap and plenty of water. If skin irritation persists medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists medical attention. Flash point : Not applicable Flash point : Not applicable Flammable Limits : Not applicable Upper explosion limit : Not applicable Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foamnone. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May bu with invisible flame. Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should	Inhalation	overheating or combustion. When symptoms persist or in all cases of
least 15 minutes. If eye irritation persists, seek medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists medical attention. Skin : Wash off with soap and plenty of water. If skin irritation persists medical attention. Flash point : Not applicable Flash point : Not applicable Flammable Limits : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not applicable Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foamnone. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May bu with invisible flame. Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should	Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
medical attention. Image: Constraint of the product of the produc	Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Flash point : Not applicable Flammable Limits Upper explosion limit : Not applicable Lower explosion limit : Not applicable Autoignition temperature : Not applicable Suitable extinguishing media : Carbon dioxide blanket, water spray, dry powder, foamnone. Special Fire Fighting : Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May bu with invisible flame. 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should	Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
Flammable Limits Upper explosion limit Not applicable Lower explosion limit Not applicable Autoignition temperature Not applicable Suitable extinguishing media Carbon dioxide blanket, water spray, dry powder, foamnone. Special Fire Fighting Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne contaminants. Unusual Fire/Explosion Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOX), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May bu with invisible flame. Personal precautions Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions Should not be released into the environment. The product should		5. FIRE-FIGHTING MEASURES
Upper explosion limit Lower explosion limit: Not applicableAutoignition temperature: Not applicableSuitable extinguishing media: Carbon dioxide blanket, water spray, dry powder, foamnone.Special Fire Fighting Procedures: Fullface self-contained breathing apparatus (SCBA) used in posit pressure mode should be worn to prevent inhalation of airborne 	Flash point	: Not applicable
Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should	Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. May burn with invisible flame.
impervious gloves, boots and coveralls. Environmental precautions : Should not be released into the environment. The product should		6. ACCIDENTAL RELEASE MEASURES
	Personal precautions	
	Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
	Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
7. HANDLING AND STORAGE		7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET 10015472 WHITE

and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. When temperatures exceed 230°C (446°F) and ventilation is inadequate to maintain concentrations below exposure limits, use a positive air supplied respirator. Air purifying respirators may not provide adequate protection. Eye/Face Protection : Safety glasses with side-shields. Wear face-shield and protective su for abnormal processing problems. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Mandbe before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) 20 mppcf PEL: Total dust. OSHA ZGIH Value Exposure time Exposure type List: Silica, amorphous 20 mppcf PEL: Total dust. OSHA ZGIH Value Exposure time Exposure type List: Silica, amorphous 20 mppcf PEL: Total dust. OSHA ZGIH 10 mg/m3 Time Weighted Average (TWA): Total dust.	ion Number 1.0 sion Date 03/10/2004				Print D	Page 3 Date 11/14/2
and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION Respiratory protection : No personal respiratory protective equipment normally required. When temperatures exceed 230°C (446°F) and ventilation is inadequate to maintain concentrations below exposure limits, use a positive air supplied respirator. Air purifying respirators may not provide adequate protection. Eye/Face Protection : Safety glasses with side-shields. Wear face-shield and protective su for abnormal processing problems. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) 20 mppcf PEL: Total dust. OSHA 23 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): Total dust. OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance Pellets, slabs Specific Gravity: : Not applicable (Odor WHITE </td <td>Handling</td> <td>С</td> <td>ontainer only in a well-ve</td> <td>entilated area. Heat</td> <td></td> <td></td>	Handling	С	ontainer only in a well-ve	entilated area. Heat		
Respiratory protection : No personal respiratory protective equipment normally required. When temperatures exceed 230°C (446°F) and ventilation is inadequate to maintain concentrations below exposure limits, use a positive air supplied respirator. Air purifying respirators may not provide adequate protection. Eye/Face Protection : Safety glasses with side-shields. Wear face-shield and protective su for abnormal processing problems. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Mandle in accordance with good industrial hygiene and safety practic Considerations Engineering measures : Head only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) 20 mppcf PEL: Total dust. Z3 3 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH (TWA): OSHA 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance Not determined Golor : WHITE Bulk density : Not applicable Appearance Not determined	Storage				l moisture	e absorption
When temperatures exceed 230°C (446°F) and ventilation is inadequate to maintain concentrations below exposure limits, use a positive air supplied respirator. Air purifying respirators may not provide adequate protection. Eye/Face Protection : Safety glasses with side-shields. Wear face-shield and protective su for abnormal processing problems. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety practic Onsiderations Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation. It is in appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Z0 mppcf PEL: Total dust. OSHA Silica, amorphous 20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average ACGIH OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Odor : WHITE <t< td=""><td>8. 1</td><td>EXPOSURE</td><td>CONTROLS / PERSO</td><td>NAL PROTECTIO</td><td>N</td><td></td></t<>	8. 1	EXPOSURE	CONTROLS / PERSO	NAL PROTECTIO	N	
for abnormal processing problems. Hand protection : Protective gloves. Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety practic Considerations : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Total dust. OSHA Silica, amorphous 20 mppcf PEL: Total dust. OSHA 20 mppcf PEL: Total dust. OSHA 20 mppcf 10 mg/m3 Time Weighted Average ACGIH (TWA): . . OSHA Z 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color :	Respiratory protection	V ir p	When temperatures excee nadequate to maintain co ositive air supplied respi	d 230°C (446°F) and ncentrations below e rator. Air purifying r	l ventilati xposure l	on is imits, use a
Skin and body protection : Long sleeved clothing. Additional Protective : Safety shoes. Measures : Safety shoes. General Hygiene : Handle in accordance with good industrial hygiene and safety practic Considerations : Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Total dust. OSHA Components Value Exposure time Exposure type List: Silica, amorphous 20 mppcf PEL: Total dust. OSHA 20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average ACGIH (TWA): : Total dust. OSHA Z OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not applicable Ador : formaldehyde Vapour density : Not applicable	Eye/Face Protection				ield and j	protective suit
Additional Protective Measures : Safety shoes. General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Total dust. OSHA Itanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH (TWA): Itanium dioxide 10 mg/m3 PEL: Total dust. OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not applicable Color : WHITE Bulk density : Not applicable Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined <td>Hand protection</td> <td>: P</td> <td>rotective gloves.</td> <td></td> <td></td> <td></td>	Hand protection	: P	rotective gloves.			
Measures : Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Total dust. OSHA : Ompoon the value : Exposure time : Exposure type : List: : Silica, amorphous : 20 mppcf PEL: : Total dust. OSHA : 10 mg/m3 : Time Weighted Average : ACGIH : (TWA): : I is mg/m3 OSHA Z : 50 id : Solid : Evaporation rate : Not applicable Appearance : Pellets, slabs : Specific Gravity: : Not determined Color : WHITE : Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting po	Skin and body protection	: L	ong sleeved clothing.			
Considerations Wash hands before breaks and at the end of workday. Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. Exposure limit(s) : Heat only in areas with appropriate exhaust ventilation at machinery. Exposure limit(s) : Exposure time Exposure type List: Silica, amorphous 20 mppcf PEL: Total dust. OSHA 20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not applicable Odor : formaldehyde Vapor pressure : Not applicable		: S	afety shoes.			
appropriate exhaust ventilation at machinery. Exposure limit(s) Exposure time Exposure type List: Silica, amorphous 20 mppcf PEL: Total dust. OSHA 20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA Z PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable						afety practice
Components Value Exposure time Exposure type List: Silica, amorphous 20 mppcf PEL: Total dust. OSHA 20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA Z 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable	Engineering measures		•		ntilation.	Provide
Silica, amorphous 20 mppcf PEL: Total dust. OSHA 20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable	Exposure limit(s)					
20 mppcf PEL: Total dust. Z3 Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA Z 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable	Components	Value	Exposure time	Exposure	type	List:
Titanium dioxide 10 mg/m3 Time Weighted Average (TWA): ACGIH 15 mg/m3 PEL: Total dust. OSHA Z 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable	Silica, amorphous					
Image: Constraint of the system (TWA): Image: Constraint of the system 15 mg/m3 PEL: Total dust. OSHA Z 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable					ust.	
15 mg/m3 PEL: Total dust. OSHA Z 9. PHYSICAL AND CHEMICAL PROPERTIES Form : Solid Evaporation rate : Not applicable Appearance : Pellets, slabs Specific Gravity: : Not determined Color : WHITE Bulk density : Not established Odor : formaldehyde Vapor pressure : Not applicable Melting point/range : Not determined Vapour density : Not applicable	Titanium dioxide	10 mg/m3	•	age		ACGIH
Form: SolidEvaporation rate: Not applicableAppearance: Pellets, slabsSpecific Gravity:: Not determinedColor: WHITEBulk density: Not establishedOdor: formaldehydeVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicable		15 mg/m3		Total du	ust.	OSHA Z1
Form: SolidEvaporation rate: Not applicableAppearance: Pellets, slabsSpecific Gravity:: Not determinedColor: WHITEBulk density: Not establishedOdor: formaldehydeVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicable				DDODEDTIES		
Appearance:Pellets, slabsSpecific Gravity::Not determinedColor:WHITEBulk density:Not establishedOdor:formaldehydeVapor pressure:Not applicableMelting point/range:Not determinedVapour density:Not applicable		9. PHYSIC	LAL AND CHEMICAL	PROPERTIES		
Color: WHITEBulk density: Not establishedOdor: formaldehydeVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicable	Form					
Odor: formaldehydeVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicable						
Melting point/range : Not determined Vapour density : Not applicable						
Boiling Point:: Not applicablepH: Not applicableWater solubility: Insoluble	Roiling Point:				. INOI	annicante



MATERIAL SAFETY DATA SHEET 10015472 WHITE

Version Number 1.0 Revision Date 03/10/2004 Page 4 of 6 Print Date 11/14/2011

10. STABILITY AND REACTIVITY				
Stability	: Stable.			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Maintain polymer temperature below 230°C (446°F). Avoid prolonged exposure at or above recommended processing temperature.			
Incompatible Materials	: Incompatible with strong oxidizers and with strong acids and bases (decomposes forming formaldehyde). At melt temperatures, acetal resins are incompatible with halogenated polymers such as vinyl (PVC) and any elastomers containing any halogenated polymers. At processing conditions, these materials are mutually destructive and involve rapid degradation. Even small amounts of such contaminants can cause sudden and spontaneous formaldehyde gas formation. Workplace fume well above threshold levels are a likely result. Unsafe pressurization of equipment such as extruder or mold can also result. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of halogenated materials from coming in contact with the acetal. Prevent contamination of virgin or rework resin.			
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. If overheated or burnt, the polymer releases formaldehyde. Decomposition of this material depends on the lenght of time it is exposed to elevated temperatures. At the recommended processing temperature of 210°C-220°C (410°F-428°F), decomposition should not be significant until after 30 minutes. Decomposition may be accelerated by contaminants, pigments and/or other additives.			
	11. TOXICOLOGICAL INFORMATION			
This mixture has not been eva				

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability

: Not readily biodegradable.

Environmental Toxicity

: Chemicals are not readily available as they are bound within the matrix



MATERIAL SAFETY DATA SHEET 10015472 WHITE

Version Number 1.0 Revision Date 03/10/2004 Page 5 of 6 Print Date 11/14/2011

Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix
Bioaccumulation Potential	•	of the polymer.
Additional advice	:	Not applicable
	1.	3. DISPOSAL CONSIDERATIONS
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	rem	ely Hazardous Substance

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET

POLYONE CORPORATION

10015472 WUITE

ersion Number 1.0		Page 6 c
Revision Date 03/10/2004		Print Date 11/14/20
Not applicable		
SARA Title III Section 313 Tox	ic (Chemicals:
Not applicable		
Canadian Regulations:		
National Pollutant Relea	se Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Not determined
Philippines PICCS	:	Listed
		16. OTHER INFORMATION

at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.