MATERIAL SAFETY DATA SHEET EMBRACE CHARCOAL-TGT

Version Number 1.0 Revision Date 03/23/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EMBRACE CHARCOAL-TGT
Product code	:	CC10051407
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Carbon black	1333-86-4	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET EMBRACE CHARCOAL-TGT

Version Number 1.0 Revision Date 03/23/2004 Page 2 of 6 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET EMBRACE CHARCOAL-TGT

Version Number 1.0 Revision Date 03/23/2004 Page 3 of 6 Print Date 11/14/2011

	a	nd contamination. Keep in a	dry, cool place.				
8. H	8. EXPOSURE CONTROLS / PERSONAL PROTECTION						
Respiratory protection : No personal respiratory protective equipment normally required.							
Eye/Face Protection	: S	afety glasses with side-shield	s.				
Hand protection	: P	rotective gloves.					
Skin and body protection	: L	ong sleeved clothing.					
Additional Protective Measures	: S	afety shoes.					
General Hygiene Considerations		Iandle in accordance with goo Vash hands before breaks and		afety practice.			
Engineering measures	Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.						
Exposure limit(s)							
Components	Value	Exposure time	Exposure type	List:			
Carbon black	3.5 mg/m3	Time Weighted Average	Total dust. as carbon	ACGIH			
	3.5 mg/m3	(TWA): PEL:	black Total dust. as carbon	OSHA Z1			
	_		black				
	9 PHVSI	CAL AND CHEMICAL PR	OPFRTIFS				
	<i>7</i> .11151						
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: Not o : Not a : Insol	ets Speci CK Bulk / faint Vapo determined Vapo applicable pH luble	ific Gravity: : Not density : Not r pressure : Not ur density : Not : Not	applicable determined established applicable applicable applicable			
	10. 5	STABILITY AND REACTI	VITY				
Stability	: S	table.					
Hazardous Polymerization	n : W	Vill not occur.					
Conditions to avoid		Keep away from oxidizing age ecomposition, do not overhea		void thermal			
Incompatible Materials	: Iı	ncompatible with strong acids	s and oxidizing agents.				



MATERIAL SAFETY DATA SHEET EMBRACE CHARCOAL-TGT

Version Number 1.0 Revision Date 03/23/2004 Page 4 of 6 Print Date 11/14/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where

PolyOne.

MATERIAL SAFETY DATA SHEET EMBRACE CHARCOAL-TGT

rsion Number 1.0 wision Date 03/23/2004	Page 5 o Print Date 11/14/20
	possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	Substances (40 CFR 302)
Not applicable	
California Proposition 65	: This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 E	stremely Hazardous Substance
Not applicable	
SARA Title III Section 313 T	oxic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Rele	ase Inventory (NPRI)
Not applicable	



MATERIAL SAFETY DATA SHEET EMBRACE CHARCOAL-TGT

Version Number 1.0 Revision Date 03/23/2004

Page 6 of 6 Print Date 11/14/2011

WHMIS Classification	:	D2A	
WHMIS Ingredient Dis	closu	re List	
CAS-No. 1333-86-4			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	:	Listed	
China IECS	:	Listed	
Europe EINECS	:	Listed	
Japan ENCS	:	Listed	
Korea KECI	:	Listed	
Philippines PICCS	:	Listed	
		16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.