

MATERIAL SAFETY DATA SHEET **BEIGE (W-75)**

Version Number 1.0 Revision Date 03/30/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (770) 271-5902
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	BEIGE (W-75)
Product code	:	CC10051653
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Rutile, antimony chromium buff	68186-90-3	1 - 5
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET **BEIGE (W-75)**

Version Number 1.0 Revision Date 03/30/2004 Page 2 of 6 Print Date 11/14/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET **BEIGE (W-75)**

Version Number 1.0 Revision Date 03/30/2004

Storage

Page 3 of 6 Print Date 11/14/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Rutile, antimony chromium buff	1 mg/m3	PEL:		OSHA Z1
	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	0.5 mg/m3	Time Weighted Average (TWA):	as Sb	ACGIH
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- Solid
 Pellets
 TAN
 Very faint
 Not determined
 Not applicable
 Insoluble
- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable



MATERIAL SAFETY DATA SHEET **BEIGE (W-75)**

Version Number 1.0 Revision Date 03/30/2004 Page 4 of 6 Print Date 11/14/2011

	10	. STABILITY AND REACTIVITY
Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
68186-90-3	Rutile, antimony chromium buff	Irritant	Eyes, Skin, Respiratory system.
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.	
Environmental Toxicity	:	Chemicals are not readily available as they are bound within the matrix of the polymer.	
Bioaccumulation Potential	:	Chemicals are not readily available as they are bound within the matrix of the polymer.	
Additional advice	:	No data available	
	13	3. DISPOSAL CONSIDERATIONS	
Product	:	Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The	



MATERIAL SAFETY DATA SHEET **BEIGE (W-75)**

ion Number 1.0 sion Date 03/30/2004				Page Print Date 11/14
		generator of waste ma classification, transpo applicable federal, sta	ortation and disposal	
Contaminated packaging	:	has the responsibility	for proper waste cla dance with applicable	e generator of waste mater assification, transportation fe federal, state/provincial
	1	4. TRANSPORT INF	ORMATION	
U.S. DOT Classification		Not regulated for tran	sportation	
ICAO/IATA (air)	•	Refer to specific regu	-	
IMO / IMDG (maritime)	•	Refer to specific regu		
		1 0		
	1:	5. REGULATORY IN	FORMATION	
US Regulations:				
OSHA Status	:	Classified as hazardo	us based on compon	ents.
TSCA Status	:	All components of th Inventory.	is product are listed	on or exempt from the TSC
US. EPA CERCLA Hazardo	ıs Sub	stances (40 CFR 302)		
Not applicable				
California Proposition 65	1 :	This product does not	contain a substance	listed by California Prop 6
SARA Title III Section 302 I	Extrem	ely Hazardous Substan	ce	
Not applicable				
SARA Title III Section 313 7	Toxic (Chemicals:		
Chemical Name			CAS-No.	Weight %
MANGANESE COM COMPOUNDS	1POUI	NDSANTIMONY	68412-38-4	0.22
CHROMIUM III CO	MPOU	JNDS	68186-90-3	1.19
Canadian Regulations:				

PolvOne

MATERIAL SAFETY DATA SHEET **BEIGE (W-75)**

Version Number 1.0

Revision Date 03/30/2004

Page 6 of 6 Print Date 11/14/2011

Chemical Name		CAS-No.	Weight %	NPRI ID#
Manganese antimony titat Pigment Yellow 164)	nium brown rutile (C.I.	68412-38-4	0.22	147
Manganese antimony titat Pigment Yellow 164)	nium brown rutile (C.I.	68412-38-4	0.22	17
Rutile, antimony chromiu	m buff	68186-90-3	1.19	68
Rutile, antimony chromiu	m buff	68186-90-3	1.19	17
WHMIS Ingredient Dis	closure List			
68186-90-3	_			
68186-90-3 7631-86-9 DSL	: All components of Substances List (DS		the Canadian	Domestic
68186-90-3 7631-86-9			the Canadian	Domestic
68186-90-3 7631-86-9 DSL			the Canadian	Domestic
68186-90-3 7631-86-9 DSL onal Inventories:	Substances List (DS		the Canadian	Domestic
68186-90-3 7631-86-9 DSL onal Inventories: Australia AICS	Substances List (DS : Listed		the Canadian	Domestic
68186-90-3 7631-86-9 DSL onal Inventories: Australia AICS China IECS	Substances List (DS : Listed : Listed		the Canadian	Domestic
68186-90-3 7631-86-9 DSL onal Inventories: Australia AICS China IECS Europe EINECS	Substances List (DS : Listed : Listed : Listed		the Canadian	Domestic

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.