

MATERIAL SAFETY DATA SHEET YELLOW 116C

Version Number 1.0 Revision Date 04/21/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	YELLOW 116C
Product code	CC10052841
Chemical Name	Mixture
CAS-No.	Mixture
Product Use	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Phenol,	25973-55-1	5 - 10
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Titanium dioxide	13463-67-7	5 - 10

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.	
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.	
Skin	: Experience shows no unusual dermatitis hazard from routine handling.	
Chronic exposure	: Refer to Section 11 for Toxicological Information.	



MATERIAL SAFETY DATA SHEET YELLOW 116C

Version Number 1.0 Revision Date 04/21/2004 Page 2 of 6 Print Date 11/14/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit	Not applicableNot applicable
Autoignition temperature Suitable extinguishing media	Not applicableCarbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET YELLOW 116C

Version Number 1.0 Revision Date 04/21/2004

Storage

Page 3 of 6 Print Date 11/14/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)


Components	Value	Exposure time	Exposure type	List:
Titanium dioxide	10 mg/m3	Time Weighted Average		ACGIH
		(TWA):		
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form	: Sc	olid	Evaporation rate	:	Not applicable
Appearance	: Pe	ellets	Specific Gravity:	:	Not determined
Color	: Y	ELLOW	Bulk density	:	Not established
Odor	: V	ery faint	Vapor pressure	:	Not applicable
Melting point/range	: No	ot determined	Vapour density	:	Not applicable
Boiling Point:	: No	ot applicable	pH	:	Not applicable
Water solubility	: In	soluble			
	1(). STABILITY AN			
		, STADILITT AN			
Stability	:	Stable.			
Hazardous Polymerization	:	Will not occur.			
Conditions to avoid	:		oxidizing agents and open floor not overheat.	ame.	To avoid thermal



MATERIAL SAFETY DATA SHEET YELLOW 116C

Version Number 1.0 Page 4 of 6 Revision Date 04/21/2004 Print Date 11/14/2011 Incompatible Materials : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), other hazardous materials, and smoke are all possible. **11. TOXICOLOGICAL INFORMATION** This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture. Toxicity Overview This product contains the following components which in their pure form have the following characteristics: Chemical Name Effect CAS-No. Target Organ 25973-55-1 Phenol, Systemic effects Kidney, Liver, reproductive 2-(2H-benzotriazol-2-yl)-4 system. ,6-bis(1,1-dimethylpropyl) 13463-67-7 Titanium dioxide Systemic effects Respiratory system. **12. ECOLOGICAL INFORMATION** Persistence and degradability : Not readily biodegradable. Environmental Toxicity Chemicals are not readily available as they are bound within the matrix : of the polymer. **Bioaccumulation Potential** : Chemicals are not readily available as they are bound within the matrix of the polymer. Additional advice : No data available **13. DISPOSAL CONSIDERATIONS** Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Recycling is preferred when possible. The generator of waste material Contaminated packaging : has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification : Not regulated for transportation.



PolyOne.
POLYONE CORPORATION
MATERIAL SAFETY DATA SHEET
YELLOW 116C
Version Number 1.0 Page 6 of 6 Revision Date 04/21/2004 Print Date 11/14/2011
Korea KECI : Listed
Philippines PICCS : Listed
16. OTHER INFORMATION
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.