

MATERIAL SAFETY DATA SHEET

Wispy Putty w/UV1B

Version Number 1.0 Revision Date 05/05/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	Wispy Putty w/UV1B
Product code	:	CC10053440
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Decanedioic acid,	52829-07-9	5 - 10
bis(2,2,6,6-tetramethyl-4-piperidinyl) ester		
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion	Resin particles, like other inert materials, can be mechanically irritating.May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

Wispy Putty w/UV1B

Version Number 1.0 Revision Date 05/05/2004 Page 2 of 6 Print Date 11/14/2011

Aggravated by Exposure:			
	4. FIRST AID MEASURES		
Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all ca doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.		
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.		
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.		
	5. FIRE-FIGHTING MEASURES		
Flash point	: Not applicable		
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 		
Special Fire Fighting Procedures Unusual Fire/Explosion	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen 		
Hazards	(NOx), other hazardous materials, and smoke are all possible.		
	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.		
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.		
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.		
	7. HANDLING AND STORAGE		
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.		



MATERIAL SAFETY DATA SHEET Wispy Putty w/UV1B

Version Number 1.0 Revision Date 05/05/2004 Page 3 of 6 Print Date 11/14/2011

 Storage
 : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

 Respiratory protection
 : No personal respiratory protective equipment normally required.

respiratory protocolon		anoa
Eye/Face Protection	: Safety glasses with side-shields.	
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved clothing.	
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safe Wash hands before breaks and at the end of workday.	ety practice.
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Pr appropriate exhaust ventilation at machinery.	rovide

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Silica, amorphous	20 mppcf	PEL:	Total dust.	OSHA
	20 mppcf	PEL:	Total dust.	Z3
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

Form	: Solid	Evaporation rate	: Not applicabl	le
Appearance	: Pellets	Specific Gravity:	: Not determin	ed
Color	: GREY	Bulk density	: Not establishe	ed
Odor	: Very faint	Vapor pressure	: Not applicabl	le
Melting point/range	: Not determined	Vapour density	: Not applicabl	le
Boiling Point:	: Not applicable	pН	: Not applicabl	le
Water solubility	: Insoluble			
	10. STABILITY AN	DREACTIVITY		
Stability	: Stable.			
Hazardous Polymerization	: Will not occur.			
Conditions to avoid	: Keep away from o	xidizing agents and open fl	ame. To avoid ther	mal



MATERIAL SAFETY DATA SHEET

Wispy Putty w/UV1B

Version Number 1.0 Revision Date 05/05/2004 Page 4 of 6 Print Date 11/14/2011

decomposition, do not overheat.

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
52829-07-9	Decanedioic acid,	Irritant	Eyes.
	bis(2,2,6,6-tetramethyl-4-p		
	iperidinyl) ester		
7631-86-9	Silica, amorphous	Irritant	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
52829-07-9	Decanedioic acid, bis(2,2,6,6-tetramethyl-4-p iperidinyl) ester	Oral LD50 Dermal LD50	3,700 mg/kg > 3,100 mg/kg	rat rabbit

12. ECOLOGICAL INFORMATION

Persistence and degradability	Not readily biodegradable.	
Environmental Toxicity	Chemicals are not readily available as they are bound within the ma of the polymer.	ıtrix
Bioaccumulation Potential	Chemicals are not readily available as they are bound within the ma of the polymer.	ıtrix
Additional advice	No data available	
	13. DISPOSAL CONSIDERATIONS	
Product	Like most thermoplastic plastics the product can be recycled. Whe possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste	

classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



MATERIAL SAFETY DATA SHEET

Wispy Putty w/UV1B

ion Number 1.0 sion Date 05/05/2004				Prin	Page : ht Date 11/14/
Contaminated packaging	:	Recycling is preferre has the responsibility and disposal in accor and local regulations	for proper waste dance with applic	classification,	transportation
	1	4. TRANSPORT INI	FORMATION		
U.S. DOT Classification	:	Not regulated for trai	nsportation.		
ICAO/IATA (air)	:	Refer to specific regu	ulation.		
IMO / IMDG (maritime)	:	Refer to specific regu	ulation.		
	1:	5. REGULATORY IN	FORMATION		
US Regulations:					
OSHA Status	:	Classified as hazardo	ous based on comp	oonents.	
TSCA Status	:	All components of th Inventory.	nis product are list	ed on or exemp	ot from the TSC
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)			
Not applicable					
California Proposition 65	:	WARNING! This pr California to cause ca		chemical know	n to the State o
SARA Title III Section 302 Ex	trem	ely Hazardous Substar	nce		
Not applicable					
SARA Title III Section 313 To	xic (Chemicals:			
Not applicable Canadian Regulations:					
National Dallutant Dala	ise I	nventory (NPRI)			
			CAS-No.	Weight %	NPRI ID#
Chemical Name	m h-	ff	60106 00 2	1 1 20	60
			68186-90-3 68186-90-3	0.28	68 17



MATERIAL SAFETY DATA SHEET Wispy Putty w/UV1B

Version Number 1.0 Revision Date 05/05/2004

Page 6 of 6 Print Date 11/14/2011

	WHMIS Classification	:	Not controlled.	
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
Nation	al Inventories:			
	Australia AICS	:	Listed	
	China IECS	:	Listed	
	Europe EINECS	:	Listed	
	Japan ENCS	:	Not determined	
	Korea KECI	:	Listed	
	Philippines PICCS	:	Listed	
			16 OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.