MATERIAL SAFETY DATA SHEET **PG 53649 BU LC UV**

Version Number 1.1 Revision Date 10/24/2006

Page 1 of 6 Print Date 11/24/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 53649 BU LC UV
Product code	:	CC10053649
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion
Acute exposure	
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.
Ingestion	: May be harmful if swallowed.
Eyes	: Irritating to eyes and respiratory system.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 53649 BU LC UV**

Version Number 1.1 Revision Date 10/24/2006 Page 2 of 6 Print Date 11/24/2011

	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after signific exposure.			
Ingestion	 Do not induce vomiting without medical advice. Seek medical attention if necessary. Rinse immediately with plenty of water for at least 15 minutes. If e irritation persists, seek medical attention. 			
Eyes				
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.			
	5. FIRE-FIGHTING MEASURES			
Flash point	: Greater than 200 °F (93 °C)			
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, dry powder, foam. 			
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 			
	6. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions : The product should not be allowed to enter drains, water cours soil. Should not be released into the environment.				
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.			
	7. HANDLING AND STORAGE			
Handling	: Heat only in areas with appropriate exhaust ventilation.			
Storage	: Keep containers dry and tightly closed to avoid moisture absorption			

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 53649 BU LC UV**

Version Number 1.1 Revision Date 10/24/2006

Page 3 of 6 Print Date 11/24/2011

8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION			
Respiratory protection	: U	Under normal handling conditions a respirator may not be required.				
Eye/Face Protection	: Sa	afety glasses with side-shields				
Hand protection	: Protective gloves.					
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: Sa	afety shoes.				
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		afety practice.		
Engineering measures		eat only in areas with appropr propriate exhaust ventilation		Provide		
Exposure limit(s)						
Components	Value					
	value	Exposure time	Exposure type	List:		
Silica, amorphous	Value 20 mppcf	Exposure time PEL:	Exposure type Total dust.	List: OSHA		
*		*				
^	20 mppcf	PEL:	Total dust.	OSHA		
^	20 mppcf 20 mppcf	PEL: PEL: Time Weighted Average	Total dust.	OSHA Z3		
^	20 mppcf 20 mppcf 0.8 mg/m3	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	Total dust.	OSHA Z3 Z3		
^	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA):	Total dust. Total dust.	OSHA Z3 Z3 MX OEL		
<u>`</u>	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA):	Total dust. Total dust. Inhalable particulate. Respirable dust.	OSHA Z3 Z3 MX OEL MX OEL		
<u>`</u>	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average	Total dust. Total dust. Inhalable particulate. Respirable dust.	OSHA Z3 Z3 MX OEL MX OEL		
Silica, amorphous	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO	Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not of the second s	OSHA Z3 Z3 MX OEL MX OEL MX OEL		
Silica, amorphous Form Appearance	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO L Evapo bus, liquid Specif	Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not of ic Gravity:	OSHA Z3 Z3 MX OEL MX OEL MX OEL		
Silica, amorphous Form Appearance Color	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : BLU	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO L Evapo bus, liquid Specifi E Bulk d	Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not of the second s	OSHA Z3 Z3 MX OEL MX OEL MX OEL established determined applicable		
Silica, amorphous Form Appearance Color Odor	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : BLUI : Very	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): CAL AND CHEMICAL PRO L Evapo pus, liquid Speciff E Bulk d faint Vapor	Total dust. Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not all of	OSHA Z3 Z3 MX OEL MX OEL MX OEL MX OEL		
Silica, amorphous Silica, amorphous	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : BLUU : Very : Not a	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): EXAL AND CHEMICAL PRO L Evapo bus, liquid Specif E Bulk d faint Vapor pplicable Vapou	Total dust. Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not a lensity ic Gravity: : Not a lensity pressure : Not a lensity ir density : Not a lensity	OSHA Z3 Z3 MX OEL MX OEL MX OEL MX OEL		
^	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : BLUU : Very : Not a	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): EXAL AND CHEMICAL PRO L Evapo bus, liquid Specif E Bulk d faint Vapor pplicable Vapou pH	Total dust. Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not a lensity ic Gravity: : Not a lensity pressure : Not a lensity ir density : Not a lensity	OSHA Z3 Z3 MX OEL MX OEL MX OEL MX OEL		
Form Appearance Color Odor Melting point/range Boiling Point:	20 mppcf 20 mppcf 0.8 mg/m3 10 mg/m3 10 mg/m3 3 mg/m3 9. PHYSIC : liquid : Visco : BLUI : Very : Not a : Inmi	PEL: PEL: Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): Time Weighted Average (TWA): EXAL AND CHEMICAL PRO L Evapo bus, liquid Specif E Bulk d faint Vapor pplicable Vapou pH	Total dust. Total dust. Total dust. Inhalable particulate. Respirable dust. DPERTIES ration rate : Not a ic Gravity: : Not a pressure : Not a ir density : Not a	OSHA Z3 Z3 MX OEL MX OEL MX OEL MX OEL		

PolyOne.

MATERIAL SAFETY DATA SHEET **PG 53649 BU LC UV**

Version Number 1.1 Revision Date 10/24/2006	6			Page 4 of 6 Print Date <i>11/24/2011</i>	
Hazardous Polymerizat	ion :	Will not occur.			
Conditions to avoid :		Keep away from oxidizing agents and open flame.			
Incompatible Materials	Incompatible with	Incompatible with strong acids and oxidizing agents.			
Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitroge (NOx), other hazardous materials, and smoke are all possible.					
	11.	TOXICOLOGIC	CAL INFORMATI	ON	
health data for the indiv Toxicity Overview	vidual comp	onents which com	prise the mixture.	sure effects listed are based on existing n have the following characteristics:	
CAS-No.	Chen	nical Name	Effect	Target Organ	
7631-86-9	Silica, amo		Irritant	Eyes, Respiratory system.	
	1		L INFORMATIO	Y	
Persistence and degrada	ability :	Not readily biod	legradable.		
Environmental Toxicity Bioaccumulation Poten		Adverse ecologi Does not bioacc	-	own or expected under normal use.	
Additional advice		No data availab			
Additional advice	•	ino uata availad.	le		
	1	3. DISPOSAL C	ONSIDERATION	S	
Product	:	generator of was classification, tr	ste material has the ansportation and dis	ed to disposal or incineration. The responsibility for proper waste sposal in accordance with and local regulations.	
Contaminated packagir	ig :	has the responsi	bility for proper wa accordance with app	e. The generator of waste material ste classification, transportation blicable federal, state/provincial	
	1	14. TRANSPORT	FINFORMATION	I	
U.S. DOT Classificatio	n :	Not regulated for	or transportation.		
ICAO/IATA (air)	:	Not regulated for	or transportation.		
IMO / IMDG (maritime	e) :	Not regulated for	or transportation.		

PolvOne.

MATERIAL SAFETY DATA SHEET **PG 53649 BU LC UV**

Version Number 1.1 Revision Date 10/24/2006 Page 5 of 6 Print Date 11/24/2011

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status

All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

:

Not applicable

California Proposition : Not applicable 65

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

Chemical Name			CAS-No.	Weight %	NPRI ID#
Bis (2-ethylhexyl) adipate			103-23-1	10.00 - 30.00	24
WHMIS Classification	:			are on the Canadian empt.	Domestic
tional Inventories:					
Australia AICS	:	Listed			
China IECS	:	Listed			
Europe EINECS	:	Listed			



MATERIAL SAFETY DATA SHEET **PG 53649 BU LC UV**

Version Number 1.1 Revision Date 10/24/2006 Page 6 of 6 Print Date 11/24/2011

Japan ENCS

: Not determined

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.