



MATERIAL SAFETY DATA SHEET

MISTLETOE

Version Number 1.1 Revision Date 06/04/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number		Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	MISTLETOE
Product code	:	CC10054149
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	1317-65-3	5 - 10
Titanium dioxide	13463-67-7	5 - 10
Chromium (III) oxide	1308-38-9	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		



MATERIAL SAFETY DATA SHEET

MISTLETOE

Version Number 1.1 Revision Date 06/04/2004 Page 2 of 6 Print Date 11/14/2011

Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.



MATERIAL SAFETY DATA SHEET **MISTLETOE**

Version Number 1.1 Revision Date 06/04/2004

Storage

Page 3 of 6 Print Date 11/14/2011

: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields.
Hand protection	:	Protective gloves.
Skin and body protection	:	Long sleeved clothing.
Additional Protective Measures	:	Safety shoes.
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Chromium (III) oxide	0.5 mg/m3	Time Weighted Average (TWA):	as Cr	ACGIH
	1 mg/m3	PEL:	as Cr	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: Solid	Evaporation rate	:	Not applicable
Appearance	: Pellets	Specific Gravity:	:	Not determined
Color	: GREEN	Bulk density	:	Not established
Odor	: Very faint	Vapor pressure	:	Not applicable
Melting point/range	: Not determined	Vapour density	:	Not applicable
Boiling Point:	: Not applicable	pН	:	Not applicable
Water solubility	: Insoluble	-		
	10. STABILITY AN	DREACTIVITY		

Stability

: Stable.



MATERIAL SAFETY DATA SHEET **MISTLETOE**

Version Number 1.1 Revision Date 06/04/2004		Page 4 of 6 Print Date 11/14/2011
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1308-38-9	Chromium (III) oxide	Irritant	Eyes, Skin.
		sensitizer	Skin.

Additional Health Hazard Information:

Chromium (III) oxide 1308-38-9 The bi and trivalent forms of chrome have a low order of acute toxicity but may cause skin sensitization and irritation to the eyes. No effects have been reported for chromium (III) oxide. Chromium (III) componds are not considered carcinogenic in animals or humans.

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	apprenete rederal, state provincial and rocal regulations.



TERIAL SAFETY DATA SI STLETOE					
sion Number 1.1 ision Date 06/04/2004				Prir	Page 5 nt Date 11/14/2
131011 Date 00/04/2004					
Contaminated packaging	:	Recycling is preferred thas the responsibility for and disposal in accordation and local regulations.	or proper waste	classification,	transportation
	1	4. TRANSPORT INFO	ORMATION		
U.S. DOT Classification	:	Not regulated for trans	portation.		
ICAO/IATA (air)	:	Refer to specific regula	ation.		
IMO / IMDG (maritime)	:	Refer to specific regula	ation.		
	15	. REGULATORY INF	ORMATION		
US Regulations:					
OSHA Status	:	Classified as hazardous	s based on com	ponents.	
TSCA Status		All components of this	product are list	ed on or exem	nt from the TSC
150115uuus	•	Inventory.	product dre list		prinoin the 150
US. EPA CERCLA Hazardou	s Sub	stances (40 CFR 302)			
Not applicable					
California Proposition	:	WARNING! This prod		chemical know	vn to the State o
65		California to cause can			
SARA Title III Section 302 E	xtrem	ely Hazardous Substance	9		
Not applicable					
SARA Title III Section 313 T	oxic (Chemicals:			
Chemical Name			CAS-No.	Weight	%
CHROMIUM III CO	MPOL	INDS	1308-38-9	23.14	
Canadian Regulations:					
Notional Dallatary Dal		NUMBER (NIDDI)			
National Pollutant Rel Chemical Name	ease II	iventory (NPKI)	CAS-No.	Weight %	NPRI ID#
Chromium (III) oxide			1308-38-9	23.14	68



MATERIAL SAFETY DATA SHEET

MISTLETOE

Version Number 1.1 Revision Date 06/04/2004 Page 6 of 6 Print Date *11/14/2011*

WHMIS Class	ification :	D2B	
WHMIS Ingred	dient Disclosı	ure List	
CAS-1 1308-3			
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.	
National Inventories:			
Australia AICS	S :	Listed	
China IECS	:	Listed	
Europe EINEC	CS :	Listed	
Japan ENCS	:	Listed	
Korea KECI	:	Listed	
Philippines PIC	CCS :	Listed	
		16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.