

## MATERIAL SAFETY DATA SHEET **PG 47053.01 BU PP UV**

Version Number 1.0 Revision Date 05/24/2004

Page 1 of 6 Print Date 11/14/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 47053.01 BU PP UV
Product code	:	CC10054301
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Zinc stearate	557-05-1	5 - 10

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

### POTENTIAL HEALTH EFFECTS

<b>Routes of Exposure:</b>	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eyes.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



# MATERIAL SAFETY DATA SHEET **PG 47053.01 BU PP UV**

Version Number 1.0 Revision Date 05/24/2004 Page 2 of 6 Print Date 11/14/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit		Not applicable
sower explosion limit	:	Not applicable
Autoignition temperature	÷	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6



# MATERIAL SAFETY DATA SHEET **PG 47053.01 BU PP UV**

Version Number 1.0 Revision Date 05/24/2004 Page 3 of 6 Print Date 11/14/2011

Considerations       Wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)         Image: Components of the symposyme	and contamination. Keep in a dry, cool place.						
Eye/Face Protection       ::       Safety glasses with side-shields.         Hand protection       ::       Protective gloves.         Skin and body protection       ::       Long sleeved clothing.         Additional Protective       ::       Safety shoes.         Measures       :       Handle in accordance with good industrial hygiene and safety pract         Considerations       :       Handle in accordance with good industrial hygiene and safety pract         Considerations       :       Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)       :       Respirable fraction.       OSHA         State stearate       :       5 mg/m3       PEL:       Total dust.       OSHA         10 mg/m3       Time Weighted Average       as stearates       ACGI         Corr       :       Solid       Evaporation rate       :       Not applicable         Appearance       ::       Pellets       Specific Gravity: ::       Not determined         Color       :       BUUE       Bulk density       :       Not applicable         Odor       :       :       Not applicable       pH       :       Not applicable         Odor       :       :       N	8. E	XPOSURE	<b>CONTROLS / PERSONA</b>	AL PROTECTION			
Hand protection       : Protective gloves.         Skin and body protection       : Long sleeved clothing.         Additional Protective       : Safety shoes.         Measures       : Safety shoes.         General Hygiene       : Handle in accordance with good industrial hygiene and safety pract Considerations         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)       : Respirable fraction. OSHA <u>Components       Value       Exposure time       Exposure type         List:       Zinc stearate       5 mg/m3       PEL:       Respirable fraction.       OSHA         10 mg/m3       Time Weighted Average       as stearates       ACGI         (TWA):       :       Not applicable         Appearance       : Pellets       Specific Gravity:       : Not applicable         Odor       : BLUE       Bulk density       : Not applicable         Melting point/range       : Not applicable       pH       : Not applicable         Boiling Point:       : Not applicable       pH       : Not applicable         Water solubility       : Insoluble       :       Not applicable         Water solubility       : Insoluble       : Will not occur.    </u>	Respiratory protection	: N	lo personal respiratory prote	ective equipment normally	required.		
Skin and body protection       : Long sleeved clothing.         Additional Protective       : Safety shoes.         Measures       :         General Hygiene       : Handle in accordance with good industrial hygiene and safety practive wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)       :         Components       Value       Exposure time       Exposure type       List:         Zine stearate       5 mg/m3       PEL:       Total dust.       OSHA         15 mg/m3       Time Weighted Average       as stearates       ACGI         (TWA):       :	Eye/Face Protection	: S	afety glasses with side-shie	lds.			
Additional Protective Measures       : Safety shoes.         General Hygiene Considerations       : Handle in accordance with good industrial hygiene and safety pract Wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)       : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)       : Respirable fraction. OSHA <u>Sine stearate</u> 5 mg/m3         15 mg/m3       PEL:         Respirable fraction. OSHA         10 mg/m3       Time Weighted Average (TWA): <b>9. PHYSICAL AND CHEMICAL PROPERTIES</b> Form       : Solid         Appearance       : Pellets         Specific Gravity:       : Not applicable         Odor       : BLUE       Bulk density       : Not applicable         Mediting point/range       : Not deplicable       pH       : Not applicable         Water solubility       : Insoluble       PH       : Not applicable         Io. STABILITY AND REACTIVITY       Stability       : Stable.         Hazardous Polymerization       : Will not occur.       Conditions to avoid       : Keep away from oxidizing agents and open flame. To avoid thern	Hand protection	: P	rotective gloves.				
Measures	Skin and body protection	: L	ong sleeved clothing.				
Considerations       Wash hands before breaks and at the end of workday.         Engineering measures       : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.         Exposure limit(s)         Exposure limit(s)         Components       Value         Exposure time       Exposure type         List:         Zinc stearate       5 mg/m3         PEL:       Respirable fraction.         OSHA         15 mg/m3       PEL:         Time Weighted Average       as stearates         ACGI         (TWA):       OSHA         PHYSICAL AND CHEMICAL PROPERTIES         Form       : Solid         Evaporation rate       : Not applicable         Appearance       : Pellets         Specific Gravity:       : Not applicable         Melting point/range       : Not determined         Vapour density       : Not applicable         Boiling Point:       : Not applicable         PH       : Not applicable         Water solubility       : Insoluble         IO. STABILITY AND REACTIVITY         Stability       : Stable.         Hazardous Polymerization       : Will not occur.         Conditions t		: S	afety shoes.				
appropriate exhaust ventilation at machinery.         Exposure limit(s)         Components       Value       Exposure time       Exposure type       List:         Zinc stearate       5 mg/m3       PEL:       Respirable fraction.       OSHA         15 mg/m3       PEL:       Total dust.       OSHA         10 mg/m3       Time Weighted Average (TWA):       as stearates       ACGI         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       :       Solid       Evaporation rate       :       Not applicable         Appearance       :       Pellets       Specific Gravity:       :       Not determine         Color       :       BLUE       Bulk density       :       Not applicable         Odor       :       Very faint       Vapour density       :       Not applicable         Boiling Point:       :       Not applicable       pH       :       Not applicable         IO. STABILITY AND REACTIVITY         Stability       :       Stable.         Hazardous Polymerization       :       Will not occur.       Conditions to avoid       :       Keep away from oxidizing agents and open flame. To avoid therm							
Components         Value         Exposure time         Exposure type         List:           Zinc stearate         5 mg/m3         PEL:         Respirable fraction.         OSHA           15 mg/m3         PEL:         Total dust.         OSHA           10 mg/m3         Time Weighted Average (TWA):         as stearates         ACGI           9. PHYSICAL AND CHEMICAL PROPERTIES           Form         :         Solid         Evaporation rate         :         Not applicable           Appearance         :         Pellets         Specific Gravity:         :         Not determine           Color         :         BLUE         Bulk density         :         Not establishe           Odor         :         Very faint         Vapour pressure         :         Not applicable           Melting point/range         :         Not applicable         pH         :         Not applicable           Boiling Point:         :         Not applicable         pH         :         Not applicable           Water solubility         :         Insoluble         :         Not applicable           Builtity         :         Stable.         :         Stable.           Hazardous Polymerization         :         Wil							
Zinc stearate       5 mg/m3       PEL:       Respirable fraction.       OSHA         15 mg/m3       PEL:       Total dust.       OSHA         10 mg/m3       Time Weighted Average (TWA):       as stearates       ACGI         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       :       Solid       Evaporation rate       :       Not applicable         Appearance       :       Pellets       Specific Gravity:       :       Not determine         Color       :       BLUE       Bulk density       :       Not establishe         Odor       :       Very faint       Vapor pressure       :       Not applicable         Boiling Point:       :       Not applicable       pH       :       Not applicable         Water solubility       :       Insoluble       Insoluble       Insoluble       Insoluble         Mathematican cocur.         Conditions to avoid       :       Will not occur.         Conditions to avoid       :       Keep away from oxidizing agents and open flame. To avoid therm	Exposure limit(s)						
Zinc stearate       5 mg/m3       PEL:       Respirable fraction.       OSHA         15 mg/m3       PEL:       Total dust.       OSHA         10 mg/m3       Time Weighted Average (TWA):       as stearates       ACGI         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       :       Solid       Evaporation rate       :       Not applicable         Appearance       :       Pellets       Specific Gravity:       :       Not determine         Color       :       BLUE       Bulk density       :       Not establishe         Odor       :       Very faint       Vapour density       :       Not applicable         Boiling point/range       :       Not applicable       pH       :       Not applicable         Water solubility       :       Insoluble       Insoluble       Insoluble         It       Stable.       Stability       :       Stable.       Example and open flame. To avoid therm	Components	Value	Exposure time	Exposure type	List:		
Image       Image       PEL:       Total dust.       OSHA         10 mg/m3       Time Weighted Average (TWA):       as stearates       ACGI         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       :       Solid       Evaporation rate       :       Not applicable         Appearance       :       Pellets       Specific Gravity:       :       Not determine         Color       :       BLUE       Bulk density       :       Not establishe         Odor       :       Very faint       Vapor pressure       :       Not applicable         Melting point/range       :       Not determined       Vapour density       :       Not applicable         Boiling Point:       :       Not applicable       pH       :       Not applicable         Water solubility       :       Insoluble       :       Insoluble         Image:       :       Stable.       :       :       Stable.         Hazardous Polymerization       :       Will not occur.       :       Conditions to avoid       :       Keep away from oxidizing agents and open flame. To avoid therm	*						
(TWA):         9. PHYSICAL AND CHEMICAL PROPERTIES         Form       : Solid       Evaporation rate       : Not applicable         Appearance       : Pellets       Specific Gravity:       : Not determine         Color       : BLUE       Bulk density       : Not establishe         Odor       : Very faint       Vapor pressure       : Not applicable         Melting point/range       : Not determined       Vapour density       : Not applicable         Boiling Point:       : Not applicable       pH       : Not applicable         Water solubility       : Insoluble       Insoluble         Io. STABILITY AND REACTIVITY         Stability       : Stable.         Hazardous Polymerization       : Will not occur.         Conditions to avoid       : Keep away from oxidizing agents and open flame. To avoid therm		15 mg/m3					
Form       : Solid       Evaporation rate       : Not applicable         Appearance       : Pellets       Specific Gravity:       : Not determine         Color       : BLUE       Bulk density       : Not establishe         Odor       : Very faint       Vapor pressure       : Not applicable         Melting point/range       : Not determined       Vapour density       : Not applicable         Boiling Point:       : Not applicable       pH       : Not applicable         Water solubility       : Insoluble       Insoluble       Insoluble         Image: Hazardous Polymerization       : Will not occur.       : Keep away from oxidizing agents and open flame. To avoid therm		10 mg/m3		e as stearates	ACGIH		
Form       : Solid       Evaporation rate       : Not applicable         Appearance       : Pellets       Specific Gravity:       : Not determine         Color       : BLUE       Bulk density       : Not establishe         Odor       : Very faint       Vapor pressure       : Not applicable         Melting point/range       : Not determined       Vapour density       : Not applicable         Boiling Point:       : Not applicable       pH       : Not applicable         Water solubility       : Insoluble       Insoluble       Insoluble         Metaradous Polymerization       : Will not occur.       : Keep away from oxidizing agents and open flame. To avoid therm							
Appearance       : Pellets       Specific Gravity:       : Not determined         Color       : BLUE       Bulk density       : Not establishe         Odor       : Very faint       Vapor pressure       : Not applicable         Melting point/range       : Not determined       Vapour density       : Not applicable         Boiling Point:       : Not applicable       pH       : Not applicable         Water solubility       : Insoluble       : Not applicable       : Not applicable         Stability       : Stable.       : Stable.       : Will not occur.         Conditions to avoid       : Keep away from oxidizing agents and open flame. To avoid therm		9. PHYSIC	CAL AND CHEMICAL P	ROPERTIES			
Stability       : Stable.         Hazardous Polymerization       : Will not occur.         Conditions to avoid       : Keep away from oxidizing agents and open flame. To avoid thern	Appearance: PelletsSpecific Gravity:: Not determinedColor: BLUEBulk density: Not establishedOdor: Very faintVapor pressure: Not applicableMelting point/range: Not determinedVapour density: Not applicableBoiling Point:: Not applicablepH: Not applicable						
Hazardous Polymerization       : Will not occur.         Conditions to avoid       : Keep away from oxidizing agents and open flame. To avoid therm		10. 5	STABILITY AND REACT	TIVITY			
Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thern	Stability	: S	table.				
	Hazardous Polymerization	n : W	Vill not occur.				
	Conditions to avoid				avoid thermal		
Incompatible Materials : Incompatible with strong acids and oxidizing agents.	Incompatible Materials	: Ir	ncompatible with strong aci	ds and oxidizing agents.			



## MATERIAL SAFETY DATA SHEET **PG 47053.01 BU PP UV**

Version Number 1.0 Revision Date 05/24/2004 Page 4 of 6 Print Date 11/14/2011

Hazardous decomposition products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
557-05-1	Zinc stearate	Systemic effects	Eyes, Skin, Respiratory system.

#### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
557-05-1	Zinc stearate	Oral LD50	> 10 gm/kg	rat

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
	: Not regulated for transportation.



# MATERIAL SAFETY DATA SHEET **PG 47053.01 BU PP UV**

Version Number 1.0 Revision Date 05/24/2004 Page 5 of 6 Print Date 11/14/2011

US Regui O T	IDG (maritime)	:	Refer to specific regula Refer to specific regula <b>. REGULATORY INF</b> Classified as hazardous All components of this Inventory.	ntion. ORMATION		pt from the TSC
US Regui O T	lations: SHA Status SCA Status CERCLA Hazardous S	15 :	. REGULATORY INF Classified as hazardous All components of this Inventory.	ORMATION		pt from the TSC
O T	SHA Status SCA Status CERCLA Hazardous S	:	Classified as hazardous All components of this Inventory.	s based on comp		pt from the TSC
O T	SHA Status SCA Status CERCLA Hazardous S	:	All components of this Inventory.	-		pt from the TSC
Т	SCA Status CERCLA Hazardous S	:	All components of this Inventory.	-		pt from the TSC
	CERCLA Hazardous S	: Subs	Inventory.	product are liste	ed on or exemp	pt from the TSC
US. EPA		Subs	stances (40 CFR 302)			
	Not applicable					
C 6:	alifornia Proposition 5	:	This product does not c	contain a substan	ce listed by C	alifornia Prop 6
SARA Ti	tle III Section 302 Extr	eme	ely Hazardous Substance	e		
Not a	pplicable					
-						
SARA Ti	tle III Section 313 Tox	ic C	hemicals:			
C	Themical Name			CAS-No.	Weight	%
	INC COMPOUNDS			557-05-1	5.00	
Canadian	Regulations:					
	ational Pollutant Releas	se Ir	ventory (NPRI)	C A C N	<b>XXX • 1</b> • 0/	
		se Ir	ventory (NPRI)	<b>2</b> • <b>2</b> • <b>2</b>		
Cher Zinc	nical Name e stearate			CAS-No. 557-05-1	Weight % 5.00	NPRI ID# 241
Cher Zinc	nical Name	se Ir			-	
Cher Zinc	nical Name e stearate			557-05-1 s product are on	5.00	241
Cher Zinc W D	nical Name stearate /HMIS Classification	:	Not controlled. All components of this	557-05-1 s product are on	5.00	241



## MATERIAL SAFETY DATA SHEET **PG 47053.01 BU PP UV**

Version Number 1.0 Revision Date 05/24/2004 Page 6 of 6 Print Date 11/14/2011

China IECS	:	Listed
Europe EINECS	:	Listed
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.