PolvOne

MATERIAL SAFETY DATA SHEET CHESTNUT TONER

Version Number 1.2 Revision Date 09/20/2007

Page 1 of 7 Print Date 12/1/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone | : | Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|----------------------------------|---|---|
| Product name | : | CHESTNUT TONER |
| Product code | : | CC10054467 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight % |
|---|------------|----------|
| Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164) | 68412-38-4 | 10 - 30 |
| Rutile, antimony chromium buff | 68186-90-3 | 10 - 30 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---------------------|--|
| Acute exposure | |
| Inhalation | : Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Particulates, like other inert materials can be mechanically irritating. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |
| Chronic exposure | : Refer to Section 11 for Toxicological Information. |

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT TONER

Version Number 1.2 Revision Date 09/20/2007 Page 2 of 7 Print Date 12/1/2011

| Aggravated by Exposure: | |
|--|--|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists see medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : Not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | Not applicable Not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT TONER

| Version Number 1.2 Revision Date 09/20/2007 | | Page 3 of 7 Print Date 12/1/2011 |
|--|----|---|
| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat |
| | | only in areas with appropriate exhaust ventilation. |
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
| 8. EXPOS | UF | RE CONTROLS / PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |

PolyOne

MATERIAL SAFETY DATA SHEET **CHESTNUT TONER**

Version Number 1.2 Revision Date 09/20/2007 Page 4 of 7 Print Date 12/1/2011

| Components | Value | Exposure time | Exposure type | List: |
|---|-----------|---------------------------------|---------------|---------|
| Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164) | 5 mg/m3 | Ceiling Limit Value: | as Mn | OSHA Z1 |
| | 0.2 mg/m3 | Time Weighted Average (TWA): | as Mn | ACGIH |
| | 0.2 mg/m3 | Time Weighted Average (TWA): | as Mn | MX OEL |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | MX OEL |
| Rutile, antimony chromium buff | 0.5 mg/m3 | Time Weighted Average (TWA): | as Cr | ACGIH |
| | 0.5 mg/m3 | PEL: | as Cr | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Color Odour Melting point/range Boiling Point: Water solubility
- : Solid : pellets : BROWN Very faint Not determined Not applicable

:

:

:

: Insoluble

Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pН

- : Not applicable Not determined :
- Not established :
- Not applicable :
- : Not applicable
- Not applicable :

10. STABILITY AND REACTIVITY

| Stability | : | Stable. |
|--------------------------|---|---|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace |

MATERIAL SAFETY DATA SHEET CHESTNUT TONER

Version Number 1.2Page 5 of 7Revision Date 09/20/2007Print Date 12/1/2011

quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), hydrogen chloride (HCl), other hazardous materials, and
smoke are all possible. Prolonged heating (approximately 30 minutes
or more) above 392 °F (200 °C) or short term heating at 482 °F (250
°C) may result in product decomposition and evolution of carbon
monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|--|----------|---------------------------------|
| 68412-38-4 | Manganese antimony titanium brown rutile (C.I. Pigment Yellow 164) | Irritant | Eyes, Skin. |
| 68186-90-3 | Rutile, antimony chromium buff | Irritant | Eyes, Skin, Respiratory system. |

Additional Health Hazard Information:

Rutile, antimony chromium buff 68186-90-3 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

| Persistence and degradability | : Not readily biodegradable. |
|-------------------------------|---|
| Environmental Toxicity | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Bioaccumulation Potential | : Chemicals are not readily available as they are bound within the polymer matrix. |
| Additional advice | : No data available |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |

PolyOne.

MATERIAL SAFETY DATA SHEET CHESTNUT TONER

| sion Number 1.2 ision Date 09/20/2007 | | | | Page 6 Print Date 12/1/2 |
|---|-------|---|------------------|--|
| Contaminated packaging | : | has the responsibility for | proper waste cl | ne generator of waste material assification, transportation le federal, state/provincial |
| | 1 | 4. TRANSPORT INFOR | MATION | |
| U.S. DOT Classification | | Not regulated for transpor | tation | |
| | · | | | |
| ICAO/IATA (air) | : | Refer to specific regulatio | n. | |
| IMO / IMDG (maritime) | : | Refer to specific regulatio | n. | |
| | 15 | . REGULATORY INFO | RMATION | |
| US Regulations: | | | | |
| OSHA Status | : | Classified as hazardous ba | ased on compo | nents. |
| TSCA Status | : | All components of this pr Inventory. | oduct are listed | on or exempt from the TSCA |
| US. EPA CERCLA Hazardous | Sub | stances (40 CFR 302) | | |
| Not applicable | | | | |
| California Proposition 65 | : | Not applicable | | |
| SARA Title III Section 302 Ext | trem | ely Hazardous Substance | | |
| Unless specific chemicals are id | denti | fied under this section, this | product is Not | Applicable under this regula |
| SARA Title III Section 313 To: | xic (| Chemicals: | | |
| Unless specific chemicals are id | denti | fied under this section, this | product is Not | Applicable under this regular |
| Chemical Name | | | CAS-No. | Weight % |
| THE REAL REPORT OF A REPORT | DSA | NTIMONY | 68412-38-4 | 10.00 - 30.00 |
| MANGANESE COMPOUN COMPOUNDS | | | | |

PolyOne

MATERIAL SAFETY DATA SHEET CHESTNUT TONER

Version Number 1.2 Revision Date 09/20/2007 Page 7 of 7 Print Date 12/1/2011

| Chemical Name | | CAS-No. | Weight % | NPRI ID# |
|---|---|---|--------------------|----------|
| Manganese antimony titaniu Pigment Yellow 164) | m brown rutile (C.I. | 68412-38-4 | 10.00 - 30.00 | 147 |
| 6 | | | 10.00 - 30.00 | 17 |
| Rutile, antimony chromium l | ouff | 68186-90-3 | 10.00 - 30.00 | 69 |
| - | | | 10.00 - 30.00 | 17 |
| WHMIS Ingredient Disc CAS-No. 68412-38-4 68186-90-3 | | | | |
| DSL | | | re on the Canadian | Domestic |
| DSL ational Inventories: | | s of this product a (DSL) or are exe | | Domestic |
| | | | | Domestic |
| ational Inventories: | Substances List | | | Domestic |
| ational Inventories: Australia AICS | Substances List | (DSL) or are exe | | Domestic |
| ational Inventories: Australia AICS China IECS | Substances List : Listed : Listed | (DSL) or are exe | | Domestic |
| ational Inventories: Australia AICS China IECS Europe EINECS | Substances List : Listed : Listed : Not determined | (DSL) or are exe | | Domestic |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.