## MATERIAL SAFETY DATA SHEET PG 54499.00 PEARL WT PET

Version Number 1.0 Revision Date 05/26/2004

Page 1 of 6 Print Date 11/14/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	PG 54499.00 PEARL WT PET
Product code	:	CC10054499
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	1 - 5
Mica	12001-26-2	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



MATERIAL SAFETY DATA SHEET PG 54499.00 PEARL WT PET

Version Number 1.0 Revision Date 05/26/2004 Page 2 of 6 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
sower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1: of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

2/6

PolyOne.

# MATERIAL SAFETY DATA SHEET PG 54499.00 PEARL WT PET

Version Number 1.0 Revision Date 05/26/2004 Page 3 of 6 Print Date 11/14/2011

		nd contamination. Keep in a d	iry, coor place.	
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protecti	ve equipment normally r	required.
Eye/Face Protection	: Sa	afety glasses with side-shields		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations		andle in accordance with good ash hands before breaks and a		afety practice.
Engineering measures		eat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Mica	20 mppcf	PEL:	Total dust.	OSHA
	3 mg/m3	Time Weighted Average	Description 1.1. Constitution	
	5 mg mo	(TWA):	Respirable fraction.	ACGIH
Titanium dioxide	10 mg/m3	(TWA): Time Weighted Average	Kespirable fraction.	ACGIH ACGIH
Titanium dioxide	-	(TWA):	Total dust.	
Titanium dioxide	10 mg/m3 15 mg/m3	(TWA): Time Weighted Average (TWA): PEL:	Total dust.	ACGIH
Titanium dioxide	10 mg/m3 15 mg/m3	(TWA): Time Weighted Average (TWA):	Total dust.	ACGIH
	10 mg/m3 15 mg/m3 9. PHYSIC	(TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust.	ACGIH OSHA Z1
Form	10 mg/m3 15 mg/m3 9. PHYSIC : Solid	(TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO	Total dust. DPERTIES ration rate : Not	ACGIH OSHA Z1 applicable
Form Appearance	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle	(TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specif	Total dust. DPERTIES ration rate : Not ic Gravity: : Not	ACGIH OSHA Z1 applicable determined
Form Appearance Color	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI	(TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specif TE Bulk d	Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not	ACGIH OSHA Z1 applicable determined established
Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very	(TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specif TE Bulk d faint Vapor	Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not pressure : Not	ACGIH OSHA Z1 applicable determined established applicable
Form Appearance Color Odor Melting point/range	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c	(TWA): Time Weighted Average (TWA): PEL: CAL AND CHEMICAL PRO Evapo ts Specifi TE Bulk d faint Vapor letermined Vapou	Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not pressure : Not r density : Not	ACGIH OSHA Z1 applicable determined established applicable applicable
Form Appearance Color Odor	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c	(TWA):         Time Weighted Average (TWA):         PEL:         CAL AND CHEMICAL PRO         ts       Specif         TE       Bulk d         faint       Vapor         letermined       Vapor         pplicable       pH	Total dust. DPERTIES ration rate : Not ic Gravity: : Not lensity : Not pressure : Not r density : Not	ACGIH OSHA Z1 applicable determined established applicable
Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol	(TWA):         Time Weighted Average (TWA):         PEL:         CAL AND CHEMICAL PRO         ts       Specif         TE       Bulk d         faint       Vapor         letermined       Vapor         pplicable       pH	Total dust. <b>DPERTIES</b> ration rate : Not ic Gravity: : Not lensity : Not pressure : Not ir density : Not : Not	ACGIH OSHA Z1 applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point:	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol 10. S	(TWA):         Time Weighted Average (TWA):         PEL:         CAL AND CHEMICAL PRODUCT         L       Evapo         ts       Specifi         TE       Bulk do         faint       Vapor         letermined       Vapor         upplicable       pH	Total dust. <b>DPERTIES</b> ration rate : Not ic Gravity: : Not lensity : Not pressure : Not ir density : Not : Not	ACGIH OSHA Z1 applicable determined established applicable applicable
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	10 mg/m3 15 mg/m3 9. PHYSIC : Solid : Pelle : WHI : Very : Not c : Not a : Insol 10. S : St	(TWA):         Time Weighted Average (TWA):         PEL:         CAL AND CHEMICAL PRO         I       Evapo         ts       Specifi         TE       Bulk d         faint       Vapor         letermined       Vapou         upplicable       pH         uble       TABILITY AND REACTIVE	Total dust. <b>DPERTIES</b> ration rate : Not ic Gravity: : Not lensity : Not pressure : Not ir density : Not : Not	ACGIH OSHA Z1 applicable determined established applicable applicable

P<u>olyOne</u>

## MATERIAL SAFETY DATA SHEET PG 54499.00 PEARL WT PET

Version Number 1.0 Revision Date 05/26/2004 Page 4 of 6 Print Date 11/14/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
12001-26-2	Mica	Systemic effects	Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matri of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matri of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
	: Not regulated for transportation.
U.S. DOT Classification	. Not regulated for transportation.

PolyOne.

# MATERIAL SAFETY DATA SHEET PG 54499.00 PEARL WT PET

Version Number 1.0 Revision Date 05/26/2004 Page 5 of 6 Print Date 11/14/2011

IMO / IMDG (maritime)	:	Refer to specific regulation.		
	15. REGULATORY INFORMATION			
US Regulations:				
OSHA Status	:	Classified as hazardous based on components.		
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.		
US. EPA CERCLA Hazardous	Subs	stances (40 CFR 302)		
Not applicable				
-	:	WARNING! This product contains a chemical known to the State of		
65		California to cause cancer.		
SARA Title III Section 302 Extr	rem	ely Hazardous Substance		
Not applicable				
SARA Title III Section 313 Tox	tic C	Themicals:		
Not applicable Canadian Regulations:				
National Pollutant Releas	se Ir	iventory (NPRI)		
Not applicable				
WHMIS Classification	:	Not controlled.		
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.		
National Inventories:				
Australia AICS	:	Not determined		
China IECS	:	Listed		
Europe EINECS	:	Listed		
Japan ENCS	:	Not determined		
Korea KECI	:	Listed		



## MATERIAL SAFETY DATA SHEET PG 54499.00 PEARL WT PET

Version Number 1.0 Revision Date 05/26/2004 Page 6 of 6 Print Date 11/14/2011

Philippines PICCS

: Not determined

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.