

MATERIAL SAFETY DATA SHEET

UV WHITE #138

Version Number 1.0 Revision Date 06/07/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	UV WHITE #138
Product code	:	CC10054777
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Phenol,	25973-55-1	5 - 10
2-(2H-benzotriazol-2-yl)-4,6-bis(1,1-dimeth		
ylpropyl)-		
Titanium dioxide	13463-67-7	30 - 60

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

UV WHITE #138

Version Number 1.0 Revision Date 06/07/2004 Page 2 of 6 Print Date 11/14/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive
Procedures Unusual Fire/Explosion Hazards	 pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET **UV WHITE #138**

Storage : 1 8. EXPOSURE Respiratory protection : 1 Eye/Face Protection : 1 Hand protection : 1 Skin and body protection : 1 Additional Protective : 1 Additional Protective : 1 Measures : 1 General Hygiene : 1 Considerations : 1 Engineering measures : 1 Exposure limit(s) : 1 Form : Solid Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	Yake measures to prevent the b nly in areas with appropriate of Geep containers dry and tightly nd contamination. Keep in a of CONTROLS / PERSONAL No personal respiratory protect afety glasses with side-shields Protective gloves. Long sleeved clothing. afety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with appropri- ppropriate exhaust ventilation	exhaust ventilation. y closed to avoid moistur dry, cool place. <u>PROTECTION</u> tive equipment normally s. d industrial hygiene and at the end of workday. riate exhaust ventilation.	re absorption		
Storage : 1 Respiratory protection : 1 Eye/Face Protection : 1 Hand protection : 1 Skin and body protection : 1 Additional Protective : 1 Additional Protective : 1 Measures : 1 General Hygiene : 1 Considerations : 1 Engineering measures : 1 Exposure limit(s) : 1 Form : Solid Appearance : PHYSI Form : Solid Appearance : PHI Color : WH Odor : Ver Melting point/range : Not	nly in areas with appropriate of Geep containers dry and tightly nd contamination. Keep in a CONTROLS / PERSONAL To personal respiratory protect afety glasses with side-shields protective gloves. Cong sleeved clothing. afety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with appropriate exhaust ventilation	exhaust ventilation. y closed to avoid moistur dry, cool place. <u>PROTECTION</u> tive equipment normally s. d industrial hygiene and at the end of workday. riate exhaust ventilation. at machinery.	re absorption required. safety practic		
8. EXPOSURE Respiratory protection : I Eye/Face Protection : I Hand protection : I Skin and body protection : I Additional Protective : I Additional Protective : I Measures : I General Hygiene : I Considerations : I Engineering measures : I Exposure limit(s) : I Components Value Value Titanium dioxide 10 mg/m3 I J : : Solit Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	nd contamination. Keep in a contamination of the second second second second respiratory protect contact and second sec	dry, cool place. <u>PROTECTION</u> tive equipment normally s. d industrial hygiene and at the end of workday. riate exhaust ventilation. at machinery.	required. safety practic		
Respiratory protection : I Eye/Face Protection : S Hand protection : I Skin and body protection : I Additional Protective : S Measures : I General Hygiene : I Considerations : I Engineering measures : I Exposure limit(s) : I Components Value I Titanium dioxide 10 mg/m3 I 5 : : Solit Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	To personal respiratory protect afety glasses with side-shields protective gloves. Song sleeved clothing. afety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with approp- ppropriate exhaust ventilation	tive equipment normally s. d industrial hygiene and at the end of workday. riate exhaust ventilation. at machinery.	safety practic		
Eye/Face Protection : S Hand protection : I Skin and body protection : I Additional Protective : I Additional Protective : I Additional Protective : I Measures : I General Hygiene : I Considerations : I Engineering measures : I Exposure limit(s) : I Components Value Value Titanium dioxide 10 mg/m3 I Image: Solid Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	afety glasses with side-shields Protective gloves. Long sleeved clothing. Lafety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with approp ppropriate exhaust ventilation	s. d industrial hygiene and at the end of workday. riate exhaust ventilation. at machinery.	safety practic		
Hand protection : I Skin and body protection : I Additional Protective : S Additional Protective : S Measures : I General Hygiene : I Considerations : I Engineering measures : I Exposure limit(s) : I Components Value Value Titanium dioxide 10 mg/m3 I Image: Solid Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	Protective gloves. Long sleeved clothing. Lafety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with appropri- ppropriate exhaust ventilation	d industrial hygiene and at the end of workday. riate exhaust ventilation. at machinery.	. Provide		
Skin and body protection : I Additional Protective : S Measures : S General Hygiene : I Considerations : I Engineering measures : I Exposure limit(s) : I Components Value Value Titanium dioxide 10 mg/m3 15 mg/m3 : Solit Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	Long sleeved clothing. afety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with approp ppropriate exhaust ventilation	at the end of workday. riate exhaust ventilation. at machinery.	. Provide		
Additional Protective : S Measures : I General Hygiene : I Considerations : I Engineering measures : I Exposure limit(s) : I Components Value Value Titanium dioxide 10 mg/m3 Image: Solid Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	afety shoes. Handle in accordance with good Vash hands before breaks and Heat only in areas with approp- ppropriate exhaust ventilation	at the end of workday. riate exhaust ventilation. at machinery.	. Provide		
Measures General Hygiene : I Considerations	Iandle in accordance with goo Vash hands before breaks and Ieat only in areas with approp ppropriate exhaust ventilation	at the end of workday. riate exhaust ventilation. at machinery.	. Provide		
Considerations I Engineering measures : Exposure limit(s) Components Value Titanium dioxide 10 mg/m3 15 mg/m3 PHYSI Form : Solid Appearance : Color : WH Odor : Melting point/range :	Vash hands before breaks and leat only in areas with approp ppropriate exhaust ventilation	at the end of workday. riate exhaust ventilation. at machinery.	. Provide		
Exposure limit(s) Components Value Titanium dioxide 10 mg/m3 15 mg/m3 9. PHYSI Form : Soli Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	ppropriate exhaust ventilation	at machinery.			
Components Value Titanium dioxide 10 mg/m3 15 mg/m3 9. PHYSI Form : Soli Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	Exposure time	Exposure type	List:		
Titanium dioxide 10 mg/m3 Titanium dioxide 10 mg/m3 15 mg/m3 9. PHYSI Form : Soli Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	Exposure time	Exposure type	List:		
Titanium dioxide 10 mg/m3 Titanium dioxide 10 mg/m3 15 mg/m3 9. PHYSI Form : Soli Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	EXPOSUTE TIME	1			
9. PHYSI Form : Soli Appearance : Pell Color : WH Odor : Ver Melting point/range : Not	Time Weighted Average (TWA):		ACGIH		
Form: SoliAppearance: PellColor: WHOdor: VerMelting point/range: Not	PEL:	Total dust.	OSHA Z		
Appearance: PellColor: WHOdor: VerMelting point/range: Not	CAL AND CHEMICAL PRO	OPERTIES			
Appearance: PellColor: WHOdor: VerMelting point/range: Not	d Evapo	oration rate : No	t applicable		
Odor: VerMelting point/range: Not		· · · · · · · · · · · · · · · · · · ·	t determined		
Melting point/range : Not		2	t established		
01			t applicable t applicable		
Doning Fond Not	applicable pH		t applicable		
Water solubility : Insc		. 10	t applicable		
-					
10.	STABILITY AND REACTI	VITY			
Stability : S	tability : Stable.				
Hazardous Polymerization : V		Hazardous Polymerization : Will not occur.			
	Vill not occur.				



MATERIAL SAFETY DATA SHEET **UV WHITE #138**

Version Number 1.0 Revision Date 06/07/2004		Page 4 of 6 Print Date 11/14/2011
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
25973-55-1	Phenol, 2-(2H-benzotriazol-2-yl)-4 ,6-bis(1,1-dimethylpropyl) -	Systemic effects	Kidney, Liver, reproductive system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste



MATERIAL SAFETY DATA SHEET **UV WHITE #138**

V VVIIIIL #150		
rsion Number 1.0 vision Date 06/07/2004		Page 5 o Print Date 11/14/20
		classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	:	Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	1	4. TRANSPORT INFORMATION
U.S. DOT Classification	:	Not regulated for transportation.
ICAO/IATA (air)	:	Refer to specific regulation.
IMO / IMDG (maritime)	:	Refer to specific regulation.
	15	5. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	rem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 To:	xic (Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	se Iı	NVENTORY (NPRI) CAS-No. Weight % NPRI ID#



MATERIAL SAFETY DATA SHEET **UV WHITE #138**

Version Number 1.0 Revision Date 06/07/2004 Page 6 of 6 Print Date 11/14/2011

Chemical Name	CAS-No.	Weight %	NPRI ID#
Iron chromite brown spinel (C.I. Pigment Brown 35)	68187-09-7	0.14	68
Chromium (III) oxide	1308-38-9	0.11	68

WHMIS Classification : Not controlled.

DSL

.

: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Not determined
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.