

MATERIAL SAFETY DATA SHEET UV TRANS. YELLOW 116U

Version Number 1.0 Revision Date 06/15/2004 Page 1 of 5 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	UV TRANS. YELLOW 116U
Product code :	CC10055436
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact	
Acute exposure		
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling. 	
Chronic exposure Medical Conditions	Refer to Section 11 for Toxicological Information.None known.	
Aggravated by Exposure:	4. FIRST AID MEASURES	



MATERIAL SAFETY DATA SHEET UV TRANS. YELLOW 116U

sion Date 06/15/2004	Print Date 11	age 2 //14/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all ca doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptometry persist or in all cases of doubt seek medical advice.	ms
Eyes	: Rinse immediately with plenty of water, also under the eyelids, least 15 minutes. If eye irritation persists, seek medical attentio	
Skin	: Wash off with soap and plenty of water. If skin irritation persist medical attention.	s see
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in pos pressure mode should be worn to prevent inhalation of airborne contaminants.	itive
Unusual Fire/Explosion Hazards	 Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrog (NOx), other hazardous materials, and smoke are all possible. 	en
	ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	ld no
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all materia plastic, cardboard or metal containers for disposal. Refer to Sect of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Honly in areas with appropriate exhaust ventilation.	Ieat
Storage	: Keep containers dry and tightly closed to avoid moisture absorp and contamination. Keep in a dry, cool place.	tion



MATERIAL SAFETY DATA SHEET UV TRANS. YELLOW 116U

Version Number 1.0 Revision Date 06/15/2004 Page 3 of 5 Print Date 11/14/2011

Respiratory protection	: No personal respira	atory protective equipment normally required.
Eye/Face Protection	: Safety glasses with	side-shields.
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved cloth	ing.
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations		the with good industrial hygiene and safety practice breaks and at the end of workday.
Engineering measures		with appropriate exhaust ventilation. Provide t ventilation at machinery.
Exposure limit(s)		
Form	PHYSICAL AND CHEM Solid Pallate	Evaporation rate : Not applicable
Appearance	: Pellets	Specific Gravity: : Not determined
Color Odor	: YELLOW : Very faint	Bulk density: Not establishedVapor pressure: Not applicable
Melting point/range	: Not determined	Vapour density : Not applicable
Boiling Point:	: Not applicable	pH : Not applicable
Water solubility	: Insoluble	1 11
	10. STABILITY AND	D REACTIVITY
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open flame. To avoid thermal not overheat.
Incompatible Materials	: Incompatible with	strong acids and oxidizing agents.
		O2), carbon monoxide (CO), oxides of nitrogen dous materials, and smoke are all possible.
Hazardous decomposition products		

PolyOne

MATERIAL SAFETY DATA SHEET UV TRANS. YELLOW 116U

Version Number 1.0 Revision Date 06/15/2004 Page 4 of 5 Print Date 11/14/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the matrix of the polymer.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	
	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

PolyOne

MATERIAL SAFETY DATA SHEET UV TRANS. YELLOW 116U

Version Numb	er 1.0
Revision Date	06/15/2004

Page 5 of 5 Print Date 11/14/2011

California Proposition : This product does not contain a substance listed by California Prop 65. 65					
SARA Title III Section 302 Extremely Hazardous Substance					
Not applicable					
SARA Title III Section 313 Toxic Chemicals:					
Not applicable Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
Not applicable					
WHMIS Classification : Not controlled.					
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.					
National Inventories:					
Australia AICS : Listed					
China IECS : Listed					
Europe EINECS : Not determined					
Japan ENCS : Not determined					
Korea KECI : Listed					
Philippines PICCS : Not determined					
16. OTHER INFORMATION					

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.