

MATERIAL SAFETY DATA SHEET PG 55580.00 FROST RD PP

Version Number 1.0 Revision Date 06/18/2004

Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	PG 55580.00 FROST RD PP	
Product code	:	CC10055580	
Chemical Name	:	Mixture	
CAS-No.	:	Mixture	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Mica	12001-26-2	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact		
Acute exposure			
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. 		
Skin	: Experience shows no unusual dermatitis hazard from routine handling.		
Chronic exposure	: Refer to Section 11 for Toxicological Information.		
Medical Conditions Aggravated by Exposure:	: None known.		



MATERIAL SAFETY DATA SHEET PG 55580.00 FROST RD PP

Version Number 1.0 Revision Date 06/18/2004 Page 2 of 6 Print Date 11/14/2011

	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes: Rinse immediately with plenty of water, also under the eye least 15 minutes. If eye irritation persists, seek medical atter	
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits	
Upper explosion limit	: Not applicable
sower explosion limit	: Not applicable
Autoignition temperature	: Not applicable
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 3 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption

PolyOne.

MATERIAL SAFETY DATA SHEET PG 55580.00 FROST RD PP

Version Number 1.0 Revision Date 06/18/2004 Page 3 of 6 Print Date 11/14/2011

and contamination. Keep in a dry, cool place. 8. EXPOSURE CONTROLS / PERSONAL PROTECTION						
Respiratory protection		lo personal respiratory protec		equired.		
Eye/Face Protection	: Safety glasses with side-shields.					
Hand protection	: Protective gloves.					
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: Safety shoes.					
General Hygiene Considerations		: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.						
Exposure limit(s)						
Components	Value	Exposure time	Exposure type	List:		
Mica	20 mppcf	PEL:	Total dust.	OSHA		
	3 mg/m3					
	5 mg/m5	Time Weighted Average (TWA):	Respirable fraction.	ACGIH		
		• •		ACGIH		
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	9. PHYSIC : Solid : Pelle : RED : Very : Not o	(TWA): CAL AND CHEMICAL PR I Evap ts Special traint Vapo determined Vapo applicable pH	OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not	ACGIH applicable determined established applicable applicable applicable		
Appearance Color Odor Melting point/range Boiling Point:	9. PHYSIC : Solid : Pelle : RED : Very : Not d : Not a : Insol	(TWA): CAL AND CHEMICAL PR I Evap ts Special traint Vapo determined Vapo applicable pH	OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	applicable determined established applicable applicable		
Appearance Color Odor Melting point/range Boiling Point:	9. PHYSIC : Solid : Pelle : RED : Very : Not a : Insol 10. S	(TWA):CAL AND CHEMICAL PRIEvapIEvapetsSpeciOBulkfaintVapodeterminedVapoapplicablepHlubleVapo	OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	applicable determined established applicable applicable		
Appearance Color Odor Melting point/range Boiling Point: Water solubility	9. PHYSIC : Solid : Pelle : RED : Very : Not a : Insol 10. S : S	(TWA): CAL AND CHEMICAL PR 1 Evap 2 Special 2 Bulk 2 Bulk 2 Faint 3 Vapo 4 Check 4 Check 5 Special 6 Pheck 6 Pheck 7 Pheck 7 Pheck 6 Pheck 7 Pheck	OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not	applicable determined established applicable applicable		
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	9. PHYSIC : Solid : Pelle : RED : Very : Not d : Not a : Insol 10. S n : W : K	(TWA): CAL AND CHEMICAL PR I Evap I Evap ets Speci I Bulk faint Vapo determined Vapo applicable pH uble STABILITY AND REACTI table. Example	OPERTIES oration rate : Not fic Gravity: : Not density : Not r pressure : Not ur density : Not : Not VITY ents and open flame. To a	applicable determined established applicable applicable		



MATERIAL SAFETY DATA SHEET PG 55580.00 FROST RD PP

Version Number 1.0 Revision Date 06/18/2004

Page 4 of 6 Print Date 11/14/2011

Hazardous decomposition	:
products	

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ		
12001-26-2	Mica	Systemic effects	Respiratory system.		
	12. ECOLOGI	CAL INFORMATION	I		
Persistence and degrada	bility : Not readily b	viodegradable.			
Environmental Toxicity		: Chemicals are not readily available as they are bound within the polymer matrix.			
Bioaccumulation Poten		: Chemicals are not readily available as they are bound within the polymer matrix.			
Additional advice	: No data avail	: No data available			
	13. DISPOSAL	CONSIDERATIONS			
Product Contaminated packagin	g : Recycling is has the respo	cling is preferred to dis waste material has the r a, transportation and disp deral, state/provincial a preferred when possible nsibility for proper was in accordance with appl	product can be recycled. Where posal or incineration. The esponsibility for proper waste posal in accordance with nd local regulations. e. The generator of waste materia te classification, transportation licable federal, state/provincial		
	14. TRANSPO	ORT INFORMATION			
U.S. DOT Classification	n : Not regulated	d for transportation.			
ICAO/IATA (air)	: Refer to spec	ific regulation.			
IMO / IMDG (maritime	e) : Refer to spec	ific regulation.			
	15. REGULAT	ORY INFORMATION	1		

PolyOne.

MATERIAL SAFETY DATA SHEET PG 55580.00 FROST RD PP

/ersion Number 1.0 Revision Date 06/18/2004		Page 5 of 6 Print Date 11/14/2011
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous S	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	This product does not contain a substance listed by California Prop 65.
SARA Title III Section 302 Extr	em	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 Tox	ic C	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Releas	e Iı	nventory (NPRI)
Not applicable		
WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:		
Australia AICS	:	Listed
China IECS	:	Listed
Europe EINECS	:	Not determined
Japan ENCS	:	Not determined
Korea KECI	:	Listed
Philippines PICCS	:	Listed
		16. OTHER INFORMATION



MATERIAL SAFETY DATA SHEET PG 55580.00 FROST RD PP

Version Number 1.0 Revision Date 06/18/2004 Page 6 of 6 Print Date 11/14/2011

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.