

### MATERIAL SAFETY DATA SHEET

### MAX FRESH GREEN

Version Number 1.0 Revision Date 06/21/2004

Page 1 of 6 Print Date 11/14/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	MAX FRESH GREEN
Product code :	CC10055673
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Silica, amorphous	7631-86-9	1 - 5
Titanium dioxide	13463-67-7	10 - 30

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



## MATERIAL SAFETY DATA SHEET MAX FRESH GREEN

Version Number 1.0 Revision Date 06/21/2004 Page 2 of 6 Print Date 11/14/2011

		4. FIRST AID MEASURES
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
		5. FIRE-FIGHTING MEASURES
Flash point	:	Not applicable
Flammable Limits		
Upper explosion limit	•	Not applicable
sower explosion limit		Not applicable
Autoignition temperature	•	Not applicable
Suitable extinguishing media	:	Carbon dioxide blanket, water spray, dry powder, foamnone.
Special Fire Fighting Procedures	:	Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. A	CCIDENTAL RELEASE MEASURES
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption

2/6



# MATERIAL SAFETY DATA SHEET MAX FRESH GREEN

Version Number 1.0 Revision Date 06/21/2004 Page 3 of 6 Print Date 11/14/2011

: N : Sa : Pr : L : Sa : H W : H	afety glasses with s rotective gloves. ong sleeved clothin afety shoes. andle in accordance Vash hands before b	ory protecti ide-shields. g. e with good reaks and a ith appropri- ventilation a	ve equipment normally r industrial hygiene and sa at the end of workday. iate exhaust ventilation. at machinery. Exposure type	afety practice.
: Si : Pi : L : Si : H W : H ap <u>Value</u>	afety glasses with s rotective gloves. ong sleeved clothin afety shoes. (andle in accordance Vash hands before b feat only in areas wi opropriate exhaust v	g. e with good reaks and a ith appropri- ventilation a	industrial hygiene and sa it the end of workday. iate exhaust ventilation. at machinery. Exposure type	afety practice. Provide
: Pr : L : S : H W : H ap Value ) mppcf	rotective gloves. ong sleeved clothin afety shoes. fandle in accordance Vash hands before b feat only in areas wi opropriate exhaust v	g. e with good reaks and a ith appropri ventilation a	industrial hygiene and sa at the end of workday. iate exhaust ventilation. at machinery. Exposure type	Provide
: L : Sa : H W : H aş <u>Value</u> ) mppcf	ong sleeved clothin afety shoes. fandle in accordance Vash hands before b feat only in areas wi ppropriate exhaust v	e with good reaks and a ith appropri ventilation a	at the end of workday. Tate exhaust ventilation. Tat machinery. Exposure type	Provide
: Si : H W : H ap Value ) mppcf	afety shoes. andle in accordance Vash hands before b leat only in areas wi opropriate exhaust v Exposure ti	e with good reaks and a ith appropri ventilation a	at the end of workday. Tate exhaust ventilation. Tat machinery. Exposure type	Provide
: H W : H ap Value ) mppcf	andle in accordance Vash hands before b leat only in areas wi opropriate exhaust v Exposure ti	reaks and a ith appropri- ventilation a	at the end of workday. Tate exhaust ventilation. Tat machinery. Exposure type	Provide
W : H ap Value ) mppcf	Vash hands before b feat only in areas wi ppropriate exhaust v Exposure ti	reaks and a ith appropri- ventilation a	at the end of workday. Tate exhaust ventilation. Tat machinery. Exposure type	Provide
ap Value ) mppcf	ppropriate exhaust v Exposure ti	ventilation a	at machinery. Exposure type	
) mppcf	<u>^</u>	me		I ist <sup>.</sup>
) mppcf	<u>^</u>	me		List.
) mppcf	<u>^</u>			
			Total dust.	OSHA
mpper	PEL:		Total dust.	Z3
) mg/m3	Time Weighted	Average		ACGIH
	(TWA):			
5 mg/m3	PEL:		Total dust.	OSHA Z1
. PHYSIC	CAL AND CHEMI	ICAL PRO	PERTIES	
· Solid	1	Evanor	ration rate · Not	applicable
				determined
				established
. –				applicable
		*	*	applicable
: Not a	applicable	pH		applicable
: Insol	uble			
10. S	STABILITY AND	REACTIV	TTY	
: S1	table.			
: W	Vill not occur.			
			-	void thermal
	PHYSIC         : Solid         : Pelle         : GRE         : GRE         : Very         : Not a         : Insol         10. S         : W         : K	mg/m3       PEL:         PHYSICAL AND CHEMI         : Solid         : Pellets         : GREEN         : Very faint         : Not determined         : Not applicable         : Insoluble         10. STABILITY AND         : Stable.         : Will not occur.         : Keep away from oxide	mg/m3       PEL:         PHYSICAL AND CHEMICAL PRO         : Solid       Evapor         : Pellets       Specifi         : GREEN       Bulk d         : Very faint       Vapor         : Not determined       Vapou         : Not applicable       pH         : Insoluble       IO. STABILITY AND REACTIV         : Stable.       :         : Will not occur.       :         : Keep away from oxidizing agen	mg/m3       PEL:       Total dust.         PHYSICAL AND CHEMICAL PROPERTIES         : Solid       Evaporation rate       : Not         : Pellets       Specific Gravity:       : Not         : GREEN       Bulk density       : Not         : Very faint       Vapor pressure       : Not         : Not determined       Vapour density       : Not         : Insoluble       Insoluble       Insoluble         Io. STABILITY AND REACTIVITY       : Stable.



## MATERIAL SAFETY DATA SHEET MAX FRESH GREEN

#### Version Number 1.0 Page 4 of 6 Revision Date 06/21/2004 Print Date 11/14/2011 **Incompatible Materials** : Incompatible with strong acids and oxidizing agents. Hazardous decomposition : Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen products (NOx), other hazardous materials, and smoke are all possible. **11. TOXICOLOGICAL INFORMATION** This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture. Toxicity Overview This product contains the following components which in their pure form have the following characteristics: CAS-No. Chemical Name Effect Target Organ 7631-86-9 Silica, amorphous Eyes, Respiratory system. Irritant 13463-67-7 Titanium dioxide Systemic effects Respiratory system. **12. ECOLOGICAL INFORMATION** Persistence and degradability : Not readily biodegradable. Environmental Toxicity Chemicals are not readily available as they are bound within the : polymer matrix. **Bioaccumulation Potential** : Chemicals are not readily available as they are bound within the polymer matrix. Additional advice : No data available **13. DISPOSAL CONSIDERATIONS** Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. **14. TRANSPORT INFORMATION** U.S. DOT Classification : Not regulated for transportation. ICAO/IATA (air) : Refer to specific regulation. IMO / IMDG (maritime) : Refer to specific regulation.



## MATERIAL SAFETY DATA SHEET MAX FRESH GREEN

Version Number 1.0 Revision Date 06/21/2004

Page 5 of 6 Print Date 11/14/2011

	15	. REGULATORY INFORMATION
US Regulations:		
OSHA Status	:	Classified as hazardous based on components.
TSCA Status	:	All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Sub	stances (40 CFR 302)
Not applicable		
California Proposition 65	:	WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 Ext	trem	ely Hazardous Substance
Not applicable		
SARA Title III Section 313 To:	xic C	Chemicals:
Not applicable Canadian Regulations:		
National Pollutant Relea	ise Ir	nventory (NPRI)
National I offatant Refea		
Not applicable		
	:	Not controlled.
Not applicable	:	Not controlled. All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
Not applicable WHMIS Classification	:	All components of this product are on the Canadian Domestic
Not applicable WHMIS Classification DSL	:	All components of this product are on the Canadian Domestic
Not applicable WHMIS Classification DSL National Inventories:	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
Not applicable WHMIS Classification DSL National Inventories: Australia AICS	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. Listed
Not applicable WHMIS Classification DSL National Inventories: Australia AICS China IECS	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. Listed Listed



# MATERIAL SAFETY DATA SHEET

# MAX FRESH GREEN

Version Number 1.0 Revision Date 06/21/2004 Page 6 of 6 Print Date 11/14/2011

Philippines PICCS : Listed

### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.