

MATERIAL SAFETY DATA SHEET

TR. BLUE

Version Number 1.0 Revision Date 06/24/2004 Page 1 of 6 Print Date 11/14/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	TR. BLUE
Product code :	CC10055748
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl	57583-35-4	1 - 5
ester		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET

TR. BLUE

Version Number 1.0 Revision Date 06/24/2004 Page 2 of 6 Print Date 11/14/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

TR. BLUE

sion Number 1.0 ision Date 06/24/2004			Print I	Page 3 Date 11/14/2	
Handling		ake measures to prevent the bui nly in areas with appropriate exl		harge. Heat	
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8.]	EXPOSURE	CONTROLS / PERSONAL P	ROTECTION		
Respiratory protection	: N	o personal respiratory protective	e equipment normally	required.	
Eye/Face Protection	: S	afety glasses with side-shields.			
Hand protection	: P	rotective gloves.			
Skin and body protection : Long sleeved clothing.					
Additional Protective : Safety shoes. Measures					
General Hygiene:Handle in accordance with good industrial hygiene and safety practic Wash hands before breaks and at the end of workday.					
Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
8-Oxa-3,5-dithia-4-sta nnatetradecanoic acid, 10-ethyl-4,4-dimethyl- 7-oxo-, 2-ethylhexyl ester	0.1 mg/m3	PEL:	as Sn	OSHA Z1	
	0.1 mg/m3	Time Weighted Average (TWA):	as Sn	ACGIH	
	0.2 mg/m3	Short Term Exposure Limit (STEL):	as Sn	ACGIH	

- Form Appearance Color Odor Melting point/range Boiling Point: Water solubility
- BLUEVery faintNot determinedNot applicableInsoluble

: Solid

: Pellets

- Evaporation rate Specific Gravity: Bulk density Vapor pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 Not applicable
 Not applicable
 Not applicable
- **10. STABILITY AND REACTIVITY**
 - 3/6



MATERIAL SAFETY DATA SHEET **TR. BLUE**

Version Number 1.0 Revision Date 06/24/2004

Page 4 of 6 Print Date 11/14/2011

Stability	:	Stable.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	C	Chemical Nam		Effect	Target Organ	
57583-35-4	8-Oxa-3,5-dithia-4-stannat etradecanoic acid, 10-ethyl-4,4-dimethyl-7-o xo-, 2-ethylhexyl ester		Irritant	Eyes, Skin.		
		12. E(COLOGICA	L INFORMATIO	DN	
Persistence and deg	radability	: No	t readily biod	degradable.		
Environmental Toxicity Bioaccumulation Potential		: Chemicals are not readily available as they are bound within the polymer matrix.				
		: Chemicals are not readily available as they are bound within the polymer matrix.				
Additional advice		: No	data availab	le		
		13. D	ISPOSAL C	ONSIDERATION	NS	



MATERIAL SAFETY DATA SHEET TR. BLUE

R. BLUE					
ersion Number 1.0 evision Date 06/24/2004	Page 5 of Print Date 11/14/201				
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.				
	14. TRANSPORT INFORMATION				
U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA (air)	: Refer to specific regulation.				
IMO / IMDG (maritime)	: Refer to specific regulation.				
	15. REGULATORY INFORMATION				
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous	Substances (40 CFR 302)				
Not applicable					
California Proposition 65	: WARNING! This product contains a chemical known to the State of California to cause cancer.				
SARA Title III Section 302 Ex	tremely Hazardous Substance				
Not applicable					
SARA Title III Section 313 Toxic Chemicals:					
Not applicable Canadian Regulations:					
National Pollutant Relea	ase Inventory (NPRI)				
	5/6				



MATERIAL SAFETY DATA SHEET

TR. BLUE

Version Number 1.0 Revision Date 06/24/2004 Page 6 of 6 Print Date *11/14/2011*

	Not applicable		
	WHMIS Classification	:	D2B
WHMIS Ingredient Disclosure List			
	CAS-No. 57583-35-4		
	DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
	National Inventories:		
	Australia AICS	:	Not determined
	China IECS	:	Listed
	Europe EINECS	:	Not determined
	Japan ENCS	:	Not determined
	Korea KECI	:	Not determined
	Philippines PICCS	:	Listed
			16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.