PolvOne

MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014

Page 1 of 7 Print Date 3/18/2014

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	030RD421 MUNSELL RED PVC HMF CC
Product code	:	CC10055803
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
C.I. Pigment red 48, calcium salt	7023-61-2	1 - 5
Benzenesulfonic acid, 5-chloro-2-[(2-	5160-02-1	1 - 5
hydroxy-1-naphthalenyl)azo]-4-methyl-,		
barium salt (2:1)		
Calcium carbonate	1317-65-3	10 - 30
Iron oxide	1309-37-1	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014 Page 2 of 7 Print Date 3/18/2014

Chronic exposure	
	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media	 not applicable not applicable not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam.
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014 Page 3 of 7 Print Date 3/18/2014

Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
		7. HANDLING AND STORAGE
Handling	:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EX	POSUI	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Γ_{1}		

Exposure limit(s)

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
Iron oxide	10 mg/m3	PEL:	Fume.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	as Fe	MX OEL
	10 mg/m3	Short Term Exposure Limit (STEL):	as Fe	MX OEL
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	ACGIH

9. PHYSICAL AND CHEMICAL PROPERTIES

MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014 Page 4 of 7 Print Date 3/18/2014

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets RED very faint Not determined not applicable insoluble 	Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	 Not applicable Not determined Not established not applicable not applicable not applicable
	10. STABILITY ANI	D REACTIVITY	
Stability	: The product is stab	le if stored and handled as	prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open fla not overheat.	ame. To avoid thermal
Incompatible Materials	or acetal copolyme processing. At pro destructive and inv mechanically clean quantities of these	strong oxidizers. Also, av rs and with amine containing cessing conditions, these molve rapid degradation. The processing equipment to a materials from coming in comination of feedstocks.	ng materials during naterials are mutually noroughly purge and woid even trace
Hazardous decomposition products	(NOx), hydrogen c smoke are all possi or more) above 392	O2), carbon monoxide (CO hloride (HCl), other hazard ble. Prolonged heating (ap 2 °F (200 °C) or short term roduct decomposition and o rogen chloride.	lous materials, and proximately 30 minutes heating at 482 °F (250

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

<u>Toxicity Overview</u> This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
7023-61-2	C.I. Pigment red 48,	Irritant	Eyes, Skin, Respiratory
	calcium salt		system.
		Toxic	digestive system.
5160-02-1	Benzenesulfonic acid, 5- chloro-2-[(2-hydroxy-1- naphthalenyl)azo]-4- methyl-, barium salt (2:1)	Irritant	Eyes, Skin.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.



MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014 Page 5 of 7 Print Date 3/18/2014

			Systemic effects	Eyes, Skin, Respiratory system.	
1309-37-1	Iron oxide		Systemic effects	Respiratory system.	
	1	2. ECOLOGI	CAL INFORMATION	N	
Persistence and de	gradability :	Not readily I	biodegradable.		
Environmental To	xicity :	Chemicals a polymer mat		as they are bound within the	
Bioaccumulation I	Potential :	Chemicals a polymer mat		as they are bound within the	
Additional advice	:	no data avai	lable		
	1	3. DISPOSAI	L CONSIDERATIONS	9	
Product	:	possible recy generator of classification	ycling is preferred to dis waste material has the 1	product can be recycled. Where posal or incineration. The responsibility for proper waste posal in accordance with nd local regulations.	
Contaminated packaging		Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.			
]	14. TRANSPO	ORT INFORMATION		
U.S. DOT Classifi	cation :	Not regulate	d for transportation.		
ICAO/IATA	:	Refer to spe	Refer to specific regulation.		
IMO/IMDG (mari	time) :	Refer to spe	Refer to specific regulation.		
	1	5. REGULAT	ORY INFORMATIO	N	
US Regulations:					
OSHA Sta	tus :	Classified as	s hazardous based on co	mponents.	
		All components of this product are listed on or exempt from the TSCA Inventory.			
US. EPA CERCL	A Hazardous Sub	stances (40 Cl	FR 302)		
not ap	plicable				

Poly<u>One</u>

MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014

Page 6 of 7 Print Date 3/18/2014

California Proposition : WARNING! This product contains a chemical known to the State of 65 California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
BARIUM COMPOUNDSBARIUM COMPOUNDS	5160-02-1	1.00 - 5.00
[EXCEPT BASO4]		

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Zinc stearate	557-05-1	0.10 - 1.00	

WHMIS Classification	:	Not controlled.
DSL	:	All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
tional Inventories:		

Nat

Australia AICS	:	Listed

- China IECS : Listed
- Europe EINECS : Listed
- Japan ENCS : Not determined
- Korea KECI : Listed
- **Philippines PICCS** : Listed

16. OTHER INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET 030RD421 MUNSELL RED PVC HMF CC

Version Number 1.3 Revision Date 03/12/2014 Page 7 of 7 Print Date 3/18/2014

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.