

### MATERIAL SAFETY DATA SHEET

### PINK PNT. 219C

Version Number 1.0 Revision Date 07/09/2004

Page 1 of 6 Print Date 11/15/2011

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	PINK PNT. 219C
Product code :	CC10056225
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	5 - 10
Calcium carbonate	1317-65-3	10 - 30

#### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	<ul> <li>Resin particles, like other inert materials, can be mechanically irritating.</li> <li>May be harmful if swallowed.</li> <li>Resin particles, like other inert materials, are mechanically irritating to eves.</li> </ul>
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.



## MATERIAL SAFETY DATA SHEET PINK PNT. 219C

Version Number 1.0 Revision Date 07/09/2004 Page 2 of 6 Print Date 11/15/2011

	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all case doubt seek medical advice.	s of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	;
Eyes	: Rinse immediately with plenty of water, also under the eyelids, fo least 15 minutes. If eye irritation persists, seek medical attention.	r at
Skin	: Wash off with soap and plenty of water. If skin irritation persists medical attention.	seel
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable</li> </ul>	
Suitable extinguishing media	: Carbon dioxide blanket, water spray, dry powder, foamnone.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positi pressure mode should be worn to prevent inhalation of airborne contaminants.	ve
Unusual Fire/Explosion Hazards	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.	÷
	. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should be allowed to enter drains, water courses or the soil.	not
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material plastic, cardboard or metal containers for disposal. Refer to Sectio of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. Here only in areas with appropriate exhaust ventilation.	ıt
Storage	: Keep containers dry and tightly closed to avoid moisture absorption	m

2/6



## MATERIAL SAFETY DATA SHEET PINK PNT. 219C

Version Number 1.0 Revision Date 07/09/2004 Page 3 of 6 Print Date 11/15/2011

afety glasses with side-shiel rotective gloves. ong sleeved clothing. afety shoes. landle in accordance with go Vash hands before breaks and leat only in areas with appro ppropriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	ective equipment normally required.         lds.         ood industrial hygiene and safety practice         od at the end of workday.         opriate exhaust ventilation. Provide         on at machinery.         Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         Total dust.       OSHA Z1
afety glasses with side-shiel rotective gloves. ong sleeved clothing. afety shoes. landle in accordance with go Vash hands before breaks and leat only in areas with appro ppropriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	Ids.       bod industrial hygiene and safety practice       id at the end of workday.       opriate exhaust ventilation. Provide       on at machinery.       Exposure type     List:       Respirable fraction.     OSHA Z1       Total dust.     OSHA Z1       Total dust.     OSHA Z1
rotective gloves. oong sleeved clothing. afety shoes. Iandle in accordance with go Vash hands before breaks and leat only in areas with appro ppropriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	pood industrial hygiene and safety practice         id at the end of workday.         opriate exhaust ventilation. Provide         on at machinery.         Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         Total dust.       OSHA Z1
ong sleeved clothing. afety shoes. Iandle in accordance with go Vash hands before breaks and leat only in areas with appro propriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	ad at the end of workday.         opriate exhaust ventilation.         provide         on at machinery.         Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
afety shoes. Iandle in accordance with go Vash hands before breaks and leat only in areas with appro ppropriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	ad at the end of workday.         opriate exhaust ventilation.         provide         on at machinery.         Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
landle in accordance with go Vash hands before breaks and leat only in areas with appro ppropriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	ad at the end of workday.         opriate exhaust ventilation.         provide         on at machinery.         Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
Vash hands before breaks and leat only in areas with appro ppropriate exhaust ventilation Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	ad at the end of workday.         opriate exhaust ventilation.         provide         on at machinery.         Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
ppropriate exhaust ventilatio Exposure time PEL: PEL: Time Weighted Average (TWA): PEL:	Exposure type       List:         Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
PEL: PEL: Time Weighted Average (TWA): PEL:	Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
PEL: PEL: Time Weighted Average (TWA): PEL:	Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
PEL: PEL: Time Weighted Average (TWA): PEL:	Respirable fraction.       OSHA Z1         Total dust.       OSHA Z1         ACGIH         Total dust.       OSHA Z1
Time Weighted Average (TWA): PEL:	Total dust.     OSHA Z1       ACGIH       Total dust.       OSHA Z1
(TWA): PEL:	Total dust. OSHA Z1
(TWA): PEL:	Total dust. OSHA Z1
	ROPERTIES
CAL AND CHEMICAL PI	
l Eva	poration rate : Not applicable
	cific Gravity: : Not determined
	k density : Not established
	or pressure : Not established
	our density : Not applicable
applicable pH	: Not applicable
luble	. Not applicable
STABILITY AND REACT	TIVITY
table.	
Vill not occur.	
	gents and open flame. To avoid thermal
5	Stable. Will not occur.



# MATERIAL SAFETY DATA SHEET **PINK PNT. 219C**

## Version Number 1.0 Revision Date 07/09/2004

Page 4 of 6 Print Date 11/15/2011

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

**Toxicity Overview** 

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.



## MATERIAL SAFETY DATA SHEET PINK PNT. 219C

Version Number 1.0 Page 5 of 6 Revision Date 07/09/2004 Print Date 11/15/2011 IMO / IMDG (maritime) : Refer to specific regulation. **15. REGULATORY INFORMATION US Regulations: OSHA Status** : Classified as hazardous based on components. **TSCA Status** All components of this product are listed on or exempt from the TSCA : Inventory. US. EPA CERCLA Hazardous Substances (40 CFR 302) Not applicable California Proposition WARNING! This product contains a chemical known to the State of : 65 California to cause cancer. SARA Title III Section 302 Extremely Hazardous Substance Not applicable SARA Title III Section 313 Toxic Chemicals: Not applicable Canadian Regulations: National Pollutant Release Inventory (NPRI) Not applicable WHMIS Classification : Not controlled. DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Listed : China IECS Listed : Europe EINECS : Listed Japan ENCS : Listed Korea KECI ÷ Listed

	POLYONE	CORPORATION
--	---------	-------------



# MATERIAL SAFETY DATA SHEET

## PINK PNT. 219C

Version Number 1.0 Revision Date 07/09/2004 Page 6 of 6 Print Date 11/15/2011

Philippines PICCS :

: Listed

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.