MATERIAL SAFETY DATA SHEET 030BU563 PVC CC HMF BLUE 1127

Version Number 1.0 Revision Date 07/30/2004 Page 1 of 6 Print Date *11/15/2011*

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	030BU563 PVC CC HMF BLUE 1127
Product code :	CC10056290
Chemical Name :	Mixture
CAS-No. :	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

Components	CAS-No.	Weight %
Aluminate (Al(OH)63-), (OC-6-11)-,	11097-59-9	1 - 5
magnesium carbonate hydroxide (2:6:1:4)		
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Particulates, like other inert materials can be mechanically irritating. Excessive inhalation of product vapors, especially during heating or processing, may be irritating to respiratory system.
Ingestion	: May be harmful if swallowed.
Eyes	: Particulates, like other inert materials can be mechanically irritating.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.



MATERIAL SAFETY DATA SHEET 030BU563 PVC CC HMF BLUE 1127

Version Number 1.0 Revision Date 07/30/2004 Page 2 of 6 Print Date 11/15/2011

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 12 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET 030BU563 PVC CC HMF BLUE 1127

Version Number 1.0			
Revision Date 07/30/2004			

Page 3 of 6 Print Date 11/15/2011

Handling	: Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.				
Storage		eep containers dry and tight ad contamination. Keep in a		e absorption	
8. H	EXPOSURE	CONTROLS / PERSONA	L PROTECTION		
Respiratory protection	: N	o personal respiratory protec	ctive equipment normally r	required.	
Eye/Face Protection	: S	: Safety glasses with side-shields.			
Hand protection	: P	: Protective gloves.			
Skin and body protection	: L	: Long sleeved clothing.			
Additional Protective Measures	: Safety shoes.				
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.				
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.				
Exposure limit(s)					
Components	Value	Exposure time	Exposure type	List:	
Aluminate	2 mg/m3	Time Weighted Average	as Al	ACGIH	
(Al(OH)63-), (OC-6-11)-, magnesium carbonate bydrogida (2)6(1)(4)		(TWA):			
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	5 mg/m3		Respirable fraction		
(OC-6-11)-, magnesium carbonate	5 mg/m3 15 mg/m3	PEL:	Respirable fraction. Total dust.	OSHA Z1	
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	15 mg/m3	PEL: PEL:	Total dust.	OSHA Z1	
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4)	15 mg/m3	PEL:	Total dust.	OSHA Z1	
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4) Calcium carbonate Calcium carbonate	15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c	PEL: PEL: CAL AND CHEMICAL PE E E Spec E Bulk faint Vapo letermined Vapo	Total dust. COPERTIES poration rate : Not ific Gravity: : Not density : Not or pressure : Not our density : Not	OSHA Z1 OSHA Z1 applicable determined established applicable applicable	
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4) Calcium carbonate Form Appearance Color Odor	15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c	PEL: PEL: CAL AND CHEMICAL PH ts Spec E Bulk faint Vapo letermined Vapo upplicable pH	Total dust. COPERTIES poration rate : Not ific Gravity: : Not density : Not or pressure : Not our density : Not	OSHA Z1 OSHA Z1 applicable determined established applicable	
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4) Calcium carbonate Calcium carbonate	15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not c : Insol	PEL: PEL: CAL AND CHEMICAL PH ts Spec E Bulk faint Vapo letermined Vapo upplicable pH	Total dust. COPERTIES poration rate : Not ific Gravity: : Not density : Not por pressure : Not pour density : Not : Not	OSHA Z1 OSHA Z1 applicable determined established applicable applicable	
(OC-6-11)-, magnesium carbonate hydroxide (2:6:1:4) Calcium carbonate Calcium carbonate	15 mg/m3 9. PHYSIC : Solid : Pelle : BLU : Very : Not c : Not a : Insol 10. S	PEL: PEL: CAL AND CHEMICAL PE ts Spec E Bulk faint Vapo letermined Vapo upplicable pH uble	Total dust. COPERTIES poration rate : Not ific Gravity: : Not density : Not por pressure : Not pour density : Not : Not	OSHA Z1 OSHA Z1 applicable determined established applicable applicable	



MATERIAL SAFETY DATA SHEET 030BU563 PVC CC HMF BLUE 1127

Version Number 1.0 Revision Date 07/30/2004 Page 4 of 6 Print Date 11/15/2011

Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Avoid contact with strong oxidizers. Also, avoid contact with acetal or acetal copolymers and with amine containing materials during processing. At processing conditions, these materials are mutually destructive and involve rapid degradation. Thoroughly purge and mechanically clean processing equipment to avoid even trace quantities of these materials from coming in contact with each other. Prevent cross contamination of feedstocks.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), hydrogen chloride (HCl), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

11097-59-9 1317-65-3 Persistence and degrad	(OC-6-11 carbonate (2:6:1:4) Calcium o	e (Al(OH)63-),)-, magnesium hydroxide carbonate 12. ECOLOGIC	Irritant Irritant Systemic effects	Eyes, Skin. Eyes, Skin. Eyes, Skin, Respiratory system.
			Systemic effects	Eyes, Skin, Respiratory system.
Persistence and degrad		12. ECOLOGIC		
Persistence and degrad		12. ECOLOGIC	AL INFORMATION	
r ersistenee und degrad	aomty .	Not readily bit	degradable.	
r ersistenee und degrad	ability :	Not readily bio	odegradable.	
polymer matrix		•	as they are bound within the	
		•	as they are bound within the	
Additional advice	:	No data availa	ble	
		13. DISPOSAL (CONSIDERATIONS	5



MATERIAL SAFETY DATA SHEET 030BU563 PVC CC HMF BLUE 1127

sion Number 1.0 ision Date 07/30/2004	Page 5 0 Print Date 11/15/20
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
Not applicable	
California Propositio 65	• : WARNING! This product contains a chemical known to the State of California to cause cancer.
SARA Title III Section 302 I	Extremely Hazardous Substance
Not applicable	
SARA Title III Section 313	'oxic Chemicals:
Not applicable Canadian Regulations:	
National Pollutant Re	ease Inventory (NPRI)



MATERIAL SAFETY DATA SHEET 030BU563 PVC CC HMF BLUE 1127

Version Number 1.0

Revision Date 07/30/2004

Page 6 of 6 Print Date 11/15/2011

Chemical Name	CAS-No.	Weight %	NPRI ID#
Phthalocyanine blue	147-14-8	2.77	70
Zinc stearate	557-05-1	0.25	241

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.
11097-59-9
147-14-8

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

Australia AICS	: Listed
China IECS	: Listed
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Listed
Philippines PICCS	: Listed

·

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.