MATERIAL SAFETY DATA SHEET KELLY GREEN PRECOLOR

Version Number 1.0 Revision Date 07/23/2004

Page 1 of 5 Print Date 11/15/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone:Emergency telephone:number	Product Stewardship (770) 271-5902 CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name :	KELLY GREEN PRECOLOR
Product code :	CC10056395
Chemical Name :	Mixture
CAS-No.	Mixture
Product Use :	Industrial Applications

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes Skin	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes. Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure Medical Conditions Aggravated by Exposure:	Refer to Section 11 for Toxicological Information.None known.
	4. FIRST AID MEASURES



MATERIAL SAFETY DATA SHEET KELLY GREEN PRECOLOR

sion Date 07/23/2004	Print Date 1	age 2 1/15/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all ca doubt seek medical advice.	
Ingestion	: Do not induce vomiting without medical advice. When symptopersist or in all cases of doubt seek medical advice.	oms
Eyes	: Rinse immediately with plenty of water, also under the eyelids, least 15 minutes. If eye irritation persists, seek medical attention	
Skin	: Wash off with soap and plenty of water. If skin irritation persis medical attention.	ts see
	5. FIRE-FIGHTING MEASURES	
Flash point	: Not applicable	
Flammable Limits Upper explosion limit sower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable Carbon dioxide blanket, water spray, dry powder, foamnone. 	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in por pressure mode should be worn to prevent inhalation of airborne	
Unusual Fire/Explosion Hazards	 contaminants. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrog (NOx), other hazardous materials, and smoke are all possible. 	gen
	ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product shou be allowed to enter drains, water courses or the soil.	ld no
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all materi plastic, cardboard or metal containers for disposal. Refer to Sec of this MSDS for proper disposal methods.	
	7. HANDLING AND STORAGE	
Handling	: Take measures to prevent the build up of electrostatic charge. I only in areas with appropriate exhaust ventilation.	Heat
Storage	: Keep containers dry and tightly closed to avoid moisture absorpt and contamination. Keep in a dry, cool place.	otion

PolyOne.

MATERIAL SAFETY DATA SHEET KELLY GREEN PRECOLOR

Version Number 1.0 Revision Date 07/23/2004 Page 3 of 5 Print Date 11/15/2011

Respiratory protection	: No personal respir	atory protective equipment normally required.
Eye/Face Protection	: Safety glasses with	n side-shields.
Hand protection	: Protective gloves.	
Skin and body protection	: Long sleeved cloth	ing.
Additional Protective Measures	: Safety shoes.	
General Hygiene Considerations		nce with good industrial hygiene and safety practice breaks and at the end of workday.
Engineering measures		with appropriate exhaust ventilation. Provide st ventilation at machinery.
Exposure limit(s)		
9.	PHYSICAL AND CHEN	MICAL PROPERTIES
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Solid Pellets GREEN Very faint Not determined Not applicable Insoluble 	Evaporation rate:Not applicableSpecific Gravity::Not determinedBulk density:Not establishedVapor pressure:Not applicableVapour density:Not applicablepH:Not applicable
	10. STABILITY AN	D REACTIVITY
Stability	: Stable.	
Hazardous Polymerization	: Will not occur.	
Conditions to avoid	: Keep away from o decomposition, do	xidizing agents and open flame. To avoid thermal not overheat.
Incompatible Materials	: Incompatible with	strong acids and oxidizing agents.
Hazardous decomposition products		O2), carbon monoxide (CO), oxides of nitrogen rdous materials, and smoke are all possible.
		L INFORMATION

PolyOne

MATERIAL SAFETY DATA SHEET KELLY GREEN PRECOLOR

Version Number 1.0 Revision Date 07/23/2004 Page 4 of 5 Print Date 11/15/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential	: Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice	: No data available
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	Not accorded for the second station
	: Not regulated for transportation.
ICAO/IATA (air)	: Refer to specific regulation.
IMO / IMDG (maritime)	: Refer to specific regulation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardous	Substances (40 CFR 302)
Not applicable	

PolyOne

MATERIAL SAFETY DATA SHEET KELLY GREEN PRECOLOR

Version Number 1.0 Revision Date 07/23/2004 Page 5 of 5 Print Date 11/15/2011

California Proposition : WARNING! This product contains a chemical known to the State of California to cause cancer.				
SARA Title III Section 302 Extremely Hazardous Substance				
Not applicable				
SARA Title III Section 313 Toxic Chemicals:				
Not applicable Canadian Regulations:				
National Pollutant Release Inventory (NPRI)				
Not applicable				
WHMIS Classification : Not controlled.				
DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
National Inventories:				
Australia AICS : Not determined				
China IECS : Not determined				
Europe EINECS : Listed				
Japan ENCS : Not determined				
Korea KECI : Not determined				
Philippines PICCS : Not determined				
 16. OTHER INFORMATION				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material when used in combination with any other materials and/or in any particular process or processing conditions.